

**STAINLESS STEEL CARE SPRAY, 342 g**

Version 5.4      Revision Date: 11/09/2020      SDS Number: 1627868-00005      Date of last issue: 05/06/2020  
Date of first issue: 12/23/2009

---

**SECTION 1. IDENTIFICATION**

Product name : STAINLESS STEEL CARE SPRAY, 342 g  
Product code : 893.121  
Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Detergent  
Cleaning agent  
Care product

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Specific target organ toxicity : Category 3  
- single exposure

**GHS label elements**

**STAINLESS STEEL CARE SPRAY, 342 g**

Version 5.4      Revision Date: 11/09/2020      SDS Number: 1627868-00005      Date of last issue: 05/06/2020  
 Date of first issue: 12/23/2009

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H336 May cause drowsiness or dizziness.

Precautionary Statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing spray.  
 P271 Use only outdoors or in a well-ventilated area.

**Response:**

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

**Storage:**

P405 Store locked up.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Isobutane	75-28-5	>= 10 - < 30 *
White mineral oil (petroleum)	8042-47-5	>= 10 - < 30 *
Propane	74-98-6	>= 1 - < 5 *
Butane	106-97-8	>= 1 - < 5 *

\* Actual concentration or concentration range is withheld as a trade secret

---

**SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.

**STAINLESS STEEL CARE SPRAY, 342 g**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
5.4	11/09/2020	1627868-00005	Date of first issue: 12/23/2009

---

- When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

**STAINLESS STEEL CARE SPRAY, 342 g**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
5.4	11/09/2020	1627868-00005	Date of first issue: 12/23/2009

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Avoid breathing spray.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.

**STAINLESS STEEL CARE SPRAY, 342 g**

Version 5.4      Revision Date: 11/09/2020      SDS Number: 1627868-00005      Date of last issue: 05/06/2020  
 Date of first issue: 12/23/2009

Take care to prevent spills, waste and minimize release to the environment.  
 Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Do not pierce or burn, even after use.  
 Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:  
 Self-reactive substances and mixtures  
 Organic peroxides  
 Oxidizing agents  
 Flammable solids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Substances and mixtures which in contact with water emit flammable gases  
 Explosives

Recommended storage temperature : 10 - 40 °C

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
Isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL	
			TWA	1,000 ppm	CA BC OEL
			STEL	1,000 ppm	ACGIH
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL	
			STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
			TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
			STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
			TWA (Mist)	1 mg/m <sup>3</sup>	CA BC OEL
Propane	74-98-6	TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH	
			TWA	1,000 ppm	CA AB OEL
			TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL
Butane	106-97-8		TWA	1,000 ppm	CA AB OEL
			TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
			TWA	1,000 ppm	CA BC OEL
			STEL	1,000 ppm	ACGIH

**STAINLESS STEEL CARE SPRAY, 342 g**

Version 5.4      Revision Date: 11/09/2020      SDS Number: 1627868-00005      Date of last issue: 05/06/2020  
Date of first issue: 12/23/2009

---

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

**Personal protective equipment**

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

## Hand protection

Material : Nitrile rubber  
Break through time : 480 min

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety glasses  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : aerosol

Propellant : Isobutane, Propane, Butane

Color : white

**STAINLESS STEEL CARE SPRAY, 342 g**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
5.4	11/09/2020	1627868-00005	Date of first issue: 12/23/2009

---

Odor : aromatic

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 11 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : 0.95 g/cm<sup>3</sup> (20 °C)  
Method: DIN 51757

Solubility(ies)  
Water solubility : completely soluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

**STAINLESS STEEL CARE SPRAY, 342 g**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
5.4	11/09/2020	1627868-00005	Date of first issue: 12/23/2009

---

**SECTION 10. STABILITY AND REACTIVITY**

- Reactivity : Not classified as a reactivity hazard.
- Chemical stability : Stable under normal conditions.
- Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.
- Conditions to avoid : Heat, flames and sparks.
- Incompatible materials : Oxidizing agents
- Hazardous decomposition products : No hazardous decomposition products are known.
- 

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Isobutane:**

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm  
Exposure time: 4 h  
Test atmosphere: gas

**White mineral oil (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min



**STAINLESS STEEL CARE SPRAY, 342 g**

Version 5.4      Revision Date: 11/09/2020      SDS Number: 1627868-00005      Date of last issue: 05/06/2020  
Date of first issue: 12/23/2009

---

Test atmosphere: gas

**Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Species : Rabbit  
Result : No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Species : Rabbit  
Result : No eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Isobutane:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo)

## STAINLESS STEEL CARE SPRAY, 342 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
5.4	11/09/2020	1627868-00005	Date of first issue: 12/23/2009

---

cytogenetic assay)  
 Species: Rat  
 Application Route: inhalation (gas)  
 Method: OECD Test Guideline 474  
 Result: negative  
 Remarks: Based on data from similar materials

### White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
 cytogenetic assay)  
 Species: Mouse  
 Application Route: Intraperitoneal injection  
 Method: OECD Test Guideline 474  
 Result: negative  
 Remarks: Based on data from similar materials

### Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
 cytogenetic assay)  
 Species: Rat  
 Application Route: inhalation (gas)  
 Method: OECD Test Guideline 474  
 Result: negative

### Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
 cytogenetic assay)  
 Species: Rat  
 Application Route: inhalation (gas)  
 Method: OECD Test Guideline 474  
 Result: negative  
 Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

### Components:

#### White mineral oil (petroleum):

Species : Rat  
 Application Route : Ingestion  
 Exposure time : 24 Months  
 Result : negative

**STAINLESS STEEL CARE SPRAY, 342 g**

Version            Revision Date:            SDS Number:            Date of last issue: 05/06/2020  
5.4                11/09/2020                1627868-00005            Date of first issue: 12/23/2009

---

**Reproductive toxicity**

Not classified based on available information.

**Components:****Isobutane:**

Effects on fertility            :    Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development    :    Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**White mineral oil (petroleum):**

Effects on fertility            :    Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Skin contact  
Result: negative

Effects on fetal development    :    Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

**Propane:**

Effects on fertility            :    Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development    :    Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Butane:**

Effects on fertility            :    Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)

**STAINLESS STEEL CARE SPRAY, 342 g**

Version 5.4      Revision Date: 11/09/2020      SDS Number: 1627868-00005      Date of last issue: 05/06/2020  
Date of first issue: 12/23/2009

---

Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**STOT-single exposure**

May cause drowsiness or dizziness.

**Components:****Isobutane:**

Assessment : May cause drowsiness or dizziness.

**Propane:**

Assessment : May cause drowsiness or dizziness.

**Butane:**

Assessment : May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Components:****Isobutane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**White mineral oil (petroleum):**

Species : Rat  
LOAEL : > 160 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
LOAEL : >= 1 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 4 Weeks  
Method : OECD Test Guideline 412

**Propane:**

Species : Rat  
NOAEL : 7.214 mg/l

## STAINLESS STEEL CARE SPRAY, 342 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
5.4	11/09/2020	1627868-00005	Date of first issue: 12/23/2009

---

Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Aspiration toxicity**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****White mineral oil (petroleum):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l  
Exposure time: 28 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1,000 mg/l  
Exposure time: 21 d

**Persistence and degradability****Components:****Isobutane:**

## STAINLESS STEEL CARE SPRAY, 342 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
5.4	11/09/2020	1627868-00005	Date of first issue: 12/23/2009

---

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**White mineral oil (petroleum):**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d

**Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2.8

**Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.31

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources

**STAINLESS STEEL CARE SPRAY, 342 g**

Version      Revision Date:      SDS Number:      Date of last issue: 05/06/2020  
5.4            11/09/2020            1627868-00005      Date of first issue: 12/23/2009

---

of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty  
(including propellant)

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number                    : UN 1950  
Proper shipping name        : AEROSOLS  
Class                         : 2.1  
Packing group                : Not assigned by regulation  
Labels                        : 2.1

**IATA-DGR**

UN/ID No.                    : UN 1950  
Proper shipping name        : Aerosols, flammable  
Class                         : 2.1  
Packing group                : Not assigned by regulation  
Labels                        : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number                    : UN 1950  
Proper shipping name        : AEROSOLS  
  
Class                         : 2.1  
Packing group                : Not assigned by regulation  
Labels                        : 2.1  
EmS Code                     : F-D, S-U  
Marine pollutant             : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number                    : UN 1950  
Proper shipping name        : AEROSOLS  
  
Class                         : 2.1  
Packing group                : Not assigned by regulation  
Labels                        : 2.1  
ERG Code                     : 126  
Marine pollutant             : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

## STAINLESS STEEL CARE SPRAY, 342 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
5.4	11/09/2020	1627868-00005	Date of first issue: 12/23/2009

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content** CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 24.43 %

**The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

### SECTION 16. OTHER INFORMATION

**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Develop-



## STAINLESS STEEL CARE SPRAY, 342 g

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
5.4	11/09/2020	1627868-00005	Date of first issue: 12/23/2009

---

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/09/2020  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8