

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version 1.1 Revision Date: 03/24/2025 SDS Number: 11519062-00002 Date of last issue: 03/14/2025
Date of first issue: 03/14/2025

SECTION 1. IDENTIFICATION

Product name : IRON FALLOUT REMOVER, 475 mL
Product code : 893.160021
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : 1-800-263-5002
Telefax : 1-905-564-3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Urgences impliquant un déversement, incendie, explosion ou
exposition: CHEMTREC (24/7): 1-800-424-9300
E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use


Recommended use : Automotive
Detergent
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Acute toxicity (Oral) : Category 4
Skin sensitization : Sub-category 1B

GHS label elements

Hazard pictograms : 

Signal Word : Warning

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version 1.1 Revision Date: 03/24/2025 SDS Number: 11519062-00002 Date of last issue: 03/14/2025
Date of first issue: 03/14/2025

Hazard Statements : H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.

Response:
P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
(2-Hydroxyethyl)ammonium mercaptoacetate	Acetic acid, mercapto-, compd. with 2-aminoethanol (1:1)	126-97-6	$\geq 10 - < 30$ *
Alcohols, C12-14, ethoxylated	No data available	68439-50-9	$\geq 1 - < 5$ *
2-Butoxyethanol	1-Butoxy-2-hydroxyethan	111-76-2	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2025
1.1	03/24/2025	11519062-00002	Date of first issue: 03/14/2025

- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Get medical attention.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
May cause an allergic skin reaction.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Not applicable
Will not burn
- Unsuitable extinguishing media : Not applicable
Will not burn
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Sulfur oxides
Nitrogen oxides (NOx)
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2025
1.1	03/24/2025	11519062-00002	Date of first issue: 03/14/2025

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing. Avoid breathing mist or vapors. Do not swallow. Avoid contact with eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment. Do not eat, drink or smoke when using this product. Take care to prevent spills, waste and minimize release to the environment.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version 1.1 Revision Date: 03/24/2025 SDS Number: 11519062-00002 Date of last issue: 03/14/2025
Date of first issue: 03/14/2025

- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
(2-Hydroxyethyl)ammonium mercaptoacetate	126-97-6	TWA	1 ppm	ACGIH
2-Butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-Butoxyethanol	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI

- Engineering measures** : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

- Filter type : Combined particulates and organic vapor type

Hand protection

- Material : PVC
Break through time : > 480 min
Glove thickness : 0.35 mm

- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to che-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2025
1.1	03/24/2025	11519062-00002	Date of first issue: 03/14/2025

- micals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : colorless
- Odor : citrus, slight, sulfurous
- Odor Threshold : No data available
- pH : 5.5
Concentration: 100 %
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : 100 °C
- Flash point : does not flash
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable
- Flammability (liquids) : Will not burn
- Upper explosion limit / Upper : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2025
1.1	03/24/2025	11519062-00002	Date of first issue: 03/14/2025

flammability limit

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : 32 hPa (25 °C)

Relative vapor density : No data available

Relative density : 1.05

Density : 1 g/cm³

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 230 °C

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : None known.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition products : No hazardous decomposition products are known.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version 1.1 Revision Date: 03/24/2025 SDS Number: 11519062-00002 Date of last issue: 03/14/2025
Date of first issue: 03/14/2025

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 583.85 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

(2-Hydroxyethyl)ammonium mercaptoacetate:

Acute oral toxicity : LD50 (Rat, female): 71 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Alcohols, C12-14, ethoxylated:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

2-Butoxyethanol:

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version 1.1 Revision Date: 03/24/2025 SDS Number: 11519062-00002 Date of last issue: 03/14/2025
Date of first issue: 03/14/2025

Components:

(2-Hydroxyethyl)ammonium mercaptoacetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Alcohols, C12-14, ethoxylated:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

2-Butoxyethanol:

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

(2-Hydroxyethyl)ammonium mercaptoacetate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Alcohols, C12-14, ethoxylated:

Result : Irritation to eyes, reversing within 7 days

2-Butoxyethanol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

(2-Hydroxyethyl)ammonium mercaptoacetate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version 1.1 Revision Date: 03/24/2025 SDS Number: 11519062-00002 Date of last issue: 03/14/2025
Date of first issue: 03/14/2025

Assessment : Probability or evidence of low to moderate skin sensitization rate in humans

Alcohols, C12-14, ethoxylated:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

2-Butoxyethanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

(2-Hydroxyethyl)ammonium mercaptoacetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Alcohols, C12-14, ethoxylated:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative
Remarks: Based on data from similar materials

2-Butoxyethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version 1.1 Revision Date: 03/24/2025 SDS Number: 11519062-00002 Date of last issue: 03/14/2025
Date of first issue: 03/14/2025

Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells

Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

2-Butoxyethanol:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Alcohols, C12-14, ethoxylated:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative
Remarks: Based on data from similar materials

2-Butoxyethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Test Type: Embryo-fetal development

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version 1.1 Revision Date: 03/24/2025 SDS Number: 11519062-00002 Date of last issue: 03/14/2025
Date of first issue: 03/14/2025

Species: Rat
Application Route: inhalation (vapor)
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

(2-Hydroxyethyl)ammonium mercaptoacetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 49 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): 3.2 mg/l
plants : Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 1.45 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Alcohols, C12-14, ethoxylated:

Toxicity to fish : LC50 : > 1 - 10 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50: > 0.1 - 1 mg/l
aquatic invertebrates : Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : ErC50: > 0.1 - 1 mg/l
plants : Exposure time: 72 h
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version 1.1 Revision Date: 03/24/2025 SDS Number: 11519062-00002 Date of last issue: 03/14/2025
Date of first issue: 03/14/2025

NOEC: > 0.1 - 1 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: > 0.1 - 1 mg/l
Exposure time: 30 d
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 0.1 - 1 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

2-Butoxyethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,464 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,800 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,840 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 679 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 21 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 134 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Persistence and degradability

Components:

(2-Hydroxyethyl)ammonium mercaptoacetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Alcohols, C12-14, ethoxylated:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 95 %
Exposure time: 28 d

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2025
1.1	03/24/2025	11519062-00002	Date of first issue: 03/14/2025

Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

2-Butoxyethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90.4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

(2-Hydroxyethyl)ammonium mercaptoacetate:

Partition coefficient: n- : log Pow: < 4
octanol/water Method: OECD Test Guideline 107

Alcohols, C12-14, ethoxylated:

Partition coefficient: n- : log Pow: 6.1
octanol/water

2-Butoxyethanol:

Partition coefficient: n- : log Pow: 0.81
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2025
1.1	03/24/2025	11519062-00002	Date of first issue: 03/14/2025

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: < 2 %

The ingredients of this product are reported in the following inventories:

NDSL : This product contains one or several components listed in the Canadian NDSL.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and

SAFETY DATA SHEET

according to the Hazardous Products Regulations



IRON FALLOUT REMOVER, 475 mL

Version	Revision Date:	SDS Number:	Date of last issue: 03/14/2025
1.1	03/24/2025	11519062-00002	Date of first issue: 03/14/2025

Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/24/2025
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8