

**MARKING PAINT, Fluorescent Orange, 453 g**

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
Date of first issue: 10/11/2017

---

**SECTION 1. IDENTIFICATION**

Product name : MARKING PAINT, Fluorescent Orange, 453 g  
Product code : 893.199301  
Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Solvent-borne coatings  
Paint  
  
Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Skin irritation : Category 2  
Specific target organ toxicity : Category 3  
- single exposure

## MARKING PAINT, Fluorescent Orange, 453 g

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
Date of first issue: 10/11/2017

---

Aspiration hazard : Category 1

Simple Asphyxiant : Category 1

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
May displace oxygen and cause rapid suffocation.

Precautionary Statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

None known.

**MARKING PAINT, Fluorescent Orange, 453 g**

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
 Date of first issue: 10/11/2017

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Limestone	Calcium carbonate	1317-65-3	$\geq 10 - < 30$ *
Propane	Dimethylmethane	74-98-6	$\geq 10 - < 30$ *
Solvent naphtha (petroleum), light aliph.	No data available	64742-89-8	$\geq 10 - < 30$ *
Butane	No data available	106-97-8	$\geq 5 - < 10$ *
Distillates (petroleum), hydrotreated light	No data available	64742-47-8	$\geq 5 - < 10$ *
Heptane	n-Heptane	142-82-5	$\geq 5 - < 10$ *
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	$\geq 5 - < 10$ *

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
 If not breathing, give artificial respiration.  
 If breathing is difficult, give oxygen.  
 Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
 Get medical attention.  
 Wash clothing before reuse.  
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
 If vomiting occurs have person lean forward.  
 Call a physician or poison control center immediately.  
 Rinse mouth thoroughly with water.  
 Never give anything by mouth to an unconscious person.
- Most important symptoms : May be fatal if swallowed and enters airways.

**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

and effects, both acute and delayed		Causes skin irritation. May cause drowsiness or dizziness. Gas reduces oxygen available for breathing.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	:	Treat symptomatically and supportively.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Hazardous combustion products	:	Carbon oxides Metal oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	:	Evacuate personnel to safe areas. Remove all sources of ignition. Ventilate the area. Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water.

**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
 Soak up with inert absorbent material.  
 Suppress (knock down) gases/vapors/mists with a water spray jet.  
 For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
 Avoid breathing spray.  
 Do not swallow.  
 Avoid contact with eyes.  
 Wash skin thoroughly after handling.  
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
 Keep container tightly closed.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Take precautionary measures against static discharges.  
 Take care to prevent spills, waste and minimize release to the environment.  
 Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.  
 Keep tightly closed.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Do not pierce or burn, even after use.  
 Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:

**MARKING PAINT, Fluorescent Orange, 453 g**

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
 Date of first issue: 10/11/2017

Self-reactive substances and mixtures  
 Organic peroxides  
 Oxidizing agents  
 Flammable solids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Substances and mixtures which in contact with water emit flammable gases  
 Explosives  
 Gases

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		STEL	20 mg/m <sup>3</sup>	CA BC OEL
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA	525 mg/m <sup>3</sup>	CA ON OEL
Heptane	142-82-5	TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm 1,640 mg/m <sup>3</sup>	CA AB OEL
		STEL	500 ppm 2,050 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	400 ppm	CA QC OEL

**MARKING PAINT, Fluorescent Orange, 453 g**

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
 Date of first issue: 10/11/2017

		STEVE	500 ppm	CA QC OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Isobutyl acetate	110-19-0	TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEVE	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH

**Engineering measures** : Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

**Personal protective equipment**

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

**Hand protection**

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
 Wear the following personal protective equipment:  
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	Aerosol containing a liquefied gas
Color	:	orange
Odor	:	aromatic
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-44 °C
Flash point	:	-19 °C
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	10.9 %(V)
Lower explosion limit / Lower flammability limit	:	1.7 %(V)
Vapor pressure	:	2,750 hPa
Relative vapor density	:	Not applicable
Relative density	:	0.77 - 0.85
Density	:	0.77 - 0.85 g/cm <sup>3</sup>
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available



**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

**Components:****Limestone:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420

---

**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

Assessment: The substance or mixture has no acute oral toxicity  
 Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Method: OECD Test Guideline 403  
 Assessment: The substance or mixture has no acute inhalation toxicity  
 Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
 Method: OECD Test Guideline 402  
 Assessment: The substance or mixture has no acute dermal toxicity  
 Remarks: Based on data from similar materials

**Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
 Exposure time: 15 min  
 Test atmosphere: gas

**Solvent naphtha (petroleum), light aliph.:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.6 mg/l  
 Exposure time: 4 h  
 Test atmosphere: vapor  
 Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
 Assessment: The substance or mixture has no acute dermal toxicity

**Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
 Exposure time: 4 h  
 Test atmosphere: vapor

**Distillates (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
 Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l  
 Exposure time: 4 h  
 Test atmosphere: vapor  
 Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
 Remarks: Based on data from similar materials

## MARKING PAINT, Fluorescent Orange, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

**Heptane:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 73.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**Isobutyl acetate:**

- Acute oral toxicity : LD50 (Rat): 13,413 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403
- LC50 (Rat): 21.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 (Rabbit): > 17,400 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Limestone:**

- Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

**Solvent naphtha (petroleum), light aliph.:**

- Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

**Distillates (petroleum), hydrotreated light:**

- Species : Rabbit  
Result : Mild skin irritation  
Remarks : Based on data from similar materials

- Assessment : Repeated exposure may cause skin dryness or cracking.

**MARKING PAINT, Fluorescent Orange, 453 g**

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
Date of first issue: 10/11/2017

---

**Heptane:**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Isobutyl acetate:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.  
Remarks : Based on harmonised classification in EU regulation  
1272/2008, Annex VI

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Limestone:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

**Solvent naphtha (petroleum), light aliph.:**

Species : Rabbit  
Result : No eye irritation

**Distillates (petroleum), hydrotreated light:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

**Heptane:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Isobutyl acetate:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

**MARKING PAINT, Fluorescent Orange, 453 g**

Version      Revision Date:      SDS Number:      Date of last issue: 10/26/2021  
1.6          05/16/2022          10693524-00005      Date of first issue: 10/11/2017

---

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Limestone:**

Test Type                                 : Local lymph node assay (LLNA)  
Routes of exposure                     : Skin contact  
Species                                    : Mouse  
Method                                    : OECD Test Guideline 429  
Result                                     : negative  
Remarks                                 : Based on data from similar materials

**Solvent naphtha (petroleum), light aliph.:**

Test Type                                 : Buehler Test  
Routes of exposure                     : Skin contact  
Species                                    : Guinea pig  
Result                                     : negative

**Distillates (petroleum), hydrotreated light:**

Test Type                                 : Maximization Test  
Routes of exposure                     : Skin contact  
Species                                    : Guinea pig  
Result                                     : negative  
Remarks                                 : Based on data from similar materials

**Heptane:**

Test Type                                 : Maximization Test  
Routes of exposure                     : Skin contact  
Species                                    : Guinea pig  
Result                                     : negative

**Isobutyl acetate:**

Test Type                                 : Maximization Test  
Routes of exposure                     : Skin contact  
Species                                    : Guinea pig  
Method                                    : OECD Test Guideline 406  
Result                                     : negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Limestone:**

Genotoxicity in vitro                 : Test Type: Bacterial reverse mutation assay (AMES)  
  Method: OECD Test Guideline 471

## MARKING PAINT, Fluorescent Orange, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

**Propane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

**Solvent naphtha (petroleum), light aliph.:**

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Inhalation  
Result: negative

**Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Distillates (petroleum), hydrotreated light:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Heptane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

**Isobutyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

## MARKING PAINT, Fluorescent Orange, 453 g

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
Date of first issue: 10/11/2017

---

**Carcinogenicity**

Not classified based on available information.

**Components:****Solvent naphtha (petroleum), light aliph.:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

**Heptane:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

**Reproductive toxicity**

Not classified based on available information.

**Components:****Limestone:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

**Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422



## MARKING PAINT, Fluorescent Orange, 453 g

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
Date of first issue: 10/11/2017

---

Result: negative

**Solvent naphtha (petroleum), light aliph.:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the  
reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the  
reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Distillates (petroleum), hydrotreated light:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

**Heptane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

## MARKING PAINT, Fluorescent Orange, 453 g

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
Date of first issue: 10/11/2017

---

**Isobutyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OPPTS 870.3800  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Inhalation  
Result: negative  
Remarks: Based on data from similar materials

**STOT-single exposure**

May cause drowsiness or dizziness.

**Components:****Propane:**

Assessment : May cause drowsiness or dizziness.

**Solvent naphtha (petroleum), light aliph.:**

Assessment : May cause drowsiness or dizziness.

**Butane:**

Assessment : May cause drowsiness or dizziness.

**Distillates (petroleum), hydrotreated light:**

Assessment : May cause drowsiness or dizziness.

**Heptane:**

Assessment : May cause drowsiness or dizziness.

**Isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.  
Remarks : Based on data from similar materials

**STOT-repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Components:****Limestone:**

Species : Rat  
NOAEL : > 300 mg/kg  
Application Route : Ingestion

## MARKING PAINT, Fluorescent Orange, 453 g

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
Date of first issue: 10/11/2017

---

Exposure time : 28 Days  
Method : OECD Test Guideline 422  
Remarks : Based on data from similar materials

**Propane:**

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Solvent naphtha (petroleum), light aliph.:**

Species : Rat  
NOAEL : > 20 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Method : OPPTS 870.3465  
Remarks : Based on data from similar materials

**Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Distillates (petroleum), hydrotreated light:**

Species : Rat  
NOAEL : > 100 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : > 1 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

Species : Rat  
LOAEL : 500 mg/kg  
Application Route : Skin contact  
Exposure time : 28 Days

**Heptane:**

Species : Rat  
NOAEL : 12.35 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days

**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

**Isobutyl acetate:**

Species	:	Rat
NOAEL	:	> 100 mg/kg
Application Route	:	Ingestion
Exposure time	:	92 Days
Remarks	:	Based on data from similar materials

Species	:	Rat
NOAEL	:	> 2.4 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**Product:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Components:****Solvent naphtha (petroleum), light aliph.:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Distillates (petroleum), hydrotreated light:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Heptane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Limestone:**

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
------------------	---	--

Toxicity to daphnia and other aquatic invertebrates	:	LL50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
---	---	--

## MARKING PAINT, Fluorescent Orange, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials

EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

**Solvent naphtha (petroleum), light aliph.:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

**Distillates (petroleum), hydrotreated light:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

## MARKING PAINT, Fluorescent Orange, 453 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

NOELR (Pseudokirchneriella subcapitata (green algae)): 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

**Heptane:**

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 4,924 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 0.2 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50: > 0.1 - 1 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 0.1 - 1 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

**Isobutyl acetate:**

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 16.6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 24.6 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 196 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (Pseudomonas putida): 487 mg/l  
Exposure time: 6 h

## MARKING PAINT, Fluorescent Orange, 453 g

Version 1.6      Revision Date: 05/16/2022      SDS Number: 10693524-00005      Date of last issue: 10/26/2021  
Date of first issue: 10/11/2017

---

**Persistence and degradability****Components:****Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Solvent naphtha (petroleum), light aliph.:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77.07 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Distillates (petroleum), hydrotreated light:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 80 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Heptane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 %  
Exposure time: 10 d

**Isobutyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 81 %  
Exposure time: 20 d

**Bioaccumulative potential****Components:****Solvent naphtha (petroleum), light aliph.:**

Partition coefficient: n-octanol/water : log Pow: > 4  
Remarks: Expert judgment

**Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.31

**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

**Heptane:**

Partition coefficient: n-octanol/water : log Pow: 4.5

**Isobutyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

**IATA-DGR**

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950

---



**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

Proper shipping name : AEROSOLS  
(Heptane, Solvent naphtha (petroleum), light aliph.)  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : yes(Heptane, Solvent naphtha (petroleum), light aliph.)

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION**

**Volatile organic compounds (VOC) content** : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 57 % / 502.8 g/l

**The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
ACGIH / TWA : 8-hour, time-weighted average

---

**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/16/2022  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS mate-

**MARKING PAINT, Fluorescent Orange, 453 g**

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
1.6	05/16/2022	10693524-00005	Date of first issue: 10/11/2017

---

Material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8