

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

SECTION 1. IDENTIFICATION

Product name : SILICONE SPRAY, 306 g

Product code : 893.221

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use :

Preservative
Lubricant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Skin irritation : Category 2

Simple Asphyxiant : Category 1

SILICONE SPRAY, 306 g

Version 9.5 Revision Date: 03/08/2023 SDS Number: 10633757-00014 Date of last issue: 12/05/2022
 Date of first issue: 06/08/2012

GHS label elements

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

 : H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 May displace oxygen and cause rapid suffocation.

Precautionary Statements

 : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P264 Wash skin thoroughly after handling.
 P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
 P332 + P313 If skin irritation occurs: Get medical attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Butane	Butyl hydride	106-97-8	$\geq 30 - < 60$ *
Propane	Dimethylmethane	74-98-6	$\geq 10 - < 30$ *
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Heptane, branched, cyclic and linear	64742-49-0	$\geq 10 - < 30$ *
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Naphtha (petroleum), hydrotreated light	64742-49-0	$\geq 5 - < 10$ *
Hydrocarbons, C9-C10, n-alkanes, isoal-	Naphtha, hydrotreated	64742-48-9	$\geq 1 - < 5$ *

SILICONE SPRAY, 306 g

Version 9.5 Revision Date: 03/08/2023 SDS Number: 10633757-00014 Date of last issue: 12/05/2022
 Date of first issue: 06/08/2012

kanes, cyclics ,<2% aromatics	heavy		
Propan-2-ol	Isopropyl alcohol	67-63-0	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 If not breathing, give artificial respiration.
 If breathing is difficult, give oxygen.
 Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention if symptoms occur.
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
 Gas reduces oxygen available for breathing.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
 Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire : Flash back possible over considerable distance.

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

- | | |
|--|---|
| fighting | Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
| Hazardous combustion products | : Carbon oxides
Silicon oxides |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SECTION 7. HANDLING AND STORAGE

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.
Avoid inhalation of vapor or mist.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
- Recommended storage temperature : < 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL

SILICONE SPRAY, 306 g

Version 9.5 Revision Date: 03/08/2023 SDS Number: 10633757-00014 Date of last issue: 12/05/2022
 Date of first issue: 06/08/2012

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm 1,640 mg/m ³	CA AB OEL
		STEL	500 ppm 2,050 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	STEL	1,000 ppm 3,500 mg/m ³	CA AB OEL
		TWA	500 ppm 1,760 mg/m ³	CA AB OEL
		TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		STEV	1,000 ppm 3,500 mg/m ³	CA QC OEL
		TWAEV	500 ppm 1,760 mg/m ³	CA QC OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA	200 ppm	CA BC OEL
		TWA	500 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA	525 mg/m ³	CA ON OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Propan-2-ol	67-63-0	STEL	400 ppm 984 mg/m ³	CA AB OEL
		TWA	200 ppm 492 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	200 ppm	CA QC OEL
		STEV	400 ppm	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

SILICONE SPRAY, 306 g

Version 9.5 Revision Date: 03/08/2023 SDS Number: 10633757-00014 Date of last issue: 12/05/2022
Date of first issue: 06/08/2012

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0.35 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Propellant	:	Propane, Butane
Color	:	colorless
Odor	:	characteristic
Odor Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-42 - 165 °C
Flash point	:	3.5 °C (1,013.25 hPa) Flash point is only valid for liquid portion in the aerosol can.
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	12.0 %(V)
Lower explosion limit / Lower flammability limit	:	0.8 %(V)
Vapor pressure	:	8,530 hPa (20 °C)
Relative vapor density	:	Not applicable
Density	:	0.757 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	287 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	1 mPa.s (20 °C)
Viscosity, kinematic	:	1 mm ² /s (40 °C)

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
---------------------------	---	--

Components:**Butane:**

Acute inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	---	--

Propane:

Acute inhalation toxicity	:	LC50 (Rat): > 800000 ppm Exposure time: 15 min
---------------------------	---	---

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Test atmosphere: gas

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity	:	LD50 (Rat): > 5,840 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 23.3 mg/l Exposure time: 4 h Test atmosphere: vapor Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rat): > 2,800 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Acute oral toxicity	:	LD50 (Rat): 16,750 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): 259.354 mg/l Exposure time: 4 h Test atmosphere: vapor Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 3,350 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 4,951 mg/m ³ Exposure time: 4 h Test atmosphere: vapor Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 3,160 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

Propan-2-ol:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 25 mg/l Exposure time: 6 h Test atmosphere: vapor

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species	: Rabbit
Result	: Skin irritation
Remarks	: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Skin irritation

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Species	: Rabbit
Result	: Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Propan-2-ol:

Species	: Rabbit
Result	: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species	: Rabbit
Result	: No eye irritation
Remarks	: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species	: Rabbit
Result	: No eye irritation
Remarks	: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Propan-2-ol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Result	:	negative
Remarks	:	Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

Propan-2-ol:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Butane:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	---	--

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo)
----------------------	---	--

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Species : Mouse
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 105 weeks
Result : negative
Remarks : Based on data from similar materials

Propan-2-ol:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 104 weeks

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Method	:	OECD Test Guideline 451
Result	:	negative

Reproductive toxicity

Not classified based on available information.

Components:**Butane:**

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
----------------------	---	--

Effects on fetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
------------------------------	---	--

Propane:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
----------------------	---	--

Effects on fetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
------------------------------	---	--

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Result: negative Remarks: Based on data from similar materials
----------------------	---	---

Effects on fetal development	:	Test Type: Fertility/early embryonic development Species: Rat Application Route: inhalation (vapor) Result: negative Remarks: Based on data from similar materials
------------------------------	---	--

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study
----------------------	---	---

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

Product:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

Components:**Butane:**

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Assessment : May cause drowsiness or dizziness.

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****Butane:**

Species	: Rat
NOAEL	: 9000 ppm
Application Route	: inhalation (gas)
Exposure time	: 6 Weeks
Method	: OECD Test Guideline 422

Propane:

Species	: Rat
NOAEL	: 7.214 mg/l
Application Route	: inhalation (gas)
Exposure time	: 6 Weeks
Method	: OECD Test Guideline 422

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species	: Rat
NOAEL	: 12.47 mg/l
Application Route	: Inhalation
Exposure time	: 90 Days
Remarks	: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species	: Rat, male
NOAEL	: 10.504 mg/l
Application Route	: inhalation (vapor)
Exposure time	: 90 Days
Remarks	: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Species : Rat

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

NOAEL : 10,186 mg/m³
Application Route : inhalation (vapor)
Exposure time : 13 Weeks

Propan-2-ol:

Species : Rat
NOAEL : 12.5 mg/l
Application Route : inhalation (vapor)
Exposure time : 104 Weeks

Aspiration toxicity

Not classified based on available information.

Components:**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 3 mg/l
aquatic invertebrates : Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100
plants : mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.17 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 0.1 - 1 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l
Exposure time: 48 h

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l
Exposure time: 16 h

Persistence and degradability**Components:****Butane:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics ,<2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 89 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1.19 (BOD5)COD: 2.23BOD/COD: 53 %

Bioaccumulative potential**Components:****Butane:**

Partition coefficient: n- : log Pow: 2.31
octanol/water

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Partition coefficient: n- : log Pow: > 4
octanol/water Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Partition coefficient: n- : log Pow: 3.6
octanol/water

Propan-2-ol:

Partition coefficient: n- : log Pow: 0.05
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1

IATA-DGR

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
ERG Code	: 126
Marine pollutant	: no

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 93.13 %

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International

SILICONE SPRAY, 306 g

Version	Revision Date:	SDS Number:	Date of last issue: 12/05/2022
9.5	03/08/2023	10633757-00014	Date of first issue: 06/08/2012

Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/08/2023
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8