

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version 8.0      Revision Date: 09/22/2023      SDS Number: 11275475-00010      Date of last issue: 04/30/2019  
Date of first issue: 12/23/2009

---

### SECTION 1. IDENTIFICATION

Product name : SPRAYABLE SEAM SEALER, Black, 310 mL  
Product code : 893.226  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Sealant  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

#### GHS label elements

|| No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### Other hazards

In use, may form flammable/explosive vapor-air mixture.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version 8.0      Revision Date: 09/22/2023      SDS Number: 11275475-00010      Date of last issue: 04/30/2019  
Date of first issue: 12/23/2009

Substance / Mixture : Mixture

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Calcium carbonate	Carbonic acid calcium salt	471-34-1	$\geq 30 - < 60$ *
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	No data available	90622-57-4	$\geq 10 - < 30$ *

\* Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2019
8.0	09/22/2023	11275475-00010	Date of first issue: 12/23/2009

---

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version 8.0      Revision Date: 09/22/2023      SDS Number: 11275475-00010      Date of last issue: 04/30/2019  
Date of first issue: 12/23/2009

- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing vapors.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents
- Recommended storage temperature : < 25 °C
- Storage period : 15 Months

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA	10 mg/m <sup>3</sup> (Calcium carbonate)	CA AB OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		STEL	20 mg/m <sup>3</sup>	CA BC OEL
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	90622-57-4	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m <sup>3</sup>	CA QC OEL

- Engineering measures : Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version 8.0      Revision Date: 09/22/2023      SDS Number: 11275475-00010      Date of last issue: 04/30/2019  
Date of first issue: 12/23/2009

---

### Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : Nitrile rubber  
Break through time : > 240 min  
Glove thickness : 0.8 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety glasses
- Skin and body protection : Wear the following personal protective equipment:
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Pasty solid
- Color : black
- Odor : hydrocarbon-like
- Odor Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2019
8.0	09/22/2023	11275475-00010	Date of first issue: 12/23/2009

---

Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Burning rate	:	<= 2.2 mm/s
Upper explosion limit / Upper flammability limit	:	7.0 %(V)
Lower explosion limit / Lower flammability limit	:	0.4 %(V)
Vapor pressure	:	1 hPa (20 °C)
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	1.34 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive

In use may form flammable/explosive vapor-air mixture.

Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac-	:	Vapors may form explosive mixture with air.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2019
8.0	09/22/2023	11275475-00010	Date of first issue: 12/23/2009

---

tions	Can react with strong oxidizing agents. In use may form flammable/explosive vapor-air mixture.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Calcium carbonate:**

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity
Acute inhalation toxicity	: LC50 (Rat): > 3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

##### **Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version 8.0      Revision Date: 09/22/2023      SDS Number: 11275475-00010      Date of last issue: 04/30/2019  
Date of first issue: 12/23/2009

---

### **Skin corrosion/irritation**

Not classified based on available information.

#### **Components:**

##### **Calcium carbonate:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

##### **Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Species : Rabbit  
Result : Mild skin irritation  
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.  
Remarks : Based on data from similar materials

### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Components:**

##### **Calcium carbonate:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

##### **Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Components:**

##### **Calcium carbonate:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

##### **Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Test Type : Maximization Test



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2019
8.0	09/22/2023	11275475-00010	Date of first issue: 12/23/2009

---

Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Calcium carbonate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

#### Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro sister chromatid exchange assay in mam-  
malian cells  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Calcium carbonate:

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version 8.0      Revision Date: 09/22/2023      SDS Number: 11275475-00010      Date of last issue: 04/30/2019  
Date of first issue: 12/23/2009

---

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

### Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

#### Calcium carbonate:

Species : Rat  
NOAEL : > 1,000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days  
Method : OECD Test Guideline 422

#### Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Species : Rat  
NOAEL : > 1 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : > 300 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version 8.0      Revision Date: 09/22/2023      SDS Number: 11275475-00010      Date of last issue: 04/30/2019  
Date of first issue: 12/23/2009

---

### Components:

#### **Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### Components:

##### **Calcium carbonate:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): 50 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201
- EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201
- Toxicity to microorganisms : NOEC: 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209
- EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

##### **Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version 8.0      Revision Date: 09/22/2023      SDS Number: 11275475-00010      Date of last issue: 04/30/2019  
Date of first issue: 12/23/2009

---

Toxicity to algae/aquatic plants : Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

: NOELR (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 1 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211

### Persistence and degradability

#### Components:

#### Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:

Biodegradability : Result: Not readily biodegradable.  
Remarks: Based on data from similar materials

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version 8.0      Revision Date: 09/22/2023      SDS Number: 11275475-00010      Date of last issue: 04/30/2019  
Date of first issue: 12/23/2009

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### TDG

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

---

### SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content**      Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations  
VOC content: 10 % / 134.3 g/l

#### The ingredients of this product are reported in the following inventories:

DSL      :    All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

CA AB OEL      :    Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL      :    Canada. British Columbia OEL  
CA QC OEL      :    Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
CA AB OEL / TWA      :    8-hour Occupational exposure limit  
CA AB OEL / STEL      :    15-minute occupational exposure limit  
CA BC OEL / TWA      :    8-hour time weighted average  
CA BC OEL / STEL      :    short-term exposure limit  
CA QC OEL / TWAEV      :    Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## SPRAYABLE SEAM SEALER, Black, 310 mL

Version	Revision Date:	SDS Number:	Date of last issue: 04/30/2019
8.0	09/22/2023	11275475-00010	Date of first issue: 12/23/2009

---

Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/22/2023  
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8