



## SUPER RTV SILICONE, Transparent, 200 g

Version 2.1      Revision Date: 05/22/2023      SDS Number: 7749060-00005      Date of last issue: 11/24/2022  
Date of first issue: 01/27/2021

---

- repeated exposure

**GHS label elements**

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H317 May cause an allergic skin reaction.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs (Blood, spleen) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P333 + P313 If skin irritation or rash occurs: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**SUPER RTV SILICONE, Transparent, 200 g**

Version 2.1      Revision Date: 05/22/2023      SDS Number: 7749060-00005      Date of last issue: 11/24/2022  
 Date of first issue: 01/27/2021

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Propane	Dimethylmethane	74-98-6	$\geq 5 - < 10$ *
O,O',O''-(Methylsilyldyne)trioxime 2-pentanone	(4E,9E)-4,7,10-Trimethyl-7-[[{(E)-(pentan-2-ylidene)amino]oxy}-6,8-dioxa-5,9-diaza-7-silatrideca-4,9-diene	37859-55-5	$\geq 1 - < 5$ *
Butane	Butyl hydride	106-97-8	$\geq 1 - < 5$ *
2-Pentanone oxime	(E)-N-(pentan-2-ylidene)hydroxylamine	623-40-5	$\geq 1 - < 5$ *
2-Pentanone, O,O',O''-(ethenylsilyldyne)trioxime	No data available	58190-62-8	$\geq 1 - < 5$ *
Dimethylbis[(1-oxodecyl)oxy]stannane	Dimethyltindecanoate	68928-76-7	$\geq 0.1 - < 1$ *

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
 Remove contaminated clothing and shoes.  
 Get medical attention.  
 Wash clothing before reuse.  
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
 Get medical attention.  
 Rinse mouth thoroughly with water.

**SUPER RTV SILICONE, Transparent, 200 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

---

- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Suspected of damaging the unborn child.  
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides  
Silicon oxides  
Nitrogen oxides (NO<sub>x</sub>)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).

**SUPER RTV SILICONE, Transparent, 200 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

---

Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe spray.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from water.  
Protect from moisture.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides

**SUPER RTV SILICONE, Transparent, 200 g**

Version 2.1      Revision Date: 05/22/2023      SDS Number: 7749060-00005      Date of last issue: 11/24/2022  
 Date of first issue: 01/27/2021

Oxidizing agents  
 Flammable solids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Substances and mixtures which in contact with water emit flammable gases  
 Explosives  
 Gases

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Dimethylbis[(1-oxodecyl)oxy]stannane	68928-76-7	TWA	0.1 mg/m <sup>3</sup> (Tin)	CA AB OEL
		STEL	0.2 mg/m <sup>3</sup> (Tin)	CA AB OEL
		TWAEV	0.1 mg/m <sup>3</sup> (Tin)	CA QC OEL
		STEV	0.2 mg/m <sup>3</sup> (Tin)	CA QC OEL
		TWA	0.1 mg/m <sup>3</sup> (Tin)	CA BC OEL
		STEL	0.2 mg/m <sup>3</sup> (Tin)	CA BC OEL
		TWA	0.1 mg/m <sup>3</sup> (Tin)	CA ON OEL
		TWA	0.1 mg/m <sup>3</sup> (Tin)	ACGIH
		STEL	0.2 mg/m <sup>3</sup> (Tin)	ACGIH

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

**SUPER RTV SILICONE, Transparent, 200 g**

Version 2.1      Revision Date: 05/22/2023      SDS Number: 7749060-00005      Date of last issue: 11/24/2022  
Date of first issue: 01/27/2021

---

**Personal protective equipment**

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Self-contained breathing apparatus
- Hand protection
- Material : Latex gloves  
Break through time : 480 min  
Glove thickness : > 0.5 mm
- Material : Chloroprene  
Break through time : 480 min  
Glove thickness : > 0.65 mm
- Material : Nitrile rubber  
Break through time : 480 min  
Glove thickness : > 0.4 mm
- Material : Fluorinated rubber  
Break through time : 480 min  
Glove thickness : > 0.7 mm
- Material : butyl-rubber  
Break through time : 480 min  
Glove thickness : > 0.47 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.





## SUPER RTV SILICONE, Transparent, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

---

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed upon contact with water or humid air.

Conditions to avoid : Exposure to moisture.  
Heat, flames and sparks.

Incompatible materials : Oxidizing agents  
Water

**Hazardous decomposition products**

Contact with water or humid air : 2-Pentanone oxime  
Methyl Isobutyl Ketoxime

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

---

**SUPER RTV SILICONE, Transparent, 200 g**

Version            Revision Date:            SDS Number:            Date of last issue: 11/24/2022  
2.1                05/22/2023                7749060-00005            Date of first issue: 01/27/2021

---

**Components:****Propane:**

Acute inhalation toxicity            : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

**O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

Acute oral toxicity                    : LD50 (Rat): 1,234 mg/kg  
Method: OECD Test Guideline 425

Acute dermal toxicity                : LD50 (Rat): > 1,782 mg/kg  
Remarks: Based on data from similar materials

**Butane:**

Acute inhalation toxicity            : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

**2-Pentanone oxime:**

Acute oral toxicity                    : LD50 (Rat): 1,133 mg/kg  
Method: OECD Test Guideline 425

Acute inhalation toxicity            : LC50 (Rat): > 1.22 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

**2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:**

Acute oral toxicity                    : LD50 (Rat): > 1,000 - < 2,000 mg/kg  
Method: OECD Test Guideline 423

Acute dermal toxicity                : LD50 (Rabbit): > 2,000 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.3.  
Remarks: Based on data from similar materials

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Acute oral toxicity                    : LD50 (Rat): 190 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity                : LD50 (Rat): > 2,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

Species                                : Rabbit  
Method                                 : OECD Test Guideline 404  
Result                                  : No skin irritation

**SUPER RTV SILICONE, Transparent, 200 g**

Version            Revision Date:            SDS Number:            Date of last issue: 11/24/2022  
2.1                05/22/2023                7749060-00005            Date of first issue: 01/27/2021

---

**2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:**

Species                : Rabbit  
Result                 : No skin irritation

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Species                : reconstructed human epidermis (RhE)  
Method                 : OECD Test Guideline 431

Species                : reconstructed human epidermis (RhE)  
Method                 : OECD Test Guideline 439

Result                 : Skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

Species                : Rabbit  
Result                 : Irritation to eyes, reversing within 21 days  
Method                 : OECD Test Guideline 405  
Remarks               : Based on data from similar materials

**2-Pentanone oxime:**

Species                : Rabbit  
Result                 : Irritation to eyes, reversing within 21 days  
Method                 : OECD Test Guideline 405

**2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:**

Species                : Rabbit  
Result                 : Irritation to eyes, reversing within 21 days  
Method                 : OECD Test Guideline 405  
Remarks               : Based on data from similar materials

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Species                : Bovine cornea  
Method                 : OECD Test Guideline 437

Result                 : No eye irritation

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**SUPER RTV SILICONE, Transparent, 200 g**

Version            Revision Date:            SDS Number:            Date of last issue: 11/24/2022  
2.1                05/22/2023                7749060-00005            Date of first issue: 01/27/2021

---

**Components:****2-Pentanone oxime:**

Test Type                                : Buehler Test  
Routes of exposure                      : Skin contact  
Species                                    : Guinea pig  
Method                                    : OECD Test Guideline 406  
Result                                     : negative

**2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:**

Test Type                                : Buehler Test  
Routes of exposure                      : Skin contact  
Species                                    : Guinea pig  
Method                                    : OECD Test Guideline 406  
Result                                     : negative  
Remarks                                 : Based on data from similar materials

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Test Type                                : Maurer optimisation test  
Routes of exposure                      : Skin contact  
Species                                    : Guinea pig  
Result                                     : positive  
Remarks                                 : Based on data from similar materials

Assessment                               : Probability or evidence of high skin sensitization rate in humans

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Propane:**

Genotoxicity in vitro                    : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo                    : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

**O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

Genotoxicity in vitro                    : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: positive

**SUPER RTV SILICONE, Transparent, 200 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

---

Test Type: In vitro mammalian cell gene mutation test  
 Method: OECD Test Guideline 476  
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 474  
 Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

**Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
 Species: Rat  
 Application Route: inhalation (gas)  
 Method: OECD Test Guideline 474  
 Result: negative  
 Remarks: Based on data from similar materials

**2-Pentanone oxime:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative

Test Type: Chromosome aberration test in vitro  
 Method: OECD Test Guideline 473  
 Result: positive

Test Type: in vitro micronucleus test  
 Method: OECD Test Guideline 487  
 Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
 Species: Rat  
 Application Route: inhalation (vapor)  
 Method: OECD Test Guideline 475  
 Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

**2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative

**SUPER RTV SILICONE, Transparent, 200 g**

Version 2.1      Revision Date: 05/22/2023      SDS Number: 7749060-00005      Date of last issue: 11/24/2022  
Date of first issue: 01/27/2021

---

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Suspected of damaging the unborn child.

**Components:****Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

**Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)

**SUPER RTV SILICONE, Transparent, 200 g**

Version 2.1      Revision Date: 05/22/2023      SDS Number: 7749060-00005      Date of last issue: 11/24/2022  
Date of first issue: 01/27/2021

---

Method: OECD Test Guideline 422

Result: negative

**2-Pentanone oxime:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: positive  
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.  
Remarks: Based on data from similar materials

**STOT-single exposure**

Not classified based on available information.

**Components:****Propane:**

Assessment : May cause drowsiness or dizziness.

**Butane:**

Assessment : May cause drowsiness or dizziness.

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Routes of exposure : Ingestion  
Target Organs : Nervous system  
Assessment : Shown to produce significant health effects in animals at concentrations of 300 mg/kg bw or less.  
Remarks : Based on data from similar materials

**STOT-repeated exposure**

May cause damage to organs (Blood, spleen) through prolonged or repeated exposure.

**SUPER RTV SILICONE, Transparent, 200 g**

Version            Revision Date:            SDS Number:            Date of last issue: 11/24/2022  
2.1                05/22/2023                7749060-00005            Date of first issue: 01/27/2021

---

**Components:****2-Pentanone oxime:**

Routes of exposure            : Ingestion  
Target Organs                 : Blood, spleen  
Assessment                     : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

**2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:**

Assessment                     : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Routes of exposure            : Ingestion  
Target Organs                 : Nervous system  
Assessment                     : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.  
Remarks                        : Based on data from similar materials

**Repeated dose toxicity****Components:****Propane:**

Species                         : Rat  
NOAEL                          : 7.214 mg/l  
Application Route             : inhalation (gas)  
Exposure time                 : 6 Weeks  
Method                         : OECD Test Guideline 422

**Butane:**

Species                         : Rat  
NOAEL                          : 9000 ppm  
Application Route             : inhalation (gas)  
Exposure time                 : 6 Weeks  
Method                         : OECD Test Guideline 422

**2-Pentanone oxime:**

Species                         : Rat  
NOAEL                          : 15 mg/kg  
LOAEL                          : 50 mg/kg  
Application Route             : Ingestion  
Exposure time                 : 6 Weeks  
Method                         : OECD Test Guideline 422

**2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:**

Species                         : Rat  
NOAEL                          : > 10 - 100 mg/kg  
Application Route             : Ingestion  
Exposure time                 : 13 Weeks  
Method                         : OECD Test Guideline 408



**SUPER RTV SILICONE, Transparent, 200 g**

Version 2.1      Revision Date: 05/22/2023      SDS Number: 7749060-00005      Date of last issue: 11/24/2022  
Date of first issue: 01/27/2021

---

Remarks : Based on data from similar materials

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Species : Rat  
NOAEL : < 10 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408  
Remarks : Based on data from similar materials

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 21.5 mg/l  
Exposure time: 28 d

**2-Pentanone oxime:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

## SUPER RTV SILICONE, Transparent, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

---

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 20 mg/l  
Exposure time: 28 d

**2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 117 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 117 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 103 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 37 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC0: > 22.2 mg/l  
Exposure time: 28 h  
Remarks: Based on data from similar materials

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 39 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 7.6 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1.2

## SUPER RTV SILICONE, Transparent, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

---

mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

**Persistence and degradability****Components:****Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 1 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**2-Pentanone oxime:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 9 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 1 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B  
Remarks: Based on data from similar materials

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 0 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**Bioaccumulative potential****Components:****Butane:**

**SUPER RTV SILICONE, Transparent, 200 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

---

Partition coefficient: n-octanol/water : log Pow: 2.31

**2-Pentanone oxime:**

Partition coefficient: n-octanol/water : log Pow: 1.43

**2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:**

Partition coefficient: n-octanol/water : log Pow: 1.25

**Dimethylbis[(1-oxoneodecyl)oxy]stannane:**

Partition coefficient: n-octanol/water : log Pow: 5.503  
Remarks: Calculation

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

**IATA-DGR**

UN/ID No. : UN 1950

---

**SUPER RTV SILICONE, Transparent, 200 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

---

Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION**

**Volatile organic compounds (VOC) content** CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 0.06 % / 0.7 g/l  
Remarks: VOC content excluding water and exempt compounds

**The ingredients of this product are reported in the following inventories:**

DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

**SUPER RTV SILICONE, Transparent, 200 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

**SECTION 16. OTHER INFORMATION**
**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA/EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

**SUPER RTV SILICONE, Transparent, 200 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/22/2023	7749060-00005	Date of first issue: 01/27/2021

---

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/22/2023  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8