

SUPER RTV SILICONE, Grey, 244 g

Version 2.1	Revision Date: 05/01/2023	SDS Number: 7748862-00006	Date of last issue: 11/24/2022 Date of first issue: 01/27/2021
----------------	------------------------------	------------------------------	---

SECTION 1. IDENTIFICATION

Product name : SUPER RTV SILICONE, Grey, 244 g

Product code : 893.3316

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Sealant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Skin sensitization : Sub-category 1A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 2 (Blood, spleen)

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

- repeated exposure

GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Blood, spleen) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P308 + P313 IF exposed or concerned: Get medical attention.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SUPER RTV SILICONE, Grey, 244 g

Version 2.1 Revision Date: 05/01/2023 SDS Number: 7748862-00006 Date of last issue: 11/24/2022
 Date of first issue: 01/27/2021

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Calcium carbonate	Carbonic acid calcium salt	471-34-1	$\geq 10 - < 30$ *
Propane	Dimethylmethane	74-98-6	$\geq 5 - < 10$ *
O,O',O''-(Methylsilyldyne)trioxime 2-pentanone	(4E,9E)-4,7,10-Trimethyl-7-[[[(E)-(pentan-2-ylidene)amino]oxy}-6,8-dioxa-5,9-diaza-7-silatrideca-4,9-diene	37859-55-5	$\geq 1 - < 5$ *
Butane	Butyl hydride	106-97-8	$\geq 1 - < 5$ *
2-Pentanone oxime	(E)-N-(pentan-2-ylidene)hydroxylamine	623-40-5	$\geq 1 - < 5$ *
2-Pentanone, O,O',O''-(ethenylsilyldyne)trioxime	No data available	58190-62-8	$\geq 1 - < 5$ *
Dimethylbis[(1-oxodecyl)oxy]stannane	Dimethyltin-dodecanoate	68928-76-7	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
 Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
 Remove contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
 Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Get medical attention.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Metal oxides
Silicon oxides
Nitrogen oxides (NO_x)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from water.
Protect from moisture.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

SUPER RTV SILICONE, Grey, 244 g

Version 2.1 Revision Date: 05/01/2023 SDS Number: 7748862-00006 Date of last issue: 11/24/2022
 Date of first issue: 01/27/2021

Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable solids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which in contact with water emit flammable gases
 Explosives
 Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA	10 mg/m ³ (Calcium carbonate)	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		STEL	20 mg/m ³	CA BC OEL
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Dimethylbis[(1-oxodecyl)oxy]stannane	68928-76-7	TWA	0.1 mg/m ³ (Tin)	CA AB OEL
		STEL	0.2 mg/m ³ (Tin)	CA AB OEL
		TWAEV	0.1 mg/m ³ (Tin)	CA QC OEL
		STEV	0.2 mg/m ³ (Tin)	CA QC OEL
		TWA	0.1 mg/m ³ (Tin)	CA BC OEL
		STEL	0.2 mg/m ³ (Tin)	CA BC OEL
		TWA	0.1 mg/m ³ (Tin)	CA ON OEL

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

		TWA	0.1 mg/m ³ (Tin)	ACGIH
		STEL	0.2 mg/m ³ (Tin)	ACGIH

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Calcium carbonate

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Latex gloves
Break through time : 480 min
Glove thickness : > 0.5 mm

Material : Chloroprene
Break through time : 480 min
Glove thickness : > 0.6 mm

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : > 0.4 mm

Material : Fluorinated rubber
Break through time : 480 min
Glove thickness : > 0.7 mm

Material : butyl-rubber
Break through time : 480 min
Glove thickness : > 0.47 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

SUPER RTV SILICONE, Grey, 244 g

Version 2.1	Revision Date: 05/01/2023	SDS Number: 7748862-00006	Date of last issue: 11/24/2022 Date of first issue: 01/27/2021
----------------	------------------------------	------------------------------	---

Safety glasses

- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Propellant : Propane, Butane
- Color : gray
- Odor : characteristic
- Odor Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : Not applicable
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : No data available

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	No data available
Solubility(ies)	:	
Water solubility	:	hydrolyzes
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
Conditions to avoid	:	Exposure to moisture. Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents Water

Hazardous decomposition products

Contact with water or humid air	:	2-Pentanone oxime Methyl Isobutyl Ketoxime
---------------------------------	---	---

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Calcium carbonate:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Acute oral toxicity : LD50 (Rat): 1,234 mg/kg
Method: OECD Test Guideline 425

Acute dermal toxicity : LD50 (Rat): > 1,782 mg/kg
Remarks: Based on data from similar materials

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Test atmosphere: vapor

2-Pentanone oxime:

Acute oral toxicity : LD50 (Rat): 1,133 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 1.22 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Acute oral toxicity : LD50 (Rat): > 1,000 - < 2,000 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.3.
Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Acute oral toxicity : LD50 (Rat): 190 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**Calcium carbonate:**

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Species : Rabbit
Result : No skin irritation

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Calcium carbonate:**

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

O,O',O''-(Methylsilyldiylne)trioxime 2-pentanone:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

2-Pentanone oxime:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days
Method	: OECD Test Guideline 405

2-Pentanone, O,O',O''-(ethenylsilyldiylne)trioxime:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species	: Bovine cornea
Method	: OECD Test Guideline 437

Result : No eye irritation

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:**Calcium carbonate:**

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

2-Pentanone oxime:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Test Type	: Maurer optimisation test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: positive
Remarks	: Based on data from similar materials

Assessment	: Probability or evidence of high skin sensitization rate in humans
------------	---

Germ cell mutagenicity

Not classified based on available information.

Components:**Calcium carbonate:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---

	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
--	---

	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
--	--

Propane:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	--

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas)
----------------------	---

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Method: OECD Test Guideline 474

Result: negative

O,O',O''-(Methylsilyldiyne)trioxime 2-pentanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

2-Pentanone oxime:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 475
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:**Calcium carbonate:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Result: negative

O,O',O''-(Methylsilyldiyn)trioxime 2-pentanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

2-Pentanone oxime:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - As- : Some evidence of adverse effects on development, based on

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

assessment

animal experiments.

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

Components:**Propane:**

Assessment : May cause drowsiness or dizziness.

Butane:

Assessment : May cause drowsiness or dizziness.

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Routes of exposure : Ingestion

Target Organs : Nervous system

Assessment : Shown to produce significant health effects in animals at concentrations of 300 mg/kg bw or less.

Remarks : Based on data from similar materials

STOT-repeated exposure

May cause damage to organs (Blood, spleen) through prolonged or repeated exposure.

Components:**2-Pentanone oxime:**

Routes of exposure : Ingestion

Target Organs : Blood, spleen

Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Routes of exposure : Ingestion

Target Organs : Nervous system

Assessment : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

Remarks : Based on data from similar materials

Repeated dose toxicity**Components:****Calcium carbonate:**

Species : Rat

NOAEL : > 1,000 mg/kg

Application Route : Ingestion

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Exposure time : 28 Days
Method : OECD Test Guideline 422

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Butane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

2-Pentanone oxime:

Species : Rat
NOAEL : 15 mg/kg
LOAEL : 50 mg/kg
Application Route : Ingestion
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

2-Pentanone, O,O',O''-(ethenylsilyldyne)trioxime:

Species : Rat
NOAEL : > 10 - 100 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : Rat
NOAEL : < 10 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Calcium carbonate:**

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): 50 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- Toxicity to microorganisms : NOEC: 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

O,O',O''-(Methylsilyldiylidene)trioxime 2-pentanone:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50: > 21.5 mg/l

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Exposure time: 28 d

2-Pentanone oxime:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50: > 20 mg/l
Exposure time: 28 d

2-Pentanone, O,O',O''-(ethenylsilyldi)trioxime:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 117 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 117 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 103 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 37 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC0: > 22.2 mg/l
Exposure time: 28 h
Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

- Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 39 mg/l

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

aquatic invertebrates	Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 7.6 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata (green algae)): 1.2 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201

Persistence and degradability**Components:****Propane:**

Biodegradability	: Result: Readily biodegradable. Biodegradation: 100 % Exposure time: 385.5 h Remarks: Based on data from similar materials
------------------	--

O,O',O''-(Methylsilylidyne)trioxime 2-pentanone:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 1 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

Butane:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 100 % Exposure time: 385.5 h Remarks: Based on data from similar materials
------------------	--

2-Pentanone oxime:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 9 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 1 % Exposure time: 28 d Method: OECD Test Guideline 301B Remarks: Based on data from similar materials
------------------	---

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential**Components:****Butane:**

Partition coefficient: n- : log Pow: 2.31
octanol/water

2-Pentanone oxime:

Partition coefficient: n- : log Pow: 1.43
octanol/water

2-Pentanone, O,O',O''-(ethenylsilylidene)trioxime:

Partition coefficient: n- : log Pow: 1.25
octanol/water

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Partition coefficient: n- : log Pow: 5.503
octanol/water Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1

IATA-DGR

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
ERG Code	: 126
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
---	---

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

VOC content: 0.06 % / 0.7 g/l
Remarks: VOC content excluding water and exempt compounds

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA ON OEL	: Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA BC OEL / STEL	: short-term exposure limit
CA ON OEL / TWA	: Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	: Time-weighted average exposure value
CA QC OEL / STEV	: Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances

SUPER RTV SILICONE, Grey, 244 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/24/2022
2.1	05/01/2023	7748862-00006	Date of first issue: 01/27/2021

es; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/01/2023
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8