

GUN WASH - AEROSOL (893.460013) PRODUCT:

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Wurth Canada Limited

345 Hanlon Creek Blvd Guelph, Ontario N1C 0A1 Tel (905) 564-6225 Fax (905) 564-3671 GUN WÁSH - AEROSOL (893.460013)

Product identifier..... Recommended use and restrictions on .. Multi-purpose solvent.

Solvent blend. Health: 3 Fire: 3 Reactivity: 1. Chemical family..... NFPA rating.....

H: 3 F: 3 R: 1. HMIS.....

Emergencies involving a spill, fire, explosion or exposure: CHEMTREC 1-800-424-9300. 24 hour emergency number:....

SECTION 02: HAZARD IDENTIFICATION



Signal WordHazard Classification	Toxicity 1. Eye Irritation — Category 2A. Skin Irritation — Category 3. Specific Target
Hazard Description	Organ Toxicity — Single Exposure — Category 3. H222 Extremely flammable aerosol. H229 Pressurized container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H316 Causes mild skin irritation. H319 Causes serious eye irritation.
Prevention	H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly
Response	after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection. P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
Storage	rinsing until medical help arrives. P312 Call a POISON CENTER/doctor if you feel unwell. P331 Do NOT induce vomiting. P332 + P313 - If skin irritation occurs get medical attention or advice. P337 + P313 - If eye irritation persists get medical attention. P403 + P233 Store in a well ventilated area. Keep container tightly closed. P405 Store locked up. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C / 122°F.
Disposal Note	

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS			
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %	
Acetone	67-64-1	65-85	
Naphtha (petroleum), hydrotreated light	64742-49-0	7-13	
Carbon dioxide	124-38-9	5-10	
< <the a="" actual="" as="" concentration(s)="" secret="" trade="" withheld="">> .</the>			

SECTION 04: FIRST-AID MEASURES

In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at Eye contact..... least 15 minutes. Obtain medical attention. Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If Skin contact..... irritation persists, seek medical attention. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is Inhalation..... difficult, give oxygen, obtain medical attention.

If ingestion is suspected, contact physician or poison control center immediately. Do not Ingestion..... induce vomiting. Rinse mouth with water. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may Most important symptoms and effects, whether acute or delayed cause headache, fatigue, dizziness and nausea. May cause redness and pain. Provide general supportive measures. Treat victims symptomatically. In case of shortness of and special treatment needed breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed. In the event of an incident involving this product Additional information..... ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Foam, "alcohol" foam, CO2, dry chemical,water fog. Do not use solid water streams or water jet.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Extremely flammable aerosol. Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. . Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate personnel to a safe area. Keep unnecessary and unprotected personnel from entering. Do not touch spilled material. Avoid breathing vapours. Wear appropriate personal protection equipment

Environmental precautions.....

Do not allow product to leak into drains or waterways. If spill does contaminate waterways then inform authorities.

Methods and materials for containment and cleaning up

Contain spilled material and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Avoid prolonged or repeated skin contact. Use in well ventilated areas. Employees should wash hands and face before eating or drinking.

Conditions for safe storage, including any incompatibilities

Store away from sunlight. Do not store above 50 deg C. Keep container closed when not in use. Store away from all sources of heat and ignition. Do not puncture, incinerate or crush container. Store away from incompatible materials.

250 ppm

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	ACGIH TLV	OSHA PEL	NIOSH
	TWA STEL F	PEL STEL	REL

Acetone 250 ppm TLV 500 ppm 1,000 ppm Not established

CA ON AB: 500ppm (TWA); 750ppm (STEL)

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

CECTION OF EXILOGONE CONTROL OF PERCONNEL INCOLOR					
IN COREDIENTO		GIH TLV		HA PEL	NIOSH
INGREDIENTS	TWA	STEL	PEL	STEL	REL
Naphtha (petroleum), hydrotreated light	1640 mg/m3 (heptane)	Not established	Not established	Not established	Not established
	1100 ppm (IDLH)				
Carbon dioxide	5000 ppm	30000 ppm	5000 ppm	No data	5000 ppm 10 hours STEL 30000 ppm 15 minutes
	STEL 30000ppm ((3%)			
Respiratory/typeLocal exhaust ventilation is recommon when contaminant levels exceed the				erly fitted respirator	
Eye/type		Safety glasses with side- additional recommendation	shields. Consult your		pment supplier for
Gloves/ type			t supplier for		
Clothing/type	othing/type			uipment supplier for	
Footwear/type	Safety boots per local regulations. Consult your personal protective equipment supplier for			uipment supplier for	
Other/type		additional recommendations Emergency showers and eye wash stations should be available. Employees should wash			
Appropriate engineering	controls	their hands and face before Local exhaust should be	ore eating, drinking, d used to maintain leve	or using tobacco products els below the exposure li	s. mits.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state	>1. Not applicable. 0.7-0.8. > 56 °C. (acetone)95. (acetone)9. (ASTM D-56). (Heptane) Ignition Distance of greater than or equal to 75 cm No data.
---------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------

Reactivity Not reactive under normal conditions of use.

SECTION 10: STABILITY AND REACTIVITY

Chemical stability	Stable at normal temperatures and pressures.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid, including static	Keep away from heat. Electrostatic charge. Incompatible with strong oxidizers. Strong
discharge, shock or vibration	oxidizing agents.
Hazardous decomposition products	Carbon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Acetone	50,100 mg/m3 8 hours, rat	5,800 mg/kg (rat oral)
Naphtha (petroleum), hydrotreated light	73680 ppm 4 hours rat	>5000 mg/kg (oral, rat) >3160 mg/mg (dermal, rabbit)
Carbon dioxide	No data	No data

SECTION 11: TOXICOLOGICAL INFORMATION

Eye contact. Skin contact. Inhalation. Route of exposure.....

Symptoms related to the physical, chemical Irritation effects.

and toxicological characteristics

Skin corrosion\irritation..... Causes mild skin irritation. Prolonged contact may be more irritating.

Serious eye damage/eye irritation..... Causes serious eve irritation.

Respiratory or Skin Sensitization..... None known.

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen. Carcinogenicity.....

No component of this product present at levels greater than or equal to 0.1%. Reproductive effects..... Mutagenicity..... No component of this product present at levels greater than or equal to 0.1%.

STOŤ-SE.... May cause drowsiness or dizziness. May cause respiratory irritation.

Not classified.

Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical Aspiration Hazard.....

pneumonitis, which can be fatal.

SECTION 12: ECOLOGICAL INFORMATION

Environmental..... May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. Acetone (CAS#: 67-64-1): Toxicity to fish: LC50 >100 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 10294 mg/L, 48 hrs; Toxicity to algae:

not available . Heptanes including isomers (CAS#: 64742-49-0): Toxicity to fish: LL50 > 13.4 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EL50 3 mg/L, 48 hrs; Toxicity to algae: EL50 10-30 mg/L, 72 hrs. Chronic Toxicity Daphnia magna: NOEC 0.17 mg/L 21

days.

Persistence and degradability..... Product has not been tested. Bioaccumulative potential..... Product has not been tested. Product has not been tested.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal. and methods of disposal, including any contaminated packaging

Mobility in soil.....

Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG Classification..... UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity

exemption when shipped in containers less than 1 Litre.

UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons). DOT Classification (Road).....

IATA Classification (Air)..... UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity. Do not ship by air without

checking appropriate IATA regulations.

UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity. Check IMDG IMDG Classification (Marine).....

regulations for limited quantity exemptions.

Marine Pollutant.....

Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July

2, 2014) - we certify that classification of this product is correct. .

SECTION 15: REGULATORY INFORMATION

On Domestic Substances List (DSL). CEPA status.....

TSCA inventory status..... All components are listed.

OSHA.....SARA Title III This product is considered hazardous under the OSHA Hazard Communication Standard.

Section 302 - extremely hazardous None.

substances

Section 311/312 - hazard categories...... Immediate health, delayed health, fire hazard.

Section 313.....EPA hazardous air pollutants (HAPS) None.

None.

40CFR63 California Proposition 65.....

For more information, go to www.P65Warnings.ca.gov. None.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS.

SECTION 16: OTHER INFORMATION

Disclaimer:....

DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

2022-11-30. 2023-10-20