

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

SECTION 1. IDENTIFICATION

Product name : REPLAST EASY 3.5 MIN, Component A

Product code : 893.50007A

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Sub-category 1A

Carcinogenicity : Category 2

Reproductive toxicity : Category 1B

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Specific target organ toxicity : Category 1 (Lungs, Adrenal gland, Liver, Heart)
- repeated exposure

GHS label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H351 Suspected of causing cancer.
H360D May damage the unborn child.
H372 Causes damage to organs (Lungs, Adrenal gland, Liver, Heart) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.
P308 + P313 IF exposed or concerned: Get medical attention.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version 4.0 Revision Date: 12/15/2023 SDS Number: 5241954-00007 Date of last issue: 11/22/2022
Date of first issue: 10/30/2019

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Talc	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	$\geq 10 - < 30$ *
Ethylenediamine, propoxylated	1,2-Ethanediamine, polymer with 2-methyloxirane	25214-63-5	$\geq 1 - < 5$ *
3,3-Dimethylbutan-2-yl)({6-[(3,3-dimethylbutan-2-yl)amino]hexyl}amine)	1,6-Hexanediamine, N1,N6-bis(1,2,2-trimethylpropyl)-	957787-76-7	$\geq 1 - < 5$ *
3-Aminomethyl-3,5,5-trimethylcyclohexylamine	Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-	2855-13-2	$\geq 1 - < 5$ *
(Di-butylamino) diphenylmethane	Benzenamine, 4,4'-methylenebis[N-(1-methylpropyl)-	5285-60-9	$\geq 1 - < 5$ *
Silicon dioxide	Silica	7631-86-9	$\geq 1 - < 5$ *
Tributyl phosphate	Phosphoric acid tributyl ester	126-73-8	$\geq 0.1 - < 1$ *
Quartz	Crystallized silicon dioxide	14808-60-7	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

- Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
Suspected of causing cancer.
May damage the unborn child.
Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : | Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : | Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Do not breathe mist or vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : | Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations. |
| Materials to avoid | : | Do not store with the following product types:
Strong oxidizing agents |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version 4.0 Revision Date: 12/15/2023 SDS Number: 5241954-00007 Date of last issue: 11/22/2022
Date of first issue: 10/30/2019

Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

Recommended storage temperature : > 34 - < 50 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Talc	14807-96-6	TWAEV (respirable dust)	2 mg/m ³	CA QC OEL
		TWA (Respirable particulates)	2 mg/m ³	CA AB OEL
		TWA (Respirable)	2 mg/m ³	CA BC OEL
		TWA	2 fibres per cubic centimeter	CA ON OEL
		TWA (Respirable fraction)	2 mg/m ³	CA ON OEL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Silicon dioxide	7631-86-9	TWAEV (respirable dust)	6 mg/m ³	CA QC OEL
Tributyl phosphate	126-73-8	TWA	0.2 ppm 2.2 mg/m ³	CA AB OEL
		TWA	0.2 ppm	CA BC OEL
		TWAEV (inhalable fraction and vapour)	5 mg/m ³	CA QC OEL
		TWA (Inhalable fraction and vapor)	5 mg/m ³	ACGIH
Quartz	14808-60-7	TWA (Respirable particulates)	0.025 mg/m ³	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m ³	CA ON OEL
		TWAEV (respirable)	0.1 mg/m ³	CA QC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version 4.0 Revision Date: 12/15/2023 SDS Number: 5241954-00007 Date of last issue: 11/22/2022
Date of first issue: 10/30/2019

		dust)		
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Quartz

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Tributyl phosphate	126-73-8	Acetylcholinesterase activity	In red blood cells	End of shift	70 % of an individual's baseline	ACGIH BEI
		Butyrylcholinesterase activity	In serum or plasma	End of shift	60 % of an individual's baseline	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : PVA
Break through time : ≤ 300 min
Glove thickness : ≥ 0.08 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : light yellow

Odor : slight

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 200 °C

Flash point : > 93.4 °C
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : 3 hPa (20 °C)

Relative vapor density : > 1

Density : 1.288 g/cm³ (20 °C)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: > 177 °C
Viscosity	
Viscosity, kinematic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle size	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	: Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
---------------------	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Ethylenediamine, propoxylated:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

3,3-Dimethylbutan-2-yl){6-[(3,3-dimethylbutan-2-yl)amino]hexyl}amine):

Acute oral toxicity : LD50 (Rat): 550 mg/kg
Method: OECD Test Guideline 425

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 (Rat, male): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.01 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

(Di-butylamino) diphenylmethane:

Acute oral toxicity : LD50 (Rat, female): > 300 - 2,000 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Tributyl phosphate:

Acute oral toxicity : LD50 (Rat): 1,552 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.242 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 3,100 mg/kg

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Talc:

Species : Rabbit
Result : No skin irritation

Ethylenediamine, propoxylated:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

3,3-Dimethylbutan-2-yl)({6-[(3,3-dimethylbutan-2-yl)amino]hexyl}amine):

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Result : Corrosive after 3 minutes to 1 hour of exposure
Remarks : Based on national or regional regulation.

(Di-butylamino) diphenylmethane:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 439
Result	:	No skin irritation

Silicon dioxide:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Tributyl phosphate:

Result	:	Skin irritation
Remarks	:	Based on national or regional regulation.

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Talc:

Species	:	Rabbit
Result	:	No eye irritation

Ethylenediamine, propoxylated:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

3,3-Dimethylbutan-2-yl)({6-[(3,3-dimethylbutan-2-yl)amino]hexyl}amine):

Species	:	Bovine cornea
Method	:	OECD Test Guideline 437
Result	:	Irreversible effects on the eye

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Species	:	Rabbit
Result	:	Irreversible effects on the eye
Method	:	OECD Test Guideline 405

(Di-butylamino) diphenylmethane:

Species	:	Bovine cornea
Method	:	OECD Test Guideline 437
Result	:	No eye irritation

Silicon dioxide:

Species	:	Rabbit
---------	---	--------

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Result	: No eye irritation
Method	: OECD Test Guideline 405

Tributyl phosphate:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Talc:

Routes of exposure	: Skin contact
Species	: Humans
Result	: negative

Ethylenediamine, propoxylated:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

3,3-Dimethylbutan-2-yl){6-[(3,3-dimethylbutan-2-yl)amino]hexyl}amine):

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: positive

Assessment	: Probability or evidence of skin sensitization in humans
------------	---

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: positive

Assessment	: Probability or evidence of high skin sensitization rate in humans
------------	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

(Di-butylamino) diphenylmethane:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: positive
Assessment	: Probability or evidence of low to moderate skin sensitization rate in humans

Tributyl phosphate:

Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Talc:

Genotoxicity in vitro	: Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro) Result: negative
Genotoxicity in vivo	: Test Type: Chromosome aberration test in vitro Species: Rat Application Route: Ingestion Result: negative

Ethylenediamine, propoxylated:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
	: Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative

3,3-Dimethylbutan-2-yl)((6-[(3,3-dimethylbutan-2-yl)amino]hexyl)amine):

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	: Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

(Di-butylamino) diphenylmethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 490
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Silicon dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative

Tributyl phosphate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:

Talc:

Species : Mouse
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : negative

Silicon dioxide:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Tributyl phosphate:

Species : Rat
Application Route : Ingestion
Exposure time : 24 month(s)
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Quartz:

Species : Humans
Application Route : inhalation (dust/mist/fume)
Result : positive

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Remarks : This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Reproductive toxicity

May damage the unborn child.

Components:

Talc:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

3,3-Dimethylbutan-2-yl)((6-[(3,3-dimethylbutan-2-yl)amino]hexyl)amine):

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

(Di-butylamino) diphenylmethane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Silicon dioxide:

|| Effects on fetal development : Test Type: Embryo-fetal development

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019



Species: Rat
Application Route: Ingestion
Result: negative

Tributyl phosphate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lungs, Adrenal gland, Liver, Heart) through prolonged or repeated exposure.

Components:

3,3-Dimethylbutan-2-yl)({6-[(3,3-dimethylbutan-2-yl)amino]hexyl}amine):

Routes of exposure : Ingestion
Target Organs : Lungs, Adrenal gland, Liver, Heart
Assessment : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

(Di-butylamino) diphenylmethane:

Routes of exposure : Ingestion
Target Organs : Liver
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Quartz:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

3,3-Dimethylbutan-2-yl)({6-[(3,3-dimethylbutan-2-yl)amino]hexyl}amine):

Species : Rat
NOAEL : 5 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Method : OECD Test Guideline 407

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Species	: Rat
NOAEL	: 60 mg/kg
LOAEL	: 160 mg/kg
Application Route	: Ingestion
Exposure time	: 13 Weeks
Method	: OECD Test Guideline 408

(Di-butylamino) diphenylmethane:

Species	: Rat
NOAEL	: 15 mg/kg
Application Route	: Ingestion
Method	: OECD Test Guideline 422

Silicon dioxide:

Species	: Rat
NOAEL	: 1.3 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 13 Weeks

Tributyl phosphate:

Species	: Mouse
LOAEL	: > 300 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Quartz:

Species	: Humans
LOAEL	: 0.053 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Remarks	: This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Talc:

Toxicity to fish	: LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
Exposure time:	24 h

Ethylenediamine, propoxylated:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 4,600 mg/l Exposure time: 96 h Method: DIN 38412
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: Directive 67/548/EEC, Annex V, C.2.
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): 150.7 mg/l Exposure time: 72 h Method: Directive 67/548/EEC, Annex V, C.3. NOEC (Desmodesmus subspicatus (green algae)): 4.25 mg/l Exposure time: 72 h Method: Directive 67/548/EEC, Annex V, C.3.
Toxicity to microorganisms	:	NOEC: 700 mg/l Exposure time: 3 h Method: ISO 8192

3,3-Dimethylbutan-2-yl)((6-[(3,3-dimethylbutan-2-yl)amino]hexyl)amine):

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): 30.24 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to microorganisms	:	EC50: > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 110 mg/l Exposure time: 96 h Method: Regulation (EC) No. 440/2008, Annex, C.1
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 23 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC10 (Desmodesmus subspicatus (green algae)): 11.2 mg/l Exposure time: 72 h Method: Regulation (EC) No. 440/2008, Annex, C.3 ErC50 (Desmodesmus subspicatus (green algae)): > 50 mg/l Exposure time: 72 h Method: Regulation (EC) No. 440/2008, Annex, C.3
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 3 mg/l Exposure time: 21 d
Toxicity to microorganisms	:	EC10 (Pseudomonas putida): 1,120 mg/l

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Exposure time: 18 h
Test substance: Neutralized product

(Di-butylamino) diphenylmethane:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 0.61 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 0.21 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 0.187 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

EL10 (Pseudokirchneriella subcapitata (green algae)): 0.081 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (activated sludge): 232 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Silicon dioxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Tributyl phosphate:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 2.6 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): 2.8 mg/l Exposure time: 72 h EC10 (Desmodesmus subspicatus (green algae)): 0.92 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Oncorhynchus mykiss (rainbow trout)): 0.82 mg/l Exposure time: 95 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0.87 mg/l Exposure time: 21 d
Toxicity to microorganisms	:	EC50: 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity	:	No toxicity at the limit of solubility.
Chronic aquatic toxicity	:	No toxicity at the limit of solubility.

Persistence and degradability

Components:

Ethylenediamine, propoxylated:

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 9 % Exposure time: 28 d Method: Regulation (EC) No. 440/2008, Annex, C.4-D
------------------	---	--

3,3-Dimethylbutan-2-yl)({6-[(3,3-dimethylbutan-2-yl)amino]hexyl}amine):

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 44 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	---	---

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 8 % Exposure time: 28 d
------------------	---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Method: Regulation (EC) No. 440/2008, Annex, C.4-A

(Di-butylamino) diphenylmethane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Tributyl phosphate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

Ethylenediamine, propoxylated:

Partition coefficient: n- : log Pow: 0.3 - 1.6
octanol/water

3,3-Dimethylbutan-2-yl){6-[(3,3-dimethylbutan-2-yl)amino]hexyl}amine):

Partition coefficient: n- : log Pow: 2.1
octanol/water

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Partition coefficient: n- : log Pow: 0.99
octanol/water Method: OECD Test Guideline 107

(Di-butylamino) diphenylmethane:

Partition coefficient: n- : log Pow: 5.4
octanol/water Method: OECD Test Guideline 117

Tributyl phosphate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 6.9 - 20

Partition coefficient: n- : log Pow: 4
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Do not dispose of waste into sewer. Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations VOC content: 0 %
--	--

The ingredients of this product are reported in the following inventories:

DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	---	--

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
-------	---	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

Revision Date	:	12/15/2023
Date format	:	mm/dd/yyyy

SAFETY DATA SHEET

according to the Hazardous Products Regulations



REPLAST EASY 3.5 MIN, Component A

Version	Revision Date:	SDS Number:	Date of last issue: 11/22/2022
4.0	12/15/2023	5241954-00007	Date of first issue: 10/30/2019

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8