

**PTFE PIPE SEALANT, 50 mL**

Version 7.0      Revision Date: 04/26/2023      SDS Number: 10638415-00010      Date of last issue: 01/25/2023  
Date of first issue: 07/16/2015

---

**SECTION 1. IDENTIFICATION**

Product name : PTFE PIPE SEALANT, 50 mL

Product code : 893.511050

Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Adhesives

Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Not a hazardous substance or mixture.

**GHS label elements**

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

## PTFE PIPE SEALANT, 50 mL

Version 7.0      Revision Date: 04/26/2023      SDS Number: 10638415-00010      Date of last issue: 01/25/2023  
 Date of first issue: 07/16/2015

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Titanium dioxide	Titanium(IV) oxide	13463-67-7	$\geq 1 - < 5$ *
Cumene hydroperoxide	$\alpha$ , $\alpha$ -Dimethylbenzyl hydroperoxide	80-15-9	$\geq 0.1 - < 1$ *
2'-Phenylacetohydrazide	1-Acetyl-2-phenylhydrazine	114-83-0	$\geq 0.1 - < 1$ *

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Silicon oxides  
Carbon oxides

## PTFE PIPE SEALANT, 50 mL

Version	Revision Date:	SDS Number:	Date of last issue: 01/25/2023
7.0	04/26/2023	10638415-00010	Date of first issue: 07/16/2015

---

Nitrogen oxides (NO<sub>x</sub>)  
Sulfur oxides  
Fluorine compounds

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the

## PTFE PIPE SEALANT, 50 mL

Version 7.0      Revision Date: 04/26/2023      SDS Number: 10638415-00010      Date of last issue: 01/25/2023  
 Date of first issue: 07/16/2015

- environment.
- Conditions for safe storage : Keep in properly labeled containers.  
 Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents  
 Gases

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable particulate matter)	2.5 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH

**This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.**

Titanium dioxide

- Engineering measures : Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.

## Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Particulates type

## Hand protection

Material : Latex gloves  
 Break through time : 480 min  
 Glove thickness : 1 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

## PTFE PIPE SEALANT, 50 mL

Version	Revision Date:	SDS Number:	Date of last issue: 01/25/2023
7.0	04/26/2023	10638415-00010	Date of first issue: 07/16/2015

---

- workday.
- Eye protection : Wear the following personal protective equipment:  
Safety glasses  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
- || Skin and body protection : Skin should be washed after contact.
- || Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Color : white
- Odor : mild
- Odor Threshold : No data available
- pH : 6 - 7  
Concentration: 10 %
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : > 100 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable
- Flammability (liquids) : Ignitable (see flash point)
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available

## PTFE PIPE SEALANT, 50 mL

Version	Revision Date:	SDS Number:	Date of last issue: 01/25/2023
7.0	04/26/2023	10638415-00010	Date of first issue: 07/16/2015

---

Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.1 g/cm <sup>3</sup> (25 °C)
Solubility(ies)	:	
Water solubility	:	partly miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	180,000 - 300,000 mPa.s ( 25 °C) Method: Brookfield
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

## PTFE PIPE SEALANT, 50 mL

Version 7.0      Revision Date: 04/26/2023      SDS Number: 10638415-00010      Date of last issue: 01/25/2023  
Date of first issue: 07/16/2015

---

**Acute toxicity**

|| Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

**Components:****Titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

**Cumene hydroperoxide:**

Acute oral toxicity : LD50 (Rat, male): 382 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment  
Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit, male): 133.6 mg/kg

**2'-Phenylacetohydrazide:**

Acute oral toxicity : LD50 (Mouse): 270 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 300 - 2,000 mg/kg  
Remarks: Based on data from similar materials

**Skin corrosion/irritation**

|| Not classified based on available information.

**Components:****Titanium dioxide:**

Species : Rabbit  
Result : No skin irritation

## PTFE PIPE SEALANT, 50 mL

Version 7.0      Revision Date: 04/26/2023      SDS Number: 10638415-00010      Date of last issue: 01/25/2023  
Date of first issue: 07/16/2015

---

**Cumene hydroperoxide:**

Species : Rabbit  
Result : Corrosive after 4 hours or less of exposure

**2'-Phenylacetohydrazide:**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Serious eye damage/eye irritation**

|| Not classified based on available information.

**Components:****Titanium dioxide:**

Species : Rabbit  
Result : No eye irritation

**Cumene hydroperoxide:**

Species : Rabbit  
Result : Irreversible effects on the eye

**2'-Phenylacetohydrazide:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Remarks : Based on data from similar materials

**Respiratory or skin sensitization****Skin sensitization**

|| Not classified based on available information.

**Respiratory sensitization**

|| Not classified based on available information.

**Components:****Titanium dioxide:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Result : negative

**Germ cell mutagenicity**

|| Not classified based on available information.

**Components:****Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative



## PTFE PIPE SEALANT, 50 mL

Version 7.0      Revision Date: 04/26/2023      SDS Number: 10638415-00010      Date of last issue: 01/25/2023  
Date of first issue: 07/16/2015

---

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

**Cumene hydroperoxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: positive

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: positive

Test Type: Chromosome aberration test in vitro  
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Skin contact  
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

**2'-Phenylacetohydrazide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: positive

**Carcinogenicity**

|| Not classified based on available information.

**Components:****Titanium dioxide:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.  
This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

**Reproductive toxicity**

|| Not classified based on available information.

**Components:****Cumene hydroperoxide:**

## PTFE PIPE SEALANT, 50 mL

Version 7.0      Revision Date: 04/26/2023      SDS Number: 10638415-00010      Date of last issue: 01/25/2023  
Date of first issue: 07/16/2015

---

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

**STOT-single exposure**

|| Not classified based on available information.

**Components:****Cumene hydroperoxide:**

Assessment : May cause respiratory irritation.

**STOT-repeated exposure**

|| Not classified based on available information.

**Components:****Cumene hydroperoxide:**

Routes of exposure : Inhalation  
Target Organs : Lungs  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

**Repeated dose toxicity****Components:****Titanium dioxide:**

Species : Rat  
NOAEL : 24,000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days

Species : Rat  
NOAEL : 10 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 y

**Aspiration toxicity**

|| Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Titanium dioxide:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

## PTFE PIPE SEALANT, 50 mL

Version	Revision Date:	SDS Number:	Date of last issue: 01/25/2023
7.0	04/26/2023	10638415-00010	Date of first issue: 07/16/2015

---

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

**Cumene hydroperoxide:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.9 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 18.84 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 3.1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

**2'-Phenylacetohydrazide:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 0.1 - 1 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

**Persistence and degradability****Components:****Cumene hydroperoxide:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 3 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**2'-Phenylacetohydrazide:**

Biodegradability : Result: Readily biodegradable.  
Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Cumene hydroperoxide:**

**PTFE PIPE SEALANT, 50 mL**

Version 7.0      Revision Date: 04/26/2023      SDS Number: 10638415-00010      Date of last issue: 01/25/2023  
Date of first issue: 07/16/2015

---

Partition coefficient: n-octanol/water      :      log Pow: 1.6  
Method: OECD Test Guideline 117

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues      :      Dispose of in accordance with local regulations.

||      Do not dispose of waste into sewer.

Contaminated packaging      :      Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

Not regulated as a dangerous good

**Special precautions for user**

Not applicable

---

**SECTION 15. REGULATORY INFORMATION****SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH      :      USA. ACGIH Threshold Limit Values (TLV)  
CA AB OEL      :      Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

---

## PTFE PIPE SEALANT, 50 mL

Version	Revision Date:	SDS Number:	Date of last issue: 01/25/2023
7.0	04/26/2023	10638415-00010	Date of first issue: 07/16/2015

CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>
--	---	---

Revision Date	:	04/26/2023
Date format	:	mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be

**PTFE PIPE SEALANT, 50 mL**

Version	Revision Date:	SDS Number:	Date of last issue: 01/25/2023
7.0	04/26/2023	10638415-00010	Date of first issue: 07/16/2015

---

considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8