

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

SECTION 1. IDENTIFICATION

Product name : MASS AIR FLOW SENSOR CLEANER, 354 g
Product code : 893.560301
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1
Skin irritation : Category 2
Specific target organ toxicity : Category 3
- single exposure
Aspiration hazard : Category 1

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version 1.0 Revision Date: 11/10/2023 SDS Number: 11293610-00001 Date of last issue: -
Date of first issue: 11/10/2023

GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary Statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version 1.0 Revision Date: 11/10/2023 SDS Number: 11293610-00001 Date of last issue: -
Date of first issue: 11/10/2023

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light	Low boiling point hydrogen treated naphtha	64742-49-0	$\geq 60 - < 80$ *
Heptane	n-Heptane	142-82-5	$\geq 10 - < 30$ *
Carbon dioxide	Carbonic anhydride	124-38-9	$\geq 1 - < 5$ *
Methylcyclohexane	Cyclohexane, methyl-	108-87-2	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items em-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

ployed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : For outdoor use only
Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
- Recommended storage temperature : < 40 °C

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version 1.0 Revision Date: 11/10/2023 SDS Number: 11293610-00001 Date of last issue: -
Date of first issue: 11/10/2023

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated light	64742-49-0	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
Heptane	142-82-5	TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm 1,640 mg/m ³	CA AB OEL
		STEL	500 ppm 2,050 mg/m ³	CA AB OEL
		TWAEV	400 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m ³	CA AB OEL
		STEL	30,000 ppm 54,000 mg/m ³	CA AB OEL
		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		STEV	30,000 ppm 54,000 mg/m ³	CA QC OEL
		TWAEV	5,000 ppm 9,000 mg/m ³	CA QC OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Methylcyclohexane	108-87-2	TWA	400 ppm 1,610 mg/m ³	CA AB OEL
		TWA	400 ppm	CA BC OEL
		TWAEV	400 ppm 1,610 mg/m ³	CA QC OEL
		TWA	400 ppm	ACGIH

Engineering measures : Minimize workplace exposure concentrations.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

- Filter type : Self-contained breathing apparatus
- Hand protection
Material : Impervious gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Propellant : Carbon dioxide
- Color : No data available
- Odor : characteristic
- Odor Threshold : No data available
- pH : Solvent mixture; pH value determination not possible, no aqueous solution
- Melting point/freezing point : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Initial boiling point and boiling range : 88 °C

Flash point : -9 °C
Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 7.0 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapor pressure : 78 - 98 hPa (20 °C)

Relative vapor density : Not applicable

Density : No data available

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.6 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Heptane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 73.5 mg/l
Exposure time: 4 h
Test atmosphere: vapor

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Carbon dioxide:

Acute inhalation toxicity : LC50 (Rat): 40000 - 50000 ppm
Exposure time: 30 min
Test atmosphere: vapor

Methylcyclohexane:

Acute oral toxicity : LD50 (Mouse): 1,200 mg/kg
Acute inhalation toxicity : LC50 (Rat, male): > 26.3 mg/l
Exposure time: 1 h
Test atmosphere: vapor

Acute dermal toxicity : LD50: > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:

Naphtha (petroleum), hydrotreated light:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Heptane:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Methylcyclohexane:

Result : Skin irritation
Remarks : Based on national or regional regulation.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated light:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Heptane:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Methylcyclohexane:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated light:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Heptane:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Methylcyclohexane:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated light:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Intraperitoneal injection
Method: OPPTS 870.5395
Result: negative

Heptane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Methylcyclohexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated light:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Method : OECD Test Guideline 451
Result : negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version 1.0 Revision Date: 11/10/2023 SDS Number: 11293610-00001 Date of last issue: -
Date of first issue: 11/10/2023

Heptane:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Naphtha (petroleum), hydrotreated light:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 414
Result: negative

Heptane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: Based on data from similar materials

Methylcyclohexane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version 1.0 Revision Date: 11/10/2023 SDS Number: 11293610-00001 Date of last issue: -
Date of first issue: 11/10/2023

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Heptane:

Assessment : May cause drowsiness or dizziness.

Methylcyclohexane:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Naphtha (petroleum), hydrotreated light:

Species : Rat
NOAEL : > 20 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Method : OPPTS 870.3465
Remarks : Based on data from similar materials

Heptane:

Species : Rat
NOAEL : 12.35 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days

Methylcyclohexane:

Species : Rat, male
NOAEL : 1.6 mg/l
LOAEL : 8 mg/l
Application Route : inhalation (vapor)
Exposure time : 12 Months

Species : Rat
NOAEL : 250 mg/kg
LOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 28 - 54 Days
Method : OECD Test Guideline 422

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrotreated light:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-garded as if it causes a human aspiration toxicity hazard.

Heptane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-garded as if it causes a human aspiration toxicity hazard.

Methylcyclohexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-garded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Naphtha (petroleum), hydrotreated light:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 8.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): >
plants : 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01
- 0.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 16 mg/l
aquatic invertebrates (Chron- : Exposure time: 21 d
ic toxicity) : Method: OECD Test Guideline 211

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Heptane:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 4,924 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 0.2 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50: > 0.1 - 1 mg/l
plants Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): > 0.1 - 1 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity) Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Carbon dioxide:

Toxicity to fish : NOEC (Lepomis macrochirus (Bluegill sunfish)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h
Remarks: Based on data from similar materials

Methylcyclohexane:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 2.07 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.326 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.134
plants mg/l
Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)):
0.0221 mg/l
Exposure time: 72 h

Toxicity to microorganisms : NOEC (activated sludge): 2.73 mg/l
Exposure time: 336 h
Method: OECD Test Guideline 301D

Persistence and degradability

Components:

Naphtha (petroleum), hydrotreated light:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 77 %
Exposure time: 28 d

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Method: OECD Test Guideline 301F

Heptane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 10 d

Methylcyclohexane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

Naphtha (petroleum), hydrotreated light:

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Expert judgment

Heptane:

Partition coefficient: n-octanol/water : log Pow: 4.5

Carbon dioxide:

Partition coefficient: n-octanol/water : log Pow: 0.83

Methylcyclohexane:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 134 - 237

Partition coefficient: n-octanol/water : log Pow: 3.88

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Contaminated packaging : Please ensure aerosol cans are sprayed completely empty (including propellant)
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS
(Heptane, Methylcyclohexane)
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

ERG Code : 126
Marine pollutant : yes(Heptane, Methylcyclohexane)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: 95 %

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA QC OEL / TWA EV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MASS AIR FLOW SENSOR CLEANER, 354 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/10/2023	11293610-00001	Date of first issue: 11/10/2023

Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/10/2023
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8