

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

SECTION 1. IDENTIFICATION

Product name : DIESELCURE, 80 mL
Product code : 893.567080
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : 1-800-263-5002
Telefax : 1-905-564-3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Additive
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 4
Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 4
Skin irritation : Category 2
Eye irritation : Category 2A
Reproductive toxicity : Category 1B

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H227 Combustible liquid.
H302 + H332 Harmful if swallowed or if inhaled.
H315 Causes skin irritation.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version 1.1 Revision Date: 02/27/2026 SDS Number: 11605386-00002 Date of last issue: 12/09/2025
Date of first issue: 12/09/2025

H319 Causes serious eye irritation.
H360D May damage the unborn child.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
2-Butoxyethanol	1-Butoxy-2-hydroxyethan	111-76-2	>= 80 - < 100 *

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version 1.1 Revision Date: 02/27/2026 SDS Number: 11605386-00002 Date of last issue: 12/09/2025
Date of first issue: 12/09/2025

(2-Methoxymethylethoxy)propanol	PPG-2 Methyl ether	34590-94-8	$\geq 10 - < 30$ *
Diethylene glycol methyl ether	2-(2-methoxyethoxy)ethanol	111-77-3	$\geq 3 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed or if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May damage the unborn child.
No information available.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire : Do not use a solid water stream as it may scatter and spread

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

fighting	fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Carbon oxides
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g., by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version 1.1 Revision Date: 02/27/2026 SDS Number: 11605386-00002 Date of last issue: 12/09/2025
Date of first issue: 12/09/2025

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : For outdoor use only
Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases
- Recommended storage temperature : > -70 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-Butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
(2-Methoxymethylethoxy)propanol	34590-94-8	TWA	100 ppm 606 mg/m ³	CA AB OEL
		STEL	150 ppm 909 mg/m ³	CA AB OEL
		TWAEV	100 ppm 606 mg/m ³	CA QC OEL
		STEV	150 ppm	CA QC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version 1.1 Revision Date: 02/27/2026 SDS Number: 11605386-00002 Date of last issue: 12/09/2025
Date of first issue: 12/09/2025

			909 mg/m ³	
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
2-Butoxyethanol	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g creatinine	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Organic vapor Type

Hand protection

Material : Fluorinated rubber

Break through time : ≥ 480 min

Glove thickness : 0.4 mm

Material : butyl-rubber

Break through time : ≥ 480 min

Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	green, clear
Odor	:	unpleasant
Odor Threshold	:	No data available
pH	:	7 Concentration: 100 %
Melting point/freezing point	:	-76.92 °C
Initial boiling point and boiling range	:	171 °C
Flash point	:	72.5 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	11.39 %(V)
Lower explosion limit / Lower flammability limit	:	1.13 %(V)
Vapor pressure	:	0.8 hPa (20 °C)
Relative vapor density	:	4.1
Density	:	0.9112 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	completely soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	259 °C
Decomposition temperature	:	No data available
Viscosity		

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

Viscosity, kinematic	:	2.266 mm ² /s (20 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Combustible liquid. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 1,313 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 12.22 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

Components:

2-Butoxyethanol:

Acute oral toxicity	:	LD50 (Guinea pig): 1,200 mg/kg
Acute inhalation toxicity	:	Acute toxicity estimate: 11 mg/l Exposure time: 4 h Test atmosphere: vapor

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

Method: Expert judgment
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

(2-Methoxymethylethoxy)propanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1.667 mg/l
Exposure time: 7 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 9,510 mg/kg

Diethylene glycol methyl ether:

Acute oral toxicity : LD50 (Guinea pig): 4,160 mg/kg

Acute dermal toxicity : LD50 (Rabbit, male): 9,404 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

2-Butoxyethanol:

Species	: Rabbit
Method	: Directive 67/548/EEC, Annex V, B.4.
Result	: Skin irritation

(2-Methoxymethylethoxy)propanol:

Species	: Rabbit
Result	: No skin irritation

Diethylene glycol methyl ether:

Species	: Rabbit
Result	: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

2-Butoxyethanol:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days
Method	: OECD Test Guideline 405

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

(2-Methoxymethylethoxy)propanol:

Species	:	Rabbit
Result	:	No eye irritation

Diethylene glycol methyl ether:

Species	:	Rabbit
Result	:	No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

2-Butoxyethanol:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

(2-Methoxymethylethoxy)propanol:

Test Type	:	Human repeat insult patch test (HRIPT)
Routes of exposure	:	Skin contact
Species	:	Humans
Result	:	negative

Diethylene glycol methyl ether:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:

2-Butoxyethanol:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	---	--

	:	Test Type: Chromosome aberration test in vitro Result: negative
--	---	--

	:	Test Type: In vitro mammalian cell gene mutation test
--	---	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

(2-Methoxymethylethoxy)propanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: *Saacharomyces cerevisiae*, mitotic recombination assay (in vitro)
Result: negative

Diethylene glycol methyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

Components:

2-Butoxyethanol:

Species	:	Rat
Application Route	:	inhalation (vapor)
Exposure time	:	2 Years
Result	:	negative

(2-Methoxymethylethoxy)propanol:

Species	:	Rat
Application Route	:	inhalation (vapor)
Exposure time	:	2 Years
Method	:	OECD Test Guideline 453
Result	:	negative
Remarks	:	Based on data from similar materials

Reproductive toxicity

May damage the unborn child.

Components:

2-Butoxyethanol:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Mouse Application Route: Ingestion Result: negative
----------------------	---	---

Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative
------------------------------	---	---

	:	Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Result: negative
--	---	--

(2-Methoxymethylethoxy)propanol:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Method: OECD Test Guideline 416 Result: negative Remarks: Based on data from similar materials
----------------------	---	--

Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Result: negative
------------------------------	---	--

Diethylene glycol methyl ether:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

Diethylene glycol methyl ether:

Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity

Components:

(2-Methoxymethylethoxy)propanol:

Species : Rat
NOAEL : 1.21 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 4 Weeks

Species : Rabbit
NOAEL : 2,850 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

Diethylene glycol methyl ether:

Species : Rat, male
NOAEL : 900 mg/kg
Application Route : Ingestion
Exposure time : 6 Weeks

Species : Rat
NOAEL : > 1.06 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks

Species : Guinea pig
NOAEL : 40 mg/kg

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

LOAEL : 200 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2-Butoxyethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,464 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,800 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 1,840 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 679 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 21 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 134 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

(2-Methoxymethylethoxy)propanol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,919 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 969 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

NOEC (Pseudokirchneriella subcapitata (green algae)): 969 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): ≥ 0.5 mg/l
Exposure time: 22 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): 4,168 mg/l
Exposure time: 18 h

Diethylene glycol methyl ether:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5,741 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,192 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Raphidocelis subcapitata (freshwater green alga)): $> 1,000$ mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): $> 1,000$ mg/l
Exposure time: 17 h
Method: DIN 38 412 Part 8

Persistence and degradability

Components:

2-Butoxyethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90.4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

(2-Methoxymethylethoxy)propanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 76 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: The test was conducted according to guideline

Diethylene glycol methyl ether:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

Bioaccumulative potential

Components:

2-Butoxyethanol:

Partition coefficient: n-octanol/water : log Pow: 0.81

(2-Methoxymethylethoxy)propanol:

Partition coefficient: n-octanol/water : log Pow: 0.004

Diethylene glycol methyl ether:

Partition coefficient: n-octanol/water : log Pow: -0.47

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	: Do not dispose of waste into sewer. Dispose of in accordance with local regulations.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

Remarks : Display "inhalation hazard" mark on package in accordance with TDG 4.23.

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: 99.99 % / 911.2 g/l

The ingredients of this product are reported in the following inventories:

CA. DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

Additional regulatory information

Diethylene glycol methyl ether 111-77-3

This product contains CAS 111-77-3, which is subject to a Significant New Activity No. 111-773 S', per Canada Gazette October 10, 2012.

Canadian lists

No substances are subject to CEPA Section 84 Ministerial Conditions.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA BC OEL / STEL	: short-term exposure limit
CA QC OEL / TWA EV	: Time-weighted average exposure value
CA QC OEL / STEV	: Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with

SAFETY DATA SHEET

according to the Hazardous Products Regulations



DIESELCURE, 80 mL

Version	Revision Date:	SDS Number:	Date of last issue: 12/09/2025
1.1	02/27/2026	11605386-00002	Date of first issue: 12/09/2025

x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 02/27/2026
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8