

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

### SECTION 1. IDENTIFICATION

Product name : CONTACT SL, Protective lacquer, 167 g  
Product code : 893.70  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : 1-800-263-5002  
Telefax : 1-905-564-3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences impliquant un déversement, incendie, explosion ou  
exposition: CHEMTREC (24/7): 1-800-424-9300  
E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Solvent-borne coatings  
Preservative  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1  
Eye irritation : Category 2A  
Specific target organ toxicity : Category 3  
- single exposure  
Simple Asphyxiant : Category 1

#### GHS label elements



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
May displace oxygen and cause rapid suffocation.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear eye protection and face protection.

**Response:**  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical attention.

**Storage:**  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Repeated exposure may cause skin dryness or cracking.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Ethyl acetate	Acetic acid ethyl	141-78-6	>= 30 - < 60 *

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

	ester		
Butane	Butyl hydride	106-97-8	>= 10 - < 30 *
2-Methoxy-1-methylethyl acetate	2-Propanol, 1-methoxy-, 2-acetate	108-65-6	>= 10 - < 30 *
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	>= 10 - < 30 *
Propane	Dimethylmethane	74-98-6	>= 10 - < 30 *

\* Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Gas reduces oxygen available for breathing.  
Prolonged or repeated contact may dry skin and cause irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May displace oxygen and cause rapid suffocation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/10/2024
10.2	07/30/2024	10774450-00012	Date of first issue: 07/18/2010

---

- Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items em-

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/10/2024
10.2	07/30/2024	10774450-00012	Date of first issue: 07/18/2010

---

ployed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing spray.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethyl acetate	141-78-6	TWA	400 ppm 1,440 mg/m <sup>3</sup>	CA AB OEL
		TWA	150 ppm	CA BC OEL
		TWAEV	400 ppm 1,440 mg/m <sup>3</sup>	CA QC OEL
Butane	106-97-8	TWA	400 ppm	ACGIH
		TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		STEL	1,000 ppm	CA BC OEL
2-Methoxy-1-methylethyl acetate	108-65-6	STEL	1,000 ppm	ACGIH
		TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
n-Butyl acetate	123-86-4	TWA	50 ppm 270 mg/m <sup>3</sup>	CA ON OEL
		STEL	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL
		TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
Propane	74-98-6	TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

#### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

- Hand protection  
Material : butyl-rubber  
Break through time : >= 60 min  
Glove thickness : 0.5 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Propellant : Propane, Butane, Isobutane
- Color : colorless
- Odor : characteristic
- Odor Threshold : No data available
- pH : Solvent mixture; pH value determination not possible, no aqueous solution
- Melting point/freezing point : No data available

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

Initial boiling point and boiling range : -44 °C

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 11.5 %(V)

Lower explosion limit / Lower flammability limit : 1.2 %(V)

Vapor pressure : 4,200 hPa (20 °C)

Relative vapor density : Not applicable

Density : 0.93 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : partly miscible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 315 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.  
Incompatible materials : Oxidizing agents  
Hazardous decomposition products : No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

#### Components:

##### **Ethyl acetate:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 22.5 mg/l  
Exposure time: 6 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

##### **Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

##### **2-Methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat, female): 5,155 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 9.34 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### **n-Butyl acetate:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### **Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **Ethyl acetate:**

Species : Rabbit  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **2-Methoxy-1-methylethyl acetate:**

Species : Rabbit  
Result : No skin irritation

#### **n-Butyl acetate:**

Species : Rabbit  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Components:**

#### **Ethyl acetate:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

### 2-Methoxy-1-methylethyl acetate:

Species : Rabbit  
Result : No eye irritation

### n-Butyl acetate:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Components:

#### Ethyl acetate:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### 2-Methoxy-1-methylethyl acetate:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### n-Butyl acetate:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Ethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Hamster  
Application Route: Ingestion  
Result: negative

### **Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### **2-Methoxy-1-methylethyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

### **n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

### **Propane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **2-Methoxy-1-methylethyl acetate:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : negative  
Remarks : Based on data from similar materials

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Ethyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Mouse  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Inhalation  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

#### **Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

Result: negative

### **2-Methoxy-1-methylethyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **n-Butyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

### **Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

### **STOT-single exposure**

May cause drowsiness or dizziness.  
May displace oxygen and cause rapid suffocation.

### **Components:**

#### **Ethyl acetate:**

Assessment : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

### **Butane:**

Assessment : May cause drowsiness or dizziness.

### **2-Methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

### **n-Butyl acetate:**

Assessment : May cause drowsiness or dizziness.

### **Propane:**

Assessment : May cause drowsiness or dizziness.

### **STOT-repeated exposure**

Not classified based on available information.

### **Repeated dose toxicity**

#### **Components:**

#### **Ethyl acetate:**

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 3,600 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 1.28 mg/l  
LOAEL : 2.75 mg/kg  
Application Route : inhalation (vapor)  
Exposure time : 94 Days

#### **Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

#### **2-Methoxy-1-methylethyl acetate:**

Species : Rat  
NOAEL :  $\geq 1,000$  mg/kg  
Application Route : Ingestion  
Exposure time : 41 - 45 Days  
Method : OECD Test Guideline 422

Species : Rat  
NOAEL :  $> 1$  mg/l  
Application Route : inhalation (vapor)  
Exposure time : 2 y

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

Method : OECD Test Guideline 453  
Remarks : Based on data from similar materials

Species : Rabbit  
NOAEL : > 200 mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

### **n-Butyl acetate:**

Species : Rat  
NOAEL : 2.4 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days

### **Propane:**

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

### **Aspiration toxicity**

Not classified based on available information.

### **Experience with human exposure**

### **Components:**

#### **Ethyl acetate:**

Eye contact : Target Organs: Eye  
Symptoms: Irritation

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Components:**

#### **Ethyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 3,090 mg/l  
aquatic invertebrates : Exposure time: 24 h  
Method: DIN 38412

Toxicity to algae/aquatic : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l  
plants : Exposure time: 72 h  
Method: OECD Test Guideline 201



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): > 1 - 9.65 mg/l  
Exposure time: 32 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 2.4 mg/l  
Exposure time: 24 d

Toxicity to microorganisms : EC10 (Photobacterium phosphoreum): 1,650 mg/l  
Exposure time: 0.25 h

### 2-Methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)): >= 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 100 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (activated sludge): > 1,000 mg/l  
Exposure time: 30 min

### n-Butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (Water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

### Persistence and degradability

#### Components:

##### **Ethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 69 %  
Exposure time: 20 d

##### **Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

##### **2-Methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **n-Butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

### Bioaccumulative potential

#### Components:

##### **Ethyl acetate:**

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): 30

Partition coefficient: n-octanol/water : log Pow: 0.68

##### **Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.31

##### **2-Methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1.2

##### **n-Butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3

#### **Mobility in soil**

No data available

#### **Other adverse effects**

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

---

## SECTION 14. TRANSPORT INFORMATION

### **International Regulations**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

---

### UNRTDG

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Environmentally hazardous : no

### IATA-DGR

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

### IMDG-Code

UN number : UN 1950  
Proper shipping name : AEROSOLS  
  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

UN number : UN 1950  
Proper shipping name : AEROSOLS  
  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

**Volatile organic compounds (VOC) content**      CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -  
Guidelines for VOC in Consumer Products  
VOC content: 74.58 % / 693.55 g/l

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version 10.2      Revision Date: 07/30/2024      SDS Number: 10774450-00012      Date of last issue: 06/10/2024  
Date of first issue: 07/18/2010

### The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA AB OEL / STEL : 15-minute occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA BC OEL / STEL : short-term exposure limit  
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)  
CA QC OEL / TWA EV : Time-weighted average exposure value  
CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation,

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## CONTACT SL, Protective lacquer, 167 g

Version	Revision Date:	SDS Number:	Date of last issue: 06/10/2024
10.2	07/30/2024	10774450-00012	Date of first issue: 07/18/2010

---

Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 07/30/2024  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8