

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

### SECTION 1. IDENTIFICATION

Product name : HIGH PERFORMANCE GREASE, 400 g  
Product code : 893.880  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : 1-800-263-5002  
Telefax : 1-905-564-3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300  
E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Lubricants and lubricant additives  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

#### GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

#### Other hazards

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version 1.0      Revision Date: 04/02/2025      SDS Number: 11524003-00001      Date of last issue: -  
Date of first issue: 04/02/2025

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	No data available	64742-52-5	$\geq 60 - < 80$ *
Residual oils (petroleum), solvent-dewaxed	No data available	64742-62-7	$\geq 10 - < 30$ *
12-Hydroxy lithium stearate	Octadecanoic acid, 12-hydroxy-, lithium salt (1:1)	7620-77-1	$\geq 5 - < 10$ *
Dilithium azelate	Nonanedioic acid, dilithium salt	38900-29-7	$\geq 1 - < 5$ *

\* Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version 1.0      Revision Date: 04/02/2025      SDS Number: 11524003-00001      Date of last issue: -  
Date of first issue: 04/02/2025

### CONTROLS/PERSONAL PROTECTION section.

- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Gases
- Recommended storage temperature : < 45 °C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m <sup>3</sup>	CA QC OEL
		TWA (Mist)	1 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
Residual oils (petroleum), solvent-dewaxed	64742-62-7	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m <sup>3</sup>	CA QC OEL
		TWA (Mist)	1 mg/m <sup>3</sup>	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Inhalable)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (Res-	3 mg/m <sup>3</sup>	CA BC OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version 1.0      Revision Date: 04/02/2025      SDS Number: 11524003-00001      Date of last issue: -  
Date of first issue: 04/02/2025

		pirable)		
		TWAEV (inhalable dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWAEV (respirable aerosol fraction)	3 mg/m <sup>3</sup>	CA QC OEL
		TWA (Inhalable particulate matter)	10 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable particulate matter)	3 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

### Hand protection

Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : >= 0.38 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety glasses  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Color	:	yellow, brown
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	> 150 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	< 1,000 kg/m <sup>3</sup> (25 °C)
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

Viscosity, kinematic	:	210 mm <sup>2</sup> /s ( 40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
---------------------	---	--

#### Components:

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

### Residual oils (petroleum), solvent-dewaxed:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

### 12-Hydroxy lithium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity

### Dilithium azelate:

Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg  
Method: OECD Test Guideline 420  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### Residual oils (petroleum), solvent-dewaxed:

Species : Rabbit

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

Result : No skin irritation  
Remarks : Based on data from similar materials

### 12-Hydroxy lithium stearate:

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Dilithium azelate:

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 439  
Remarks : Based on data from similar materials

Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

#### Residual oils (petroleum), solvent-dewaxed:

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

### 12-Hydroxy lithium stearate:

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

### Dilithium azelate:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version 1.0      Revision Date: 04/02/2025      SDS Number: 11524003-00001      Date of last issue: -  
Date of first issue: 04/02/2025

---

### Components:

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

#### **Residual oils (petroleum), solvent-dewaxed:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **12-Hydroxy lithium stearate:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

#### **Dilithium azelate:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative  
Remarks : Based on data from similar materials

### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

#### **Residual oils (petroleum), solvent-dewaxed:**

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

### Dilithium azelate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

### Components:

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 78 weeks  
Method : OECD Test Guideline 451  
Result : negative

#### **Residual oils (petroleum), solvent-dewaxed:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 78 weeks  
Result : negative  
Remarks : Based on data from similar materials

### Reproductive toxicity

Not classified based on available information.

### Components:

#### **Residual oils (petroleum), solvent-dewaxed:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

test  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Skin contact  
Result: negative

### **Dilithium azelate:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Skin contact  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Skin contact  
Result: negative  
Remarks: Based on data from similar materials

### **STOT-single exposure**

Not classified based on available information.

### **STOT-repeated exposure**

Not classified based on available information.

### **Components:**

#### **12-Hydroxy lithium stearate:**

Routes of exposure : Ingestion  
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

### **Repeated dose toxicity**

### **Components:**

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rat  
NOAEL : > 0.98 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 28 Days  
Remarks : Based on data from similar materials

#### **Residual oils (petroleum), solvent-dewaxed:**

Species : Rat  
NOAEL : 1,000 mg/kg

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version 1.0      Revision Date: 04/02/2025      SDS Number: 11524003-00001      Date of last issue: -  
Date of first issue: 04/02/2025

---

Application Route : Skin contact  
Exposure time : 13 Weeks  
Method : OECD Test Guideline 411  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : > 980 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 4 Weeks  
Remarks : Based on data from similar materials

### 12-Hydroxy lithium stearate:

Species : Rat  
NOAEL : > 88 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### Dilithium azelate:

Species : Rat  
NOAEL : 1,089.75 mg/kg  
Application Route : Skin contact  
Exposure time : 28 Days  
Remarks : Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron- : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version 1.0      Revision Date: 04/02/2025      SDS Number: 11524003-00001      Date of last issue: -  
Date of first issue: 04/02/2025

---

ic toxicity)      Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l  
Exposure time: 10 min  
Remarks: Based on data from similar materials

### Residual oils (petroleum), solvent-dewaxed:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l  
Exposure time: 10 min  
Remarks: Based on data from similar materials

### 12-Hydroxy lithium stearate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### Dilithium azelate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version 1.0      Revision Date: 04/02/2025      SDS Number: 11524003-00001      Date of last issue: -  
Date of first issue: 04/02/2025

---

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

### Persistence and degradability

#### Components:

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

##### **Residual oils (petroleum), solvent-dewaxed:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B  
Remarks: Based on data from similar materials

##### **12-Hydroxy lithium stearate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

##### **Dilithium azelate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 30 d  
Method: OECD Test Guideline 301D  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

### Bioaccumulative potential

#### Components:

##### Dilithium azelate:

Partition coefficient: n-octanol/water : log Pow: -3.53

##### Mobility in soil

No data available

##### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

#### TDG

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

---

## SECTION 15. REGULATORY INFORMATION

### Volatile organic compounds (VOC) content

CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -  
Guidelines for VOC in Consumer Products  
VOC content: 0 % / 0 g/l

---

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

### The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWA EV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recom-

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HIGH PERFORMANCE GREASE, 400 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/02/2025	11524003-00001	Date of first issue: 04/02/2025

---

recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 04/02/2025  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8