

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

SECTION 1. IDENTIFICATION

Product name : PLASTIC WELDER, Adhesive component, 19 mL

Product code : 893.910122

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3
- single exposure

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H227 Combustible liquid.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Ethyl 2-cyanoacrylate	1-methyl-1-phenylethylhydroperoxide	7085-85-0	$\geq 80 - \leq 100$ *
Isopropyl 2-cyanoacrylate	2-Propenoic acid, 2-cyano-, 1-methylethyl ester	10586-17-1	$\geq 5 - < 10$ *
1,4-Benzenediol	Hydroquinone	123-31-9	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- | | |
|-------------------------|--|
| General advice | : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| If inhaled | : If inhaled, remove to fresh air.
Get medical attention. |
| In case of skin contact | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
Eyelid bonding: see a doctor. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
Get medical attention. |

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed

: Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Suspected of causing cancer.

Protection of first-aiders

: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician

: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

: Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media

: High volume water jet

Specific hazards during fire fighting

: Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products

: Carbon oxides
Nitrogen oxides (NO_x)

Specific extinguishing methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions

: Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8 Revision Date: 05/30/2023 SDS Number: 10776941-00007 Date of last issue: 11/17/2022
 Date of first issue: 05/30/2017

Store in accordance with the particular national regulations.
 Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents
 Explosives
 Gases

Storage period : 12 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethyl 2-cyanoacrylate	7085-85-0	TWA	0.2 ppm 1 mg/m ³	CA AB OEL
		TWA	0.2 ppm	CA BC OEL
		TWA	0.2 ppm	ACGIH
		STEL	1 ppm	ACGIH
1,4-Benzenediol	123-31-9	TWA	2 mg/m ³	CA AB OEL
		TWA	1 mg/m ³	CA BC OEL
		TWAEV	1 mg/m ³	CA QC OEL
		TWA	1 mg/m ³	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
1,4-Benzenediol	123-31-9	Methemoglobin	In blood	During or at the end of the shift	5 % Hb	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection
 Material : Nitrile rubber

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

- | | |
|--------------------------|--|
| Remarks | : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often! |
| Eye protection | : Wear the following personal protective equipment:
Safety goggles |
| Skin and body protection | : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). |
| Hygiene measures | : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- | | |
|---|-------------------------|
| Appearance | : liquid |
| Color | : light yellow |
| Odor | : irritating |
| Odor Threshold | : No data available |
| pH | : No data available |
| Melting point/freezing point | : No data available |
| Initial boiling point and boiling range | : 84 - 86 °C
(4 hPa) |
| Flash point | : 83 °C |

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

Method: closed cup

Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	1.33 hPa (20 °C)
Relative vapor density	:	ca. 1
Relative density	:	No data available
Density	:	1.02 - 1.06 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	practically insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	30 - 50 mPa.s (20 °C)
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Combustible liquid. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Ethyl 2-cyanoacrylate:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Isopropyl 2-cyanoacrylate:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg

1,4-Benzenediol:

Acute oral toxicity	:	LD50 (Rat): 375 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC0 (Rat): 7.8 mg/l Exposure time: 1 h Test atmosphere: dust/mist Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

PLASTIC WELDER, Adhesive component, 19 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2022
1.8	05/30/2023	10776941-00007	Date of first issue: 05/30/2017

Components:**Ethyl 2-cyanoacrylate:**

Species	:	Rabbit
Result	:	Skin irritation

Isopropyl 2-cyanoacrylate:

Species	:	Rabbit
Result	:	Skin irritation
Remarks	:	Based on data from similar materials

1,4-Benzenediol:

Species	:	Rat
Result	:	No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Ethyl 2-cyanoacrylate:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Isopropyl 2-cyanoacrylate:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Remarks	:	Based on data from similar materials

1,4-Benzenediol:

Result	:	Irreversible effects on the eye
Remarks	:	Based on national or regional regulation.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:**Isopropyl 2-cyanoacrylate:**

Result	:	negative
--------	---	----------

1,4-Benzenediol:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

Result : positive

Assessment : Probability or evidence of skin sensitization in humans

Germ cell mutagenicity

Not classified based on available information.

Components:**Ethyl 2-cyanoacrylate:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Isopropyl 2-cyanoacrylate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

1,4-Benzenediol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: positive

Germ cell mutagenicity - Assessment : Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

Carcinogenicity

Suspected of causing cancer.

Components:**1,4-Benzenediol:**

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : positive

PLASTIC WELDER, Adhesive component, 19 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2022
1.8	05/30/2023	10776941-00007	Date of first issue: 05/30/2017

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

Components:**1,4-Benzenediol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

May cause respiratory irritation.

Components:**Ethyl 2-cyanoacrylate:**

Assessment : May cause respiratory irritation.

Isopropyl 2-cyanoacrylate:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****1,4-Benzenediol:**

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Aspiration toxicity

Not classified based on available information.

PLASTIC WELDER, Adhesive component, 19 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2022
1.8	05/30/2023	10776941-00007	Date of first issue: 05/30/2017

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****1,4-Benzenediol:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 0.638 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0.061 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 0.33 mg/l Exposure time: 72 h EC10 (Pseudokirchneriella subcapitata (green algae)): 0.034 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0.0029 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	:	IC50: 71 mg/l Exposure time: 2 h

Persistence and degradability**Components:****Ethyl 2-cyanoacrylate:**

Biodegradability	:	Remarks: No data available
------------------	---	----------------------------

1,4-Benzenediol:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 80 % Exposure time: 28 d
------------------	---	---

Bioaccumulative potential**Components:****Ethyl 2-cyanoacrylate:**

Partition coefficient: n-octanol/water	:	Pow: 0.776
--	---	------------

Isopropyl 2-cyanoacrylate:

Partition coefficient: n-octanol/water	:	log Pow: 1.83
--	---	---------------

PLASTIC WELDER, Adhesive component, 19 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2022
1.8	05/30/2023	10776941-00007	Date of first issue: 05/30/2017

1,4-Benzenediol:

Partition coefficient: n-octanol/water : log Pow: 0.59

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

UN/ID No.	: UN 3334
Proper shipping name	: Aviation regulated liquid, n.o.s. (Ethyl 2-cyanoacrylate, Isopropyl 2-cyanoacrylate)
Class	: 9
Packing group	: III
Labels	: Miscellaneous
Packing instruction (cargo aircraft)	: 964
Packing instruction (passenger aircraft)	: 964

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

PLASTIC WELDER, Adhesive component, 19 mL

Version 1.8	Revision Date: 05/30/2023	SDS Number: 10776941-00007	Date of last issue: 11/17/2022 Date of first issue: 05/30/2017
----------------	------------------------------	-------------------------------	---

TDG

Not regulated as a dangerous good

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products VOC content: 2 % / 20 g/l
---	---

The ingredients of this product are reported in the following inventories:

DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	--

Additional regulatory information

1,4-Benzenediol	123-31-9
-----------------	----------

This product contains CAS 123-31-9, which is subject to a Significant New Activity No. 123-31-9 S', per Canada Gazette December 21, 2011

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA QC OEL / TWAEV	: Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

PLASTIC WELDER, Adhesive component, 19 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/17/2022
1.8	05/30/2023	10776941-00007	Date of first issue: 05/30/2017

tem; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/30/2023
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8