

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

SECTION 1. IDENTIFICATION

Product name : PLASTIC WELDER, Activator component, 59 mL

Product code : 893.910123

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Solvent mixture
Primers

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 4

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017





Eye irritation : Category 2A

Carcinogenicity : Category 1B

Specific target organ toxicity : Category 3
- single exposure

Specific target organ toxicity : Category 2 (Reproductive organs)
- repeated exposure

GHS label elements

Hazard pictograms :    

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H302 + H312 Harmful if swallowed or in contact with skin.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
H373 May cause damage to organs (Reproductive organs) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating and lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:
P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth.
P302 + P352 + P312 IF ON SKIN: Wash with plenty of soap and water. Call a doctor if you feel unwell.

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Vapors may form explosive mixture with air.
Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Acetone	2-Propanone	67-64-1	$\geq 80 - \leq 100$ *
N,N-dimethyl-p-toluidine	N,N,4-trimethylaniline	99-97-8	$\geq 10 - < 30$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

- Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed or in contact with skin.
Causes serious eye irritation.
Toxic if inhaled.
May cause drowsiness or dizziness.
May cause cancer.
May cause damage to organs through prolonged or repeated exposure.
Prolonged or repeated contact may dry skin and cause irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

so.
Evacuate area.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for fire-fighters Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SECTION 7. HANDLING AND STORAGE

- | | |
|-------------------------|--|
| Technical measures | : Ground and bond container and receiving equipment.
See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment. |
| Advice on safe handling | : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow. |

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

Do not get in eyes.
 Wash skin thoroughly after handling.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Non-sparking tools should be used.
 Keep container tightly closed.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharges.
 Do not eat, drink or smoke when using this product.
 Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
 Store locked up.
 Keep tightly closed.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents
 Self-reactive substances and mixtures
 Organic peroxides
 Flammable solids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which in contact with water emit flammable gases
 Explosives
 Gases
 Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	500 ppm 1,190 mg/m ³	CA QC OEL
		STEV	1,000 ppm 2,380 mg/m ³	CA QC OEL
		TWA	250 ppm	ACGIH

PLASTIC WELDER, Activator component, 59 mL

Version 4.0 Revision Date: 11/11/2022 SDS Number: 10786623-00007 Date of last issue: 06/07/2022
 Date of first issue: 04/26/2017

		STEL	500 ppm	ACGIH
--	--	------	---------	-------

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : butyl-rubber
Break through time : 240 min
Glove thickness : > 0.5 mm
Wearing time : 30 min

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
 Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
 Wear the following personal protective equipment:
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
 Skin contact must be avoided by using impervious protective

PLASTIC WELDER, Activator component, 59 mL

Version 4.0	Revision Date: 11/11/2022	SDS Number: 10786623-00007	Date of last issue: 06/07/2022 Date of first issue: 04/26/2017
----------------	------------------------------	-------------------------------	---

Hygiene measures		clothing (gloves, aprons, boots, etc).
	:	If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
		When using do not eat, drink or smoke.
		Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	colorless
Odor	:	acetone-like
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	56 °C Solvent
Flash point	:	-18 °C Solvent
Evaporation rate	:	> 1
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	12.8 %(V)
Lower explosion limit / Lower flammability limit	:	2.5 %(V)
Vapor pressure	:	240 hPa (20 °C) Solvent
Relative vapor density	:	> 1
Relative density	:	No data available
Density	:	0.79 - 0.83 g/cm ³ (20 °C)

PLASTIC WELDER, Activator component, 59 mL

Version 4.0	Revision Date: 11/11/2022	SDS Number: 10786623-00007	Date of last issue: 06/07/2022 Date of first issue: 04/26/2017
----------------	------------------------------	-------------------------------	---

Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: < 1 mPa.s (22 °C)
Viscosity, kinematic	: < 5 mm²/s (20 °C)
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle size	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed or in contact with skin.
Toxic if inhaled.

Product:

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

Acute oral toxicity	:	Acute toxicity estimate: 588.24 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 8.24 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: 1,765 mg/kg Method: Calculation method

Components:**Acetone:**

Acute oral toxicity	:	LD50 (Rat): 5,800 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Rabbit): 7,426 mg/kg

N,N-dimethyl-p-toluidine:

Acute oral toxicity	:	Acute toxicity estimate (Rat): 100 mg/kg Method: Expert judgment Remarks: Based on national or regional regulation.
Acute inhalation toxicity	:	LC50 (Rat): 1.40 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	Acute toxicity estimate: 300 mg/kg Method: Expert judgment Remarks: Based on national or regional regulation.

Skin corrosion/irritation

Not classified based on available information.

Components:**Acetone:**

Assessment	:	Repeated exposure may cause skin dryness or cracking.
------------	---	---

N,N-dimethyl-p-toluidine:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

Components:**Acetone:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

N,N-dimethyl-p-toluidine:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Acetone:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

N,N-dimethyl-p-toluidine:

Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Acetone:**

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
-----------------------	---	---

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion
----------------------	---	--

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

Result: negative

N,N-dimethyl-p-toluidine:Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negativeTest Type: Chromosome aberration test in vitro
Result: negative**Carcinogenicity**

May cause cancer.

Components:**Acetone:**

Species	: Mouse
Application Route	: Skin contact
Exposure time	: 424 days
Result	: negative

N,N-dimethyl-p-toluidine:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 104 -105 weeks
Result	: positive

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 104 -105 weeks
Result	: positive

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

Reproductive toxicity

Not classified based on available information.

Components:**Acetone:**Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negativeEffects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Acetone:**

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Reproductive organs) through prolonged or repeated exposure.

Components:**N,N-dimethyl-p-toluidine:**

Routes of exposure : Ingestion
Target Organs : Reproductive organs
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Repeated dose toxicity**Components:****Acetone:**

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 1,700 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 45 mg/l
Application Route : inhalation (vapor)
Exposure time : 8 Weeks

N,N-dimethyl-p-toluidine:

Species : Rat
LOAEL : 62.5 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

Components:**Acetone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Acetone:**

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (Daphnia magna (Water flea)): \geq 79 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211 |
| Toxicity to microorganisms | : | EC50: 61,150 mg/l
Exposure time: 30 min
Method: ISO 8192 |

N,N-dimethyl-p-toluidine:

- | | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 46 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 13.7 mg/l
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | ErC50 (Chlorella pyrenoidosa): 22 mg/l
Exposure time: 72 h |
| Toxicity to microorganisms | : | EC50 (Photobacterium phosphoreum): 13.6 mg/l
Exposure time: 30 min |

Persistence and degradability**Components:****Acetone:**

- | | | |
|------------------|---|---|
| Biodegradability | : | Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d |
|------------------|---|---|

N,N-dimethyl-p-toluidine:

- | | | |
|------------------|---|--|
| Biodegradability | : | Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d |
|------------------|---|--|

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

Bioaccumulative potential**Components:****Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

N,N-dimethyl-p-toluidine:

Partition coefficient: n-octanol/water : log Pow: 1.729

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- | | |
|------------------------|--|
| Waste from residues | : Dispose of in accordance with local regulations. |
| Contaminated packaging | : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product. |

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 1992
Proper shipping name	: FLAMMABLE LIQUID, TOXIC, N.O.S. (Acetone, N,N-dimethyl-p-toluidine)
Class	: 3
Subsidiary risk	: 6.1
Packing group	: II
Labels	: 3 (6.1)

IATA-DGR

UN/ID No.	: UN 1992
Proper shipping name	: Flammable liquid, toxic, n.o.s. (Acetone, N,N-dimethyl-p-toluidine)
Class	: 3
Subsidiary risk	: 6.1

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

Packing group : II
Labels : Flammable Liquids, Toxic
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 352

IMDG-Code

UN number : UN 1992
Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.
(Acetone, N,N-dimethyl-p-toluidine)
Class : 3
Subsidiary risk : 6.1
Packing group : II
Labels : 3 (6.1)
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number : UN 1992
Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.
(Acetone, N,N-dimethyl-p-toluidine)
Class : 3
Subsidiary risk : 6.1
Packing group : II
Labels : 3 (6.1)
ERG Code : 131
Marine pollutant : no
Remarks : Display "inhalation hazard" mark on package in accordance with TDG 4.23.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 15 % / 121 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD

PLASTIC WELDER, Activator component, 59 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/07/2022
4.0	11/11/2022	10786623-00007	Date of first issue: 04/26/2017

compile the Material Safety
Data SheeteChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date	:	11/11/2022
Date format	:	mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8