

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

SECTION 1. IDENTIFICATION

Product name : PLASTIC ADHESION PROMOTER, 307 g
Product code : 893.91013
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Primers

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Eye irritation : Category 2A
Specific target organ toxicity - single exposure : Category 3

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

Specific target organ toxicity - repeated exposure : Category 2 (Auditory system)

Simple Asphyxiant : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure.
May displace oxygen and cause rapid suffocation.

Precautionary Statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear eye protection and face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical attention if you feel unwell.
P337 + P313 If eye irritation persists: Get medical attention.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
 Date of first issue: 05/03/2017

Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Isobutyl acetate	Acetic acid, 2-methylpropyl ester	110-19-0	$\geq 60 - < 80$ *
Isobutane	Propane, 2-methyl-	75-28-5	$\geq 10 - < 30$ *
Acetone	2-Propanone	67-64-1	$\geq 5 - < 10$ *
Propane	Dimethylmethane	74-98-6	$\geq 5 - < 10$ *
Xylene	Benzene, dimethyl-	1330-20-7	$\geq 1 - < 5$ *
Propan-2-ol	Isopropyl alcohol	67-63-0	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 If not breathing, give artificial respiration.
 If breathing is difficult, give oxygen.
 Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
 Remove contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
 If easy to do, remove contact lens, if worn.
 Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention if symptoms occur.
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and : Causes serious eye irritation.
 May cause drowsiness or dizziness.

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

delayed : May cause damage to organs through prolonged or repeated exposure.
Gas reduces oxygen available for breathing.
Prolonged or repeated contact may dry skin and cause irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

oil barriers).
 Retain and dispose of contaminated wash water.
 Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
 Soak up with inert absorbent material.
 Suppress (knock down) gases/vapors/mists with a water spray jet.
 For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
 Clean up remaining materials from spill with suitable absorbent.
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
 Do not breathe spray.
 Do not swallow.
 Do not get in eyes.
 Wash skin thoroughly after handling.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.
 Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.
 Keep tightly closed.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Do not pierce or burn, even after use.
 Keep cool. Protect from sunlight.

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
 Date of first issue: 05/03/2017

Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable solids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which in contact with water emit flammable gases
 Explosives
 Gases

Recommended storage temperature : > 0 - 40 °C

Storage period : 18 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isobutyl acetate	110-19-0	TWA	150 ppm 713 mg/m ³	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
Isobutane	75-28-5	STEL	150 ppm	ACGIH
		TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
Acetone	67-64-1	STEL	1,000 ppm	ACGIH
		TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	500 ppm 1,190 mg/m ³	CA QC OEL
Propane	74-98-6	STEV	1,000 ppm 2,380 mg/m ³	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	1,000 ppm	CA AB OEL
Xylene	1330-20-7	TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
		TWA	100 ppm 434 mg/m ³	CA AB OEL

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
 Date of first issue: 05/03/2017

		STEL	150 ppm 651 mg/m ³	CA AB OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	150 ppm 651 mg/m ³	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
Propan-2-ol	67-63-0	STEL	400 ppm 984 mg/m ³	CA AB OEL
		TWA	200 ppm 492 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m ³	CA QC OEL
		STEV	500 ppm 1,230 mg/m ³	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Self-contained breathing apparatus
- Hand protection
- Material : Chemical-resistant gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : aerosol
- Propellant : Isobutane, Propane
- Color : Clear to slightly hazy, colorless
- Odor : fruity
- Odor Threshold : No data available

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : 56 °C

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 12.8 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Vapor pressure : 2,410 - 3,450 hPa (20 °C)

Relative vapor density : > 1

Relative density : No data available

Density : 0.85 - 0.87 g/cm³ (20 °C)

Solubility(ies)
Water solubility : partly soluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : < 10 mPa.s (20 °C)
Viscosity, kinematic : < 10 mm²/s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Metal corrosion rate : Not corrosive to metals.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapors may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Isobutyl acetate:**

Acute oral toxicity : LD50 (Rat): 13,413 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

LC50 (Rat): 21.2 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

Acute dermal toxicity : LD50 (Rabbit): > 17,400 mg/kg

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l
Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**Isobutyl acetate:**

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

Assessment : Repeated exposure may cause skin dryness or cracking.
Remarks : Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Xylene:

Species : Rabbit
Result : Skin irritation

Propan-2-ol:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Isobutyl acetate:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Acetone:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Propan-2-ol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

Components:**Isobutyl acetate:**

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Acetone:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Xylene:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Propan-2-ol:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Isobutyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

Remarks: Based on data from similar materials

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Acetone:**

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Propan-2-ol:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 104 weeks
Method : OECD Test Guideline 451
Result : negative

Reproductive toxicity

Not classified based on available information.

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

Components:**Isobutyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OPPTS 870.3800
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.
Remarks : Based on data from similar materials

Isobutane:

Assessment : May cause drowsiness or dizziness.

Acetone:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

PLASTIC ADHESION PROMOTER, 307 g

Version 3.3 Revision Date: 05/16/2022 SDS Number: 10693487-00006 Date of last issue: 10/26/2021
Date of first issue: 05/03/2017

STOT-repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:**Xylene:**

Routes of exposure : inhalation (vapor)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity**Components:****Isobutyl acetate:**

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 92 Days
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 2.4 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Acetone:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 1,700 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 45 mg/l
Application Route : inhalation (vapor)
Exposure time : 8 Weeks

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

Exposure time : 6 Weeks
 Method : OECD Test Guideline 422

Xylene:

Species : Rat
 LOAEL : > 0.2 - 1 mg/l
 Application Route : inhalation (vapor)
 Exposure time : 13 Weeks
 Remarks : Based on data from similar materials

Species : Rat
 LOAEL : 150 mg/kg
 Application Route : Ingestion
 Exposure time : 90 Days

Propan-2-ol:

Species : Rat
 NOAEL : 12.5 mg/l
 Application Route : inhalation (vapor)
 Exposure time : 104 Weeks

Aspiration toxicity

Not classified based on available information.

Components:
Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Components:
Isobutyl acetate:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 16.6 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 24.6 mg/l
 aquatic invertebrates : Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): 397
 plants : mg/l

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 196 mg/l

Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (Pseudomonas putida): 487 mg/l
 Exposure time: 6 h

Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
 Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 79 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l
 Exposure time: 30 min
 Method: ISO 8192

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
 Exposure time: 24 h
 Method: OECD Test Guideline 202
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
 Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l
 Exposure time: 35 d
 Method: OECD Test Guideline 210
 Remarks: Based on data from similar materials

Toxicity to daphnia and other : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

aquatic invertebrates (Chronic toxicity) : Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l
Exposure time: 16 h

Persistence and degradability**Components:****Isobutyl acetate:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 20 d

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Acetone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1.19 (BOD5)COD: 2.23BOD/COD: 53 %

Bioaccumulative potential**Components:****Isobutyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3

Isobutane:

Partition coefficient: n-octanol/water : log Pow: 2.8

Acetone:

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

Xylene:Partition coefficient: n-octanol/water : log Pow: 3.16
Remarks: Calculation**Propan-2-ol:**

Partition coefficient: n-octanol/water : log Pow: 0.05

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1

IATA-DGR

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
ERG Code	: 126
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 88 - 89 % / 748 - 756.5 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION
Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No

PLASTIC ADHESION PROMOTER, 307 g

Version	Revision Date:	SDS Number:	Date of last issue: 10/26/2021
3.3	05/16/2022	10693487-00006	Date of first issue: 05/03/2017

1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/16/2022
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8