

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

SECTION 1. IDENTIFICATION

Product name : AL 870, Aluminum anti-seize, 284 g

Product code : 893.921575

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : 1-800-263-5002

Telefax : 1-905-564-3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version 1.0 Revision Date: 01/24/2025 SDS Number: 11505544-00001 Date of last issue: -
Date of first issue: 01/24/2025

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), solvent refined heavy naphthenic	Mineral oil, petroleum distillates, solvent-refined heavy naphthenic	64741-96-4	$\geq 30 - < 60$ *
Limestone	Calcium carbonate	1317-65-3	$\geq 10 - < 30$ *
Talc	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	$\geq 10 - < 30$ *
Graphite	Graphitic carbon	7782-42-5	$\geq 1 - < 5$ *
Silicon, amorphous	Silicon dioxide	112945-52-5	$\geq 1 - < 5$ *
Aluminium	No data available	7429-90-5	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

Storage period : 36 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), solvent refined heavy naphthenic	64741-96-4	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Limestone	1317-65-3	TWA	10 mg/m ³	CA AB OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		STEL	20 mg/m ³	CA BC OEL
Talc	14807-96-6	TWAEV (respirable dust)	2 mg/m ³	CA QC OEL
		TWA (Respirable particulates)	2 mg/m ³	CA AB OEL
		TWA (Respirable)	2 mg/m ³	CA BC OEL
		TWA	2 fibres per cubic	CA ON OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version 1.0 Revision Date: 01/24/2025 SDS Number: 11505544-00001 Date of last issue: -
Date of first issue: 01/24/2025

			centimeter	
		TWA (Respirable fraction)	2 mg/m ³	CA ON OEL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Graphite	7782-42-5	TWA (Respirable)	2 mg/m ³	CA BC OEL
		TWAEV (respirable dust)	2 mg/m ³	CA QC OEL
		TWA (Respirable)	2 mg/m ³	CA AB OEL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Silicon, amorphous	112945-52-5	TWAEV (respirable dust)	6 mg/m ³	CA QC OEL
Aluminium	7429-90-5	TWA (Dust)	10 mg/m ³	CA AB OEL
		TWA (Respirable)	1 mg/m ³ (Aluminum)	CA BC OEL
		TWAEV (respirable dust)	5 mg/m ³	CA QC OEL
		TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection
Material : Chemical-resistant gloves

Remarks : Wash hands before breaks and at the end of workday.
Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Eye protection	: Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Wear the following personal protective equipment: Safety glasses Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Skin and body protection	: Skin should be washed after contact.
Hygiene measures	: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Grease, Pasty solid
Color	: silver
Odor	: slight
Odor Threshold	: No data available
pH	: substance/mixture is non-soluble (in water)
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: 221 °C Method: Cleveland open cup Solvent
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Flammability (liquids)	: Not applicable
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower	: No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

flammability limit

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : 1.1 g/cm³

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact

Ingestion

Eye contact

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

Limestone:

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

Talc:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
---------------------	------------------------------------------------------------------------------

Graphite:

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 423 Assessment: The substance or mixture has no acute oral toxicity
---------------------	-----------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Silicon, amorphous:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Aluminium:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 0.888 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Limestone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Talc:

Species : Rabbit

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Result : No skin irritation

Graphite:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Silicon, amorphous:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Aluminium:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Limestone:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Talc:

Species : Rabbit
Result : No eye irritation

Graphite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Silicon, amorphous:

Species : Rabbit
Result : No eye irritation

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Aluminium:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative
Remarks	:	Based on data from similar materials

Limestone:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative
Remarks	:	Based on data from similar materials

Talc:

Routes of exposure	:	Skin contact
Species	:	Humans
Result	:	negative

Graphite:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Result	:	negative

Aluminium:

Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

Limestone:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials
	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative Remarks: Based on data from similar materials
	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Remarks: Based on data from similar materials

Talc:

Genotoxicity in vitro	: Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro) Result: negative
Genotoxicity in vivo	: Test Type: Chromosome aberration test in vitro Species: Rat Application Route: Ingestion Result: negative

Graphite:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	-------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Silicon, amorphous:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Aluminium:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative
Remarks : Based on data from similar materials

Talc:

Species : Mouse
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Silicon, amorphous:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	103 weeks
Result	:	negative
Remarks	:	Based on data from similar materials

Aluminium:

Species	:	Rat
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	86 weeks
Result	:	negative

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Effects on fertility	:	Test Type: Reproduction/Developmental toxicity screening test
		Species: Rat
		Application Route: Ingestion
		Result: negative
		Remarks: Based on data from similar materials

Effects on fetal development	:	Test Type: Embryo-fetal development
		Species: Rat
		Application Route: Skin contact
		Method: OECD Test Guideline 414
		Result: negative
		Remarks: Based on data from similar materials

Limestone:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
		Species: Rat
		Application Route: Ingestion
		Method: OECD Test Guideline 422
		Result: negative
		Remarks: Based on data from similar materials

Effects on fetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
		Species: Rat
		Application Route: Ingestion
		Method: OECD Test Guideline 422
		Result: negative
		Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Talc:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Silicon, amorphous:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Aluminium:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Repeated dose toxicity

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Species	:	Rabbit
NOAEL	:	1,000 mg/kg
Application Route	:	Skin contact
Exposure time	:	4 Weeks
Method	:	OECD Test Guideline 410
Remarks	:	Based on data from similar materials

Species	:	Rat
NOAEL	:	> 980 mg/m ³
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	4 Weeks
Remarks	:	Based on data from similar materials

Limestone:

Species	:	Rat
NOAEL	:	> 300 mg/kg
Application Route	:	Ingestion
Exposure time	:	28 Days
Method	:	OECD Test Guideline 422
Remarks	:	Based on data from similar materials

Silicon, amorphous:

Species	:	Rat
NOAEL	:	1.3 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
		Exposure time: 96 h
		Method: OECD Test Guideline 203
		Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
		Exposure time: 48 h
		Method: OECD Test Guideline 202
		Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Limestone:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
Exposure time: 24 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Graphite:

- Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Silicon, amorphous:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Aluminium:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Toxicity to fish : NOEC (Salmo trutta (brown trout)): > 80 µg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): > 0.135 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability

Components:

Distillates (petroleum), solvent refined heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content

Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations
VOC content: 1.54 % / 15.39 g/l
Remarks: VOC content excluding water and exempt compounds

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with

SAFETY DATA SHEET

according to the Hazardous Products Regulations



AL 870, Aluminum anti-seize, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	01/24/2025	11505544-00001	Date of first issue: 01/24/2025

x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 01/24/2025
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8