

# Sealant Selection Guide



Name:	EASYSIL	MULTIPURPOSE SILICONE	FLEXIFILL	INDOOR SEALANT
	Acetic silicone	Neutral	Siliconized acrylic	Acrylic
Colours:	<input type="radio"/> Transparent (892.560304) <input type="radio"/> White (892.560303) <input checked="" type="radio"/> Aluminum (892.560307)	<input type="radio"/> Translucent (892.560004) <input type="radio"/> White (892.560003) <input checked="" type="radio"/> Grey (892.560002)	<input type="radio"/> White (892.165020)	<input type="radio"/> White (892.165021)
Size:	300 mL Cartridge			
Features:	<ul style="list-style-type: none"> <li>• 100% Silicone</li> <li>• Waterproof</li> <li>• UV &amp; Weather Resistant</li> <li>• Excellent temperature resistance</li> </ul>		<ul style="list-style-type: none"> <li>• Great for filling &amp; sealing gaps</li> <li>• Water resistant</li> <li>• Flexible &amp; crack resistant</li> <li>• Paintable</li> <li>• Easy cleanup with water</li> </ul>	
	<ul style="list-style-type: none"> <li>• Extra protection from mold &amp; mildew</li> </ul>	<ul style="list-style-type: none"> <li>• Non-corrosive, safe on sensitive surfaces</li> <li>• Low odour</li> </ul>	<ul style="list-style-type: none"> <li>• Enhanced flexibility &amp; water resistance</li> <li>• Glossy finish</li> </ul>	<ul style="list-style-type: none"> <li>• Low cost</li> </ul>
Use case:	Indoor & Outdoor		Indoor & Outdoor	Indoor
Applications:	<ul style="list-style-type: none"> <li>• Best for non-porous materials</li> <li>• Kitchen &amp; Bath</li> <li>• Window &amp; Door</li> <li>• Aluminum</li> <li><i>*Not to be used on sensitive metals, stone, electronics, mirrors</i></li> </ul>	<ul style="list-style-type: none"> <li>• Best for porous materials</li> <li>• Window &amp; Door</li> <li>• Kitchen &amp; Bath</li> <li>• Sealing around natural stone</li> <li>• Exterior sealing on wood, brick or concrete</li> </ul>	<ul style="list-style-type: none"> <li>• Filling gaps in trim, baseboard and crown molding</li> <li>• Sealing drywall joints or cracks before painting</li> <li>• Filling gaps around window and door casing</li> <li>• Cosmetic repair</li> </ul>	
Paintable:	No		Yes	
Application Temp:	5°C to 40°C (41°F to 104°F)		5°C to 35°C (41°F to 95°F)	
Min Temp Resistance:	-40°C (-40°F)	-50°C (-58°F)	-10°C (-14°F)	
Max Temp Resistance:	150°C (302°F)		80°C (176°F)	
Tack Free Time: (23°C and 50% RH)	12 min	4 - 10 min	15 - 45 min	15 - 60 min
Joint Movement:	+/- 25%	+/- 25% (Colours) +/- 12.5% (Translucent)	+/- 12.5%	-
Standards Met:	EN-15651-1: Facade EN-15651-2: Glazing EN-15651-3: Sanitary Joints	EN-15651-1: Facade EN-15651-3: Sanitary Joints	EN-15651-1: Facade	