



SAFETY DATA SHEET

1. Identification

Product identifier: SILICONE SPRAY

Other means of identification

SDS number: RE1000007592

Recommended restrictions

Recommended use: Coating.

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: SPRAYWAY, INC.
Address: 8001 KEELE ST
CONCORD, ONTARIO L4K 1Y8
Telephone: 800-332-9000

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2

Aspiration Hazard Category 1

Environmental Hazards

Acute hazards to the aquatic environment Category 2

Chronic hazards to the aquatic environment Category 2

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
Causes skin irritation.
May be fatal if swallowed and enters airways.
Toxic to aquatic life with long lasting effects.



Precautionary Statements

- Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves.
- Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. Collect spillage.
- Storage:** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Propane		74-98-6	15 - 40%
Naphtha (petroleum), hydrotreated light		64742-49-0	15 - 40%
Heptane		142-82-5	10 - 30%
Naphtha (petroleum), hydrotreated heavy		64742-48-9	1 - 5%
Cyclohexane, methyl-		108-87-2	1 - 5%
Siloxanes and Silicones, di-Me		63148-62-9	1 - 5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
- Inhalation:** Move to fresh air.
- Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

- Symptoms:** No data available.
- Hazards:** No data available.



Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 3



8. Exposure controls/personal protection

**Control Parameters
Occupational Exposure Limits**

Chemical Identity	Type	Exposure Limit Values	Source
Propane	TWA	1,000 ppm	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Propane	8 HR ACL	1,000 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Propane	TWA	1,000 ppm 1,800 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Propane	TWA	1,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	15 MIN ACL	1,250 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Naphtha (petroleum), hydrotreated light	TWA	400 ppm 1,590 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Naphtha (petroleum), hydrotreated light	15 MIN ACL	500 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	8 HR ACL	400 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Naphtha (petroleum), hydrotreated light	TWA	400 ppm 1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Heptane	TWA	400 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	500 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Heptane	STEL	500 ppm 2,050 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Heptane	8 HR ACL	400 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Heptane	TWA	400 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2012)
	STEL	500 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2012)
Heptane	STEL	500 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Heptane	STEL	500 ppm 2,050 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	400 ppm 1,640 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	15 MIN ACL	500 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	TWA	400 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	TWA	400 ppm 1,640 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Heptane	TWA	400 ppm	US. ACGIH Threshold Limit Values, as amended (02 2012)
	STEL	500 ppm	US. ACGIH Threshold Limit Values, as amended (02 2012)
Naphtha (petroleum), hydrotreated heavy	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cyclohexane, methyl-	TWA	400 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cyclohexane, methyl-	TWA	400 ppm 1,610 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Cyclohexane, methyl-	TWA	400 ppm 1,610 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Cyclohexane, methyl-	TWA	400 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)



Cyclohexane, methyl-	8 HR ACL	400 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	500 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Cyclohexane, methyl-	TWA	400 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Cyclohexane, methyl-	TWA	400 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Benzene, ethyl-	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Benzene, ethyl-	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Benzene, ethyl-	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Benzene, ethyl-	8 HR ACL	100 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Benzene, ethyl-	TWA	20 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	STEL	125 ppm	543 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Benzene, ethyl-	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	15 MIN ACL	125 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Benzene, ethyl-	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (12 2010)
Cyclohexane	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cyclohexane	TWA	300 ppm	1,030 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Cyclohexane	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
Cyclohexane	8 HR ACL	100 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Cyclohexane	TWA	100 ppm	344 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Cyclohexane	TWA	100 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	15 MIN ACL	150 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Cyclohexane	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Hexane	TWA	50 ppm	176 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Hexane	TWA	50 ppm	176 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Hexane	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Hexane	15 MIN ACL	62.5 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Hexane	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	50 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Hexane	TWA	50 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Hexane	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Benzene, methyl-	TWA	50 ppm	188 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Benzene, methyl-	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene, methyl-	8 HR ACL	50 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)



	15 MIN ACL	60 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Benzene, methyl-	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Benzene, methyl-	TWA	50 ppm	188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Benzene, methyl-	TWA	20 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Benzene, methyl-	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Benzene	STEL	2.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	STEL	2.5 ppm	8 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	TWA	0.5 ppm	1.6 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Benzene	TWA	0.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	STEL	2.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Benzene	STEL	2.5 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
	TWA	0.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	1 ppm	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	STEL	5 ppm	15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	0.5 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Benzene	TWA	0.5 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	STEL	2.5 ppm		US. ACGIH Threshold Limit Values, as amended (2008)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

- General information:** Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
- Eye/face protection:** Wear safety glasses with side shields (or goggles).
- Skin Protection**
- Hand Protection:** No data available.
- Other:** Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
- Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:** Observe good industrial hygiene practices. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.



9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.

Odor: No data available.

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: -104.44 °C

Evaporation rate: No data available.

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: 4,481 - 5,862 hPa (20 °C)

Vapor density: No data available.

Density: No data available.

Relative density: No data available.

Solubility(ies)

Solubility in water: No data available.

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.

Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous reactions: No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition Products: No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.



Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

- Propane LD 50: > 5,000 mg/kg
- Naphtha (petroleum), hydrotreated light LD 50 (Rat): > 5,000 mg/kg
- Heptane LD 50 (Rat): > 5,000 mg/kg
- Naphtha (petroleum), hydrotreated heavy LD 50 (Rat): > 5,000 mg/kg
- Cyclohexane, methyl- LD Lo (Rabbit): 4,000 - 4,500 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

- Propane LD 50: > 5,000 mg/kg
- Naphtha (petroleum), hydrotreated light LD 50 (Rabbit): > 3,750 mg/kg
- Heptane LD 50 (Rabbit): > 2,000 mg/kg
- Naphtha (petroleum), hydrotreated heavy LD 50 (Rabbit): > 6,000 mg/kg
- Cyclohexane, methyl- LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product: ATEmix: 96.41 mg/l

Repeated dose toxicity

Product: No data available.



Specified substance(s):

Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Naphtha (petroleum), hydrotreated light	NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Read- across based on grouping of substances (category approach), Key study NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study
Heptane	NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental result, Key study
Naphtha (petroleum), hydrotreated heavy	NOAEL (Rat(Female, Male), Inhalation): 9,840 mg/m3 Inhalation Experimental result, Key study NOAEL (Rat(Male), Oral, 28 d): < 500 mg/kg Oral Experimental result, Supporting study NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal Experimental result, Key study
Cyclohexane, methyl-	NOAEL (Rat(Female, Male), Inhalation): 1,600 mg/m3 Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Oral, 28 d): 1,000 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female, Male), Oral, 28 d): 250 mg/kg Oral Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light	In vitro (Human): not corrosive Experimental result, Supporting study
Heptane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light	Rabbit, 24 - 72 hrs: Not irritating
Heptane	Rabbit, 24 - 72 hrs: Not irritating
Naphtha (petroleum), hydrotreated heavy	Rabbit, 24 - 72 hrs: Not irritating
Cyclohexane, methyl-	Rabbit, 0.5 - 168 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Heptane	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Naphtha (petroleum), hydrotreated heavy	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Cyclohexane, methyl-	Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.



Specified substance(s):
Cyclohexane, methyl- May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

ACGIH Carcinogen List:
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specified substance(s):
Heptane Narcotic effect. - Category 3 with narcotic effects.
Cyclohexane, methyl- Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Specified substance(s):
Cyclohexane, methyl- Category 1

Aspiration Hazard
Product: No data available.

Specified substance(s):
Naphtha (petroleum),
hydrotreated light May be fatal if swallowed and enters airways.

Heptane May be fatal if swallowed and enters airways.

Naphtha (petroleum),
hydrotreated heavy May be fatal if swallowed and enters airways.

Cyclohexane, methyl- May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.



Specified substance(s):

Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Naphtha (petroleum), hydrotreated light	LC 50 (96 h): 8.41 mg/l Experimental result, Key study
Naphtha (petroleum), hydrotreated heavy	LL 50 (Oncorhynchus mykiss, 96 h): 10 mg/l Experimental result, Key study
Cyclohexane, methyl-	LC 50 (Oryzias latipes, 96 h): 2.07 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study
---	--

Chronic hazards to the aquatic environment:

Fish

Product: NOEC : < 1 mg/l

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study
---	---

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Naphtha (petroleum), hydrotreated light	95 % (10 d) The 10-day window requirement is fulfilled. 90.35 % (28 d) Detected in water. Experimental result, Supporting study
Naphtha (petroleum), hydrotreated heavy	90.35 % (28 d) Detected in water. Experimental result, Supporting study
Cyclohexane, methyl-	> 0 % (28 d) Detected in water. Experimental result, Weight of Evidence study > 0 % (28 d) Detected in water. Experimental result, Weight of Evidence study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.



Specified substance(s):

Naphtha (petroleum), hydrotreated light	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study
Naphtha (petroleum), hydrotreated heavy	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study
Cyclohexane, methyl-	Cyprinus carpio, Bioconcentration Factor (BCF): > 95 - < 321 Aquatic sediment Experimental result, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light	Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study
---	---

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Propane	No data available.
Naphtha (petroleum), hydrotreated light	No data available.
Heptane	No data available.
Naphtha (petroleum), hydrotreated heavy	No data available.
Cyclohexane, methyl-	No data available.
Siloxanes and Silicones, di-Me	No data available.

Other adverse effects: Toxic to aquatic life with long lasting effects.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

TDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	–
EmS No.:	–
Packing Group:	–
Environmental Hazards:	Yes
Special precautions for user:	Not regulated.

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	–
EmS No.:	F-D, S-U
Packing Group:	–
Environmental Hazards:	Yes
Special precautions for user:	Not regulated.



IATA

UN Number:	UN 1950
Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	–
Packing Group:	–
Environmental Hazards:	Yes
Special precautions for user:	Not regulated.
Cargo aircraft only:	Allowed.

15. Regulatory information

Canada Federal Regulations

List of Toxic Substances (CEPA, Schedule 1)

Chemical Identity

Benzene

Export Control List (CEPA 1999, Schedule 3)

Not Regulated

National Pollutant Release Inventory (NPRI)

Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional Reporting Requirements

NPRI PT5	Propane
	Naphtha (petroleum), hydrotreated light
	Heptane
	Naphtha (petroleum), hydrotreated heavy
	Hexane
	Benzene, methyl-
	Benzene

Canada. National Pollutant Release Inventory (NPRI) (Schedule 1, Parts 1-4)

NPRI	Not Regulated
------	---------------

Greenhouse Gases

Not Regulated

Controlled Drugs and Substances Act

CA CDSI	Not Regulated
CA CDSII	Not Regulated
CA CDSIII	Not Regulated
CA CDSIV	Not Regulated
CA CDSV	Not Regulated
CA CDSVII	Not Regulated
CA CDSVIII	Not Regulated

Precursor Control Regulations

Chemical Identity

Benzene, methyl-

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable



Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	On or in compliance with the inventory
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	On or in compliance with the inventory
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	On or in compliance with the inventory
Ontario Inventory:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date: 07/06/2021

Revision Date: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.