

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

SECTION 1. IDENTIFICATION

Product name : 2K RAPID PRIMER FILLER, 238 g
Product code : 5867.000122
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : 1-800-263-5002
Telefax : 1-905-564-3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Urgences impliquant un déversement, incendie, explosion ou
exposition: CHEMTREC (24/7): 1-800-424-9300
E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Coatings
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1
Eye irritation : Category 2A
Carcinogenicity : Category 2
Specific target organ toxicity : Category 3
- single exposure
Specific target organ toxicity : Category 2 (Auditory system)
- repeated exposure

GHS label elements

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.

Storage:
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Dimethyl ether	Methane, 1,1'-oxybis-	115-10-6	$\geq 30 - < 60$ *
Acetone	2-Propanone	67-64-1	$\geq 10 - < 30$ *
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	$\geq 10 - < 30$ *
Xylene	Benzene, dimethyl-	1330-20-7	$\geq 1 - < 5$ *
Isobutyl methyl ketone	4-Methylpentan-2-one	108-10-1	$\geq 1 - < 5$ *
Butan-1-ol	n-Butyl alcohol	71-36-3	$\geq 1 - < 5$ *
Heptan-2-one	Methyl amyl ketone	110-43-0	$\geq 1 - < 5$ *
1-Methoxy-2-propanol	METHOXYISOPROPANOL	107-98-2	$\geq 1 - < 5$ *
Zinc oxide	Zinc monoxide	1314-13-2	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Prolonged or repeated contact may dry skin and cause irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/08/2024
9.2	12/03/2024	10658337-00013	Date of first issue: 05/02/2018

May cause damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/08/2024
9.2	12/03/2024	10658337-00013	Date of first issue: 05/02/2018

oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dimethyl ether	115-10-6	TWA	1,000 ppm	CA BC OEL
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	250 ppm	CA QC OEL
		STEV	500 ppm	CA QC OEL
		TWA	250 ppm	ACGIH
n-Butyl acetate	123-86-4	STEL	200 ppm 950 mg/m ³	CA AB OEL
		TWA	150 ppm 713 mg/m ³	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
Xylene	1330-20-7	TWA	100 ppm 434 mg/m ³	CA AB OEL
		STEL	150 ppm 651 mg/m ³	CA AB OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	150 ppm 651 mg/m ³	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version
9.2

Revision Date:
12/03/2024

SDS Number:
10658337-00013

Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

		TWA	20 ppm	ACGIH
Isobutyl methyl ketone	108-10-1	TWA	50 ppm 205 mg/m ³	CA AB OEL
		STEL	75 ppm 307 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		STEV	75 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
Butan-1-ol	71-36-3	TWA	20 ppm 60 mg/m ³	CA AB OEL
		TWA	15 ppm	CA BC OEL
		C	30 ppm	CA BC OEL
		C	50 ppm 152 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
Heptan-2-one	110-43-0	TWA	50 ppm 233 mg/m ³	CA AB OEL
		TWA	50 ppm	CA BC OEL
		TWA	25 ppm 115 mg/m ³	CA ON OEL
		TWAEV	50 ppm 233 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH
1-Methoxy-2-propanol	107-98-2	TWA	100 ppm 369 mg/m ³	CA AB OEL
		STEL	150 ppm 553 mg/m ³	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	100 ppm 369 mg/m ³	CA QC OEL
		STEV	150 ppm 553 mg/m ³	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
Zinc oxide	1314-13-2	TWA (Respirable)	2 mg/m ³	CA AB OEL
		STEL (Respirable)	10 mg/m ³	CA AB OEL
		TWA (Respirable)	2 mg/m ³	CA BC OEL
		STEL (Respirable)	10 mg/m ³	CA BC OEL
		TWAEV (respirable dust)	2 mg/m ³	CA QC OEL
		STEV (respirable dust)	10 mg/m ³	CA QC OEL
		TWA (Respi-	2 mg/m ³	ACGIH

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

		able particulate matter)		
		STEL (Respirable particulate matter)	10 mg/m ³	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Isobutyl methyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : butyl-rubber
Break through time : 15 min
Glove thickness : 0.7 mm

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : aerosol
- Propellant : Dimethyl ether
- Color : colored
- Odor : characteristic
- Odor Threshold : No data available
- pH : Solvent mixture; pH value determination not possible, no aqueous solution
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : Not applicable

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/08/2024
9.2	12/03/2024	10658337-00013	Date of first issue: 05/02/2018

Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	18.6 %(V)
Lower explosion limit / Lower flammability limit	:	2.6 %(V)
Vapor pressure	:	3,400 hPa (20 °C)
Relative vapor density	:	Not applicable
Relative density	:	No data available
Solubility(ies)	:	
Water solubility	:	partly miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	235 °C
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/08/2024
9.2	12/03/2024	10658337-00013	Date of first issue: 05/02/2018

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm
Exposure time: 4 h
Test atmosphere: gas

Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Isobutyl methyl ketone:

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Butan-1-ol:

Acute oral toxicity : LD50 (Rat, female): 790 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 17.76 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit, male): 3,430 mg/kg

Heptan-2-one:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 16.7 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

1-Methoxy-2-propanol:

Acute oral toxicity : LD50 (Rat): 4,016 mg/kg

Acute inhalation toxicity : LC50 (Mouse): < 22.2 mg/l

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Xylene:

Species : Rabbit
Result : Skin irritation

Isobutyl methyl ketone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Butan-1-ol:

Species : Rabbit
Result : Skin irritation

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Heptan-2-one:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Mild skin irritation

1-Methoxy-2-propanol:

Species : Rabbit
Result : No skin irritation

Zinc oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Acetone:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

n-Butyl acetate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Isobutyl methyl ketone:

Species : Human
Result : Irritation to eyes, reversing within 21 days

Butan-1-ol:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Heptan-2-one:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

1-Methoxy-2-propanol:

Species : Rabbit
Result : No eye irritation

Zinc oxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Acetone:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

n-Butyl acetate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Xylene:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Isobutyl methyl ketone:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Butan-1-ol:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Heptan-2-one:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

1-Methoxy-2-propanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Zinc oxide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Application Route: inhalation (gas)
Result: negative

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Genotoxicity in vivo : Result: negative
: Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Isobutyl methyl ketone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: equivocal

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Butan-1-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Heptan-2-one:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: DNA Repair
Species: Rat
Application Route: inhalation (vapor)
Result: negative

1-Methoxy-2-propanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: equivocal

Test Type: DNA damage and repair, unscheduled DNA syn-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

thesis in mammalian cells (in vitro)
Method: OECD Test Guideline 482
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: equivocal

Test Type: Chromosome aberration test in vitro
Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Suspected of causing cancer.

Components:

Dimethyl ether:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Result : negative

Acetone:

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Isobutyl methyl ketone:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Method : OECD Test Guideline 451
Result : positive

Species : Mouse
Application Route : inhalation (vapor)
Exposure time : 2 Years
Method : OECD Test Guideline 451
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

1-Methoxy-2-propanol:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : negative

Zinc oxide:

Species : Mouse
Application Route : Ingestion
Exposure time : 1 Years
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Dimethyl ether:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Isobutyl methyl ketone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Butan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Heptan-2-one:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 421
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 414
Result: negative

1-Methoxy-2-propanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

Acetone:

Assessment : May cause drowsiness or dizziness.

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

Isobutyl methyl ketone:

Assessment : May cause drowsiness or dizziness.

Butan-1-ol:

Assessment : May cause respiratory irritation.

Assessment : May cause drowsiness or dizziness.

1-Methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:

Xylene:

Routes of exposure : inhalation (vapor)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Heptan-2-one:

Assessment : No significant health effects observed in animals at concentra-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

tions of 100 mg/kg bw or less.

Zinc oxide:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Dimethyl ether:

Species : Rat
NOAEL : 47.11 mg/l
Application Route : inhalation (vapor)
Exposure time : 2 y

Acetone:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 1,700 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 45 mg/l
Application Route : inhalation (vapor)
Exposure time : 8 Weeks

n-Butyl acetate:

Species : Rat
NOAEL : 2.4 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days

Xylene:

Species : Rat
LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Isobutyl methyl ketone:

Species : Rat
NOAEL : 250 mg/kg
LOAEL : 1,000 mg/kg

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Application Route : Ingestion
Exposure time : 13 Weeks

Species : Rat
NOAEL : 4.106 mg/l
Application Route : inhalation (vapor)
Exposure time : 14 Weeks

Butan-1-ol:

Species : Rat
NOAEL : 125 mg/kg
LOAEL : 500 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Species : Rat
NOAEL : > 1 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Heptan-2-one:

Species : Rat
NOAEL : > 20 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Species : Rat
NOAEL : \geq 4.779 mg/l
Application Route : inhalation (vapor)
Exposure time : 10 Months

1-Methoxy-2-propanol:

Species : Rat
NOAEL : 919 mg/kg
Application Route : Ingestion
Exposure time : 35 Days

Species : Rat
NOAEL : 1.1 mg/l
Application Route : inhalation (vapor)
Exposure time : 2 y
Method : OECD Test Guideline 453

Species : Rabbit
NOAEL : 1,838 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/08/2024
9.2	12/03/2024	10658337-00013	Date of first issue: 05/02/2018

Zinc oxide:

Species	:	Rat, male
NOAEL	:	0.0015 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	3 Months
Method	:	OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Isobutyl methyl ketone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Butan-1-ol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Heptan-2-one:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Dimethyl ether:

Toxicity to fish	:	LC50 (Poecilia reticulata (guppy)): > 4,100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 4,400 mg/l Exposure time: 48 h
Toxicity to microorganisms	:	EC10 (Pseudomonas putida): > 1,600 mg/l

Acetone:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): \geq 79 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC50: 61,150 mg/l
Exposure time: 30 min
Method: ISO 8192

n-Butyl acetate:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (Water flea)): 44 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials
- Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

Xylene:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Isobutyl methyl ketone:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 179 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 200 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 30 mg/l
Exposure time: 21 d

Butan-1-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,376 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,328 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 225 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

EC10 (Raphidocelis subcapitata (freshwater green alga)): 134 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 4.1 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (Pseudomonas putida): 2,476 mg/l
Exposure time: 17 h
Method: DIN 38 412 Part 8

Heptan-2-one:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 131 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 90.1 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 98.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 42.68 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 52 mg/l
Exposure time: 16 h

1-Methoxy-2-propanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 6,812 mg/l
Exposure time: 96 h
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 23,300 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Skeletonema costatum (marine diatom)): 6,745 mg/l
Exposure time: 72 h
Method: ISO 10253

Toxicity to microorganisms : IC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Zinc oxide:

Toxicity to fish : LC50 : > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136 mg/l

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Jordanella floridae (flagfish)): > 0.01 - 0.1 mg/l
Exposure time: 14 Weeks
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l
Exposure time: 7 d
Remarks: Based on data from similar materials

Persistence and degradability

Components:

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Acetone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Isobutyl methyl ketone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Butan-1-ol:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version 9.2 Revision Date: 12/03/2024 SDS Number: 10658337-00013 Date of last issue: 08/08/2024
Date of first issue: 05/02/2018

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 %
Exposure time: 20 d

Heptan-2-one:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 69 %
Exposure time: 28 d
Method: OECD Test Guideline 310

1-Methoxy-2-propanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 96 %
Exposure time: 28 d
Method: OECD Test Guideline 301E

Bioaccumulative potential

Components:

Dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0.2

Acetone:

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16
Remarks: Calculation

Isobutyl methyl ketone:

Partition coefficient: n-octanol/water : log Pow: 1.9

Butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 1
Method: OECD Test Guideline 117

Heptan-2-one:

Partition coefficient: n-octanol/water : log Pow: 2.26

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/08/2024
9.2	12/03/2024	10658337-00013	Date of first issue: 05/02/2018

1-Methoxy-2-propanol:

Partition coefficient: n-octanol/water : log Pow: < 1

Zinc oxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 78 - 2,060

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo) : 203

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/08/2024
9.2	12/03/2024	10658337-00013	Date of first issue: 05/02/2018

aircraft)

Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
ERG Code : 126
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/08/2024
9.2	12/03/2024	10658337-00013	Date of first issue: 05/02/2018

CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit

CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA BC OEL / STEL : short-term exposure limit

CA BC OEL / C : ceiling limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)

CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

CA QC OEL / C : Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/03/2024
Date format : mm/dd/yyyy

SAFETY DATA SHEET

according to the Hazardous Products Regulations



2K RAPID PRIMER FILLER, 238 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/08/2024
9.2	12/03/2024	10658337-00013	Date of first issue: 05/02/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8