

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

**SECTION 1. IDENTIFICATION**

Product name : 2K RAPID PRIMER FILLER, 366 g

Product code : 5867.000122

Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Coatings

Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Eye irritation : Category 2A

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
 Date of first issue: 05/02/2018

- single exposure

Specific target organ toxicity : Category 2 (Auditory system)  
 - repeated exposure

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements :

**Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves, protective clothing, eye protection and face protection.

**Response:**

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical attention.  
 P337 + P313 If eye irritation persists: Get medical attention.

**Storage:**

P405 Store locked up.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
 Date of first issue: 05/02/2018

**Other hazards**

Repeated exposure may cause skin dryness or cracking.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Dimethyl ether	Methane, 1,1'-oxybis-	115-10-6	$\geq 30 - < 60$ *
Acetone	2-Propanone	67-64-1	$\geq 10 - < 30$ *
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	$\geq 10 - < 30$ *
Xylene	Benzene, dimethyl-	1330-20-7	$\geq 1 - < 5$ *
Isobutyl methyl ketone	4-Methylpentan-2-one	108-10-1	$\geq 1 - < 5$ *
Butan-1-ol	n-Butyl alcohol	71-36-3	$\geq 1 - < 5$ *
Heptan-2-one	Methyl amyl ketone	110-43-0	$\geq 1 - < 5$ *
1-Methoxy-2-propanol	METHOXYISOPROPANOL	107-98-2	$\geq 1 - < 5$ *
Zinc oxide	Zinc monoxide	1314-13-2	$\geq 1 - < 5$ *

|| \* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
 Remove contaminated clothing and shoes.  
 Get medical attention.  
 Wash clothing before reuse.  
 Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
 If easy to do, remove contact lens, if worn.  
 Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
 Get medical attention.  
 Rinse mouth thoroughly with water.

**2K RAPID PRIMER FILLER, 366 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

---

- Most important symptoms and effects, both acute and delayed : Prolonged or repeated contact may dry skin and cause irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or

**2K RAPID PRIMER FILLER, 366 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

---

oil barriers).  
 Retain and dispose of contaminated wash water.  
 Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
 Soak up with inert absorbent material.  
 Suppress (knock down) gases/vapors/mists with a water spray jet.  
 For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
 Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
 Do not breathe spray.  
 Do not swallow.  
 Do not get in eyes.  
 Wash skin thoroughly after handling.  
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Take precautionary measures against static discharges.  
 Take care to prevent spills, waste and minimize release to the environment.  
 Do not spray on an open flame or other ignition source.  
  
 Do not breathe decomposition products.

Conditions for safe storage : Store locked up.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Do not pierce or burn, even after use.  
 Keep cool. Protect from sunlight.

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
 Date of first issue: 05/02/2018

Materials to avoid : Do not store with the following product types:  
 Self-reactive substances and mixtures  
 Organic peroxides  
 Oxidizing agents  
 Flammable solids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Substances and mixtures which in contact with water emit flammable gases  
 Explosives  
 Gases

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dimethyl ether	115-10-6	TWA	1,000 ppm	CA BC OEL
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm 1,800 mg/m <sup>3</sup>	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	500 ppm 1,190 mg/m <sup>3</sup>	CA QC OEL
		STEV	1,000 ppm 2,380 mg/m <sup>3</sup>	CA QC OEL
n-Butyl acetate	123-86-4	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		STEL	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL
		TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
Xylene	1330-20-7	TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm 434 mg/m <sup>3</sup>	CA AB OEL
		STEL	150 ppm 651 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	100 ppm 434 mg/m <sup>3</sup>	CA QC OEL
		STEV	150 ppm 651 mg/m <sup>3</sup>	CA QC OEL
		TWA	100 ppm	CA BC OEL

**2K RAPID PRIMER FILLER, 366 g**
Version  
8.0Revision Date:  
10/11/2022SDS Number:  
10658337-00009Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

		STEL	150 ppm	CA BC OEL
		TWA	20 ppm	ACGIH
Isobutyl methyl ketone	108-10-1	TWA	50 ppm 205 mg/m <sup>3</sup>	CA AB OEL
		STEL	75 ppm 307 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		STEV	75 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
Butan-1-ol	71-36-3	TWA	20 ppm 60 mg/m <sup>3</sup>	CA AB OEL
		TWA	15 ppm	CA BC OEL
		C	30 ppm	CA BC OEL
		C	50 ppm 152 mg/m <sup>3</sup>	CA QC OEL
		TWA	20 ppm	ACGIH
Heptan-2-one	110-43-0	TWA	50 ppm 233 mg/m <sup>3</sup>	CA AB OEL
		TWA	50 ppm	CA BC OEL
		TWA	25 ppm 115 mg/m <sup>3</sup>	CA ON OEL
		TWAEV	50 ppm 233 mg/m <sup>3</sup>	CA QC OEL
		TWA	50 ppm	ACGIH
1-Methoxy-2-propanol	107-98-2	TWA	100 ppm 369 mg/m <sup>3</sup>	CA AB OEL
		STEL	150 ppm 553 mg/m <sup>3</sup>	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	100 ppm 369 mg/m <sup>3</sup>	CA QC OEL
		STEV	150 ppm 553 mg/m <sup>3</sup>	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
Zinc oxide	1314-13-2	TWA (Respirable)	2 mg/m <sup>3</sup>	CA AB OEL
		STEL (Respirable)	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Respirable)	2 mg/m <sup>3</sup>	CA BC OEL
		STEL (Respirable)	10 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (respirable dust)	2 mg/m <sup>3</sup>	CA QC OEL
		STEV (respirable dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respi-	2 mg/m <sup>3</sup>	ACGIH

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
 Date of first issue: 05/02/2018

		able particulate matter)		
		STEL (Respirable particulate matter)	10 mg/m <sup>3</sup>	ACGIH

**Occupational exposure limits of decomposition products**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Formaldehyde	50-00-0	TWA	0.75 ppm 0.9 mg/m <sup>3</sup>	CA AB OEL
		(c)	1 ppm 1.3 mg/m <sup>3</sup>	CA AB OEL
		TWA	0.1 ppm	CA BC OEL
		STEL	0.3 ppm	CA BC OEL
		STEL	1 ppm	CA ON OEL
		C	1.5 ppm	CA ON OEL
		C	2 ppm 3 mg/m <sup>3</sup>	CA QC OEL
		TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
Methanol	67-56-1	TWA	200 ppm 262 mg/m <sup>3</sup>	CA AB OEL
		STEL	250 ppm 328 mg/m <sup>3</sup>	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		STEV	250 ppm 328 mg/m <sup>3</sup>	CA QC OEL
		TWAEV	200 ppm 262 mg/m <sup>3</sup>	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI



**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
 Date of first issue: 05/02/2018

Isobutyl methyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI
------------------------	----------	------------------------	-------	--	--------	-----------

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

**Personal protective equipment**

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

**Hand protection**

Material : butyl-rubber  
 Break through time : <= 15 min  
 Glove thickness : 0.7 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
 Wear the following personal protective equipment:  
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
 When using do not eat, drink or smoke.  
 Wash contaminated clothing before re-use.

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : aerosol

Propellant : Dimethyl ether

Color : colored

Odor : characteristic

Odor Threshold : No data available

pH : Solvent mixture; pH value determination not possible, no aqueous solution

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 18.6 %(V)

Lower explosion limit / Lower flammability limit : 2.6 %(V)

Vapor pressure : 3,400 hPa (20 °C)

Relative vapor density : Not applicable

Relative density : No data available

Solubility(ies)  
Water solubility : partly miscible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 235 °C

Decomposition temperature : No data available

**2K RAPID PRIMER FILLER, 366 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

---

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

**Hazardous decomposition products**  
Thermal decomposition : Formaldehyde  
Methanol

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

---

## 2K RAPID PRIMER FILLER, 366 g

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

Method: Calculation method

**Components:****Dimethyl ether:**

Acute inhalation toxicity : LC50 (Rat): 164000 ppm  
Exposure time: 4 h  
Test atmosphere: gas

**Acetone:**

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

**n-Butyl acetate:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Xylene:**

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

**Isobutyl methyl ketone:**

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

**Butan-1-ol:**

Acute oral toxicity : LD50 (Rat): 790 mg/kg  
Acute inhalation toxicity : LC0 (Rat): > 17.76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Acute dermal toxicity : LD50 (Rabbit): 3,430 mg/kg

**Heptan-2-one:**

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 16.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

**1-Methoxy-2-propanol:**

Acute oral toxicity : LD50 (Rat): 4,016 mg/kg  
Acute inhalation toxicity : LC50 (Mouse): < 22.2 mg/l  
Exposure time: 6 h  
Test atmosphere: vapor  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Zinc oxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

**n-Butyl acetate:**

Species : Rabbit  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

**Xylene:**

Species : Rabbit  
Result : Skin irritation

**Isobutyl methyl ketone:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

**Butan-1-ol:**

Species : Rabbit  
Result : Skin irritation

**Heptan-2-one:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

**1-Methoxy-2-propanol:**

Species : Rabbit  
Result : No skin irritation

**Zinc oxide:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****Acetone:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

**n-Butyl acetate:**

Species : Rabbit  
Result : No eye irritation

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

|| Method : OECD Test Guideline 405

**Xylene:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

**Isobutyl methyl ketone:**

|| Species : Human  
|| Result : Irritation to eyes, reversing within 21 days

**Butan-1-ol:**

Species : Rabbit  
Result : Irreversible effects on the eye  
Method : OECD Test Guideline 405

**Heptan-2-one:**

|| Species : Rabbit  
|| Result : No eye irritation  
|| Method : OECD Test Guideline 405

**1-Methoxy-2-propanol:**

|| Species : Rabbit  
|| Result : No eye irritation

**Zinc oxide:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Acetone:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**n-Butyl acetate:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

**Xylene:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Result : negative

**Isobutyl methyl ketone:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

**Butan-1-ol:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

**Heptan-2-one:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

**1-Methoxy-2-propanol:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**Zinc oxide:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Dimethyl ether:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative



## 2K RAPID PRIMER FILLER, 366 g

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)  
Application Route: inhalation (gas)  
Result: negative

**Acetone:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

**n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Xylene:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Skin contact  
Result: negative

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

**Isobutyl methyl ketone:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: equivocal

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

**Butan-1-ol:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

**Heptan-2-one:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: DNA Repair  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**1-Methoxy-2-propanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

## 2K RAPID PRIMER FILLER, 366 g

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-  
malian cells  
Result: equivocal

Test Type: DNA damage and repair, unscheduled DNA syn-  
thesis in mammalian cells (in vitro)  
Method: OECD Test Guideline 482  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

**Zinc oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: equivocal

Test Type: Chromosome aberration test in vitro  
Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Method: OECD Test Guideline 474  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

**Carcinogenicity**

Suspected of causing cancer.

**Components:****Dimethyl ether:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Result : negative

**Acetone:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 424 days  
Result : negative

**Xylene:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative

**Isobutyl methyl ketone:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive

Species : Mouse  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

**1-Methoxy-2-propanol:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : negative

**Zinc oxide:**

Species : Mouse

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

Application Route : Ingestion  
Exposure time : 1 Years  
Result : negative  
Remarks : Based on data from similar materials

**Reproductive toxicity**

Not classified based on available information.

**Components:****Dimethyl ether:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Acetone:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**n-Butyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Xylene:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Isobutyl methyl ketone:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Butan-1-ol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

**Heptan-2-one:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 421  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 414  
Result: negative

**1-Methoxy-2-propanol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)

**2K RAPID PRIMER FILLER, 366 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

---

Result: negative

**Zinc oxide:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

**STOT-single exposure**

May cause drowsiness or dizziness.

**Components:****Dimethyl ether:**

Assessment : May cause drowsiness or dizziness.

**Acetone:**

Assessment : May cause drowsiness or dizziness.

**n-Butyl acetate:**

Assessment : May cause drowsiness or dizziness.

**Xylene:**

Assessment : May cause respiratory irritation.

**Isobutyl methyl ketone:**

||Assessment : May cause drowsiness or dizziness.

**Butan-1-ol:**

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

**1-Methoxy-2-propanol:**

Assessment : May cause drowsiness or dizziness.

**STOT-repeated exposure**

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

**Components:****Xylene:**

Routes of exposure : inhalation (vapor)  
Target Organs : Auditory system  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

**Heptan-2-one:**

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Zinc oxide:**

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

**Repeated dose toxicity****Components:****Dimethyl ether:**

Species : Rat  
NOAEL : 47.11 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 2 y

**Acetone:**

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1,700 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 45 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 8 Weeks

**n-Butyl acetate:**

Species : Rat  
NOAEL : 2.4 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days

**Xylene:**

Species : Rat  
LOAEL : > 0.2 - 1 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials



**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

Species : Rat  
LOAEL : 150 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

**Isobutyl methyl ketone:**

Species : Rat  
NOAEL : 250 mg/kg  
LOAEL : 1,000 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

Species : Rat  
NOAEL : 4.106 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 14 Weeks

**Butan-1-ol:**

Species : Rat  
NOAEL : 125 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

**Heptan-2-one:**

Species : Rat  
NOAEL : > 20 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

Species : Rat  
NOAEL :  $\geq 4.779$  mg/l  
Application Route : inhalation (vapor)  
Exposure time : 10 Months

**1-Methoxy-2-propanol:**

Species : Rat  
NOAEL : 919 mg/kg  
Application Route : Ingestion  
Exposure time : 35 Days

Species : Rat  
NOAEL : 1.1 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 2 y  
Method : OECD Test Guideline 453

Species : Rabbit  
NOAEL : 1,838 mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

**Zinc oxide:**

Species : Rat, male  
NOAEL : 0.0015 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 3 Months  
Method : OECD Test Guideline 413

**Aspiration toxicity**

Not classified based on available information.

**Components:****Acetone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

**Xylene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Isobutyl methyl ketone:**

|| The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

**Butan-1-ol:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

**Heptan-2-one:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Dimethyl ether:**

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4,100 mg/l  
Exposure time: 96 h  
  
Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 4,400 mg/l  
aquatic invertebrates : Exposure time: 48 h  
  
Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1,600 mg/l

**Acetone:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l

**2K RAPID PRIMER FILLER, 366 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

---

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)):  $\geq$  79 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l  
Exposure time: 30 min  
Method: ISO 8192

**n-Butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (Water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

**Xylene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l

**2K RAPID PRIMER FILLER, 366 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

plants	Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l Exposure time: 35 d Method: OECD Test Guideline 210 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	: NOEC: > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials

**Isobutyl methyl ketone:**

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 179 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 200 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 30 mg/l Exposure time: 21 d

**Butan-1-ol:**

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 1,376 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1,328 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 225 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 4.1 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	: EC50 (Pseudomonas putida): 4,390 mg/l Exposure time: 17 h

**Heptan-2-one:**

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 131 mg/l
------------------	---

**2K RAPID PRIMER FILLER, 366 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

---

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 90.1 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 98.2 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 42.68 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 52 mg/l  
Exposure time: 16 h

**1-Methoxy-2-propanol:**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 6,812 mg/l  
Exposure time: 96 h  
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 23,300 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Skeletonema costatum (marine diatom)): 6,745 mg/l  
Exposure time: 72 h  
Method: ISO 10253

Toxicity to microorganisms : IC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

**Zinc oxide:**

Toxicity to fish : LC50: > 0.1 - 1 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136 mg/l  
Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Jordanella floridae (flagfish)): > 0.01 - 0.1 mg/l  
Exposure time: 14 Weeks  
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

aquatic invertebrates (Chronic toxicity)

Exposure time: 7 d  
Remarks: Based on data from similar materials

**Persistence and degradability****Components:****Dimethyl ether:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

**Acetone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

**n-Butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

**Xylene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**Isobutyl methyl ketone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Butan-1-ol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 92 %  
Exposure time: 20 d

**Heptan-2-one:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 69 %  
Exposure time: 28 d  
Method: OECD Test Guideline 310

**1-Methoxy-2-propanol:**

**2K RAPID PRIMER FILLER, 366 g**

Version 8.0      Revision Date: 10/11/2022      SDS Number: 10658337-00009      Date of last issue: 08/02/2022  
Date of first issue: 05/02/2018

---

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 96 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301E

**Bioaccumulative potential****Components:****Dimethyl ether:**

Partition coefficient: n-octanol/water : log Pow: 0.2

**Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

**n-Butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3

**Xylene:**

Partition coefficient: n-octanol/water : log Pow: 3.16  
Remarks: Calculation

**Isobutyl methyl ketone:**

Partition coefficient: n-octanol/water : log Pow: 1.9

**Butan-1-ol:**

Partition coefficient: n-octanol/water : log Pow: 1

**Heptan-2-one:**

Partition coefficient: n-octanol/water : log Pow: 2.26

**1-Methoxy-2-propanol:**

Partition coefficient: n-octanol/water : log Pow: < 1

**Zinc oxide:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 78 - 2,060

**Mobility in soil**

No data available

**2K RAPID PRIMER FILLER, 366 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

---

**Other adverse effects**No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)
- 

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

- UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

**IATA-DGR**

- UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

- UN number : UN 1950  
Proper shipping name : AEROSOLS
- Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation**



**2K RAPID PRIMER FILLER, 366 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

---

**TDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION****The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA AB OEL / STEL : 15-minute occupational exposure limit  
CA AB OEL / (c) : ceiling occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA BC OEL / STEL : short-term exposure limit  
CA BC OEL / C : ceiling limit  
CA ON OEL / C : Ceiling Limit (C)  
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)  
CA ON OEL / STEL : Short-Term Exposure Limit (STEL)  
CA QC OEL / TWA EV : Time-weighted average exposure value  
CA QC OEL / STEV : Short-term exposure value  
CA QC OEL / C : Ceiling

---

## 2K RAPID PRIMER FILLER, 366 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/02/2022
8.0	10/11/2022	10658337-00009	Date of first issue: 05/02/2018

---

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/11/2022  
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8