

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

SECTION 1. IDENTIFICATION

Product name : Solder Slug, 3/0 AWG, Purple

Product code : 8217.9506

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Solder

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Carcinogenicity : Category 2

Reproductive toxicity : Category 1A

Effects on or via lactation

Specific target organ toxicity : Category 1 (Central nervous system, Kidney, Blood)
- repeated exposure

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H351 Suspected of causing cancer.
H360FD May damage fertility. May damage the unborn child.
H362 May cause harm to breast-fed children.
H372 Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust, fume, gas, mist, vapors or spray.
P263 Avoid contact during pregnancy and while nursing.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves, protective clothing, eye protection and face protection.
Response:
P308 + P313 IF exposed or concerned: Get medical attention.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

May cause thermal burns.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Tin	No data available	7440-31-5	$\geq 60 - < 80$ *
Lead	Plumbum	7439-92-1	$\geq 30 - < 60$ *
Rosin	No data available	8050-09-7	$\geq 1 - < 5$ *

* Actual concentration or concentration range is withheld as a trade secret

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.1	06/24/2024	10776807-00008	Date of first issue: 06/07/2017

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : Cool melted product on skin with plenty of water. Do not remove solidified product.
Remove contaminated clothing and shoes.
Get medical attention immediately.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eye with plenty of water.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Suspected of causing cancer.
May damage fertility. May damage the unborn child.
May cause harm to breast-fed children.
Causes damage to organs through prolonged or repeated exposure.
Contact with hot product will cause thermal burns.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Not applicable
Will not burn
- Unsuitable extinguishing media : Not applicable
Will not burn
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Metal oxides
Lead compounds
Carbon oxides
-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.1	06/24/2024	10776807-00008	Date of first issue: 06/07/2017

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Allow to solidify, use mechanical handling equipment.
Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not breathe decomposition products.

Avoid contact during pregnancy and while nursing.
Do not get on skin or clothing.
Do not breathe dust, fume, gas, mist, vapors or spray.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-
-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

assessment
Keep container tightly closed.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Tin	7440-31-5	TWA	2 mg/m ³	CA AB OEL
		TWA	2 mg/m ³	CA BC OEL
		TWA	2 mg/m ³	CA ON OEL
		TWAEV	2 mg/m ³	CA QC OEL
		TWA (Inhalable particulate matter)	2 mg/m ³ (Tin)	ACGIH
Lead	7439-92-1	TWA	0.05 mg/m ³	CA BC OEL
		TWA	0.05 mg/m ³ (Lead)	CA AB OEL
		TWAEV	0.05 mg/m ³ (Lead)	CA QC OEL
		TWA	0.05 mg/m ³ (Lead)	CA ON OEL
		TWA	0.05 mg/m ³ (Lead)	ACGIH
Rosin	8050-09-7	TWA (Inhalable particulate matter)	0.001 mg/m ³ (total Resin acids)	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lead monoxide	1317-36-8	TWA	0.05 mg/m ³ (Lead)	CA AB OEL
		TWAEV	0.05 mg/m ³	CA QC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

			(Lead)	
		TWA	0.05 mg/m ³ (Lead)	CA BC OEL
		TWA	0.05 mg/m ³ (Lead)	CA ON OEL
		TWA	0.05 mg/m ³ (Lead)	ACGIH
Formaldehyde	50-00-0	TWA	0.75 ppm 0.9 mg/m ³	CA AB OEL
		(c)	1 ppm 1.3 mg/m ³	CA AB OEL
		TWA	0.1 ppm	CA BC OEL
		STEL	0.3 ppm	CA BC OEL
		STEL	1 ppm	CA ON OEL
		C	1.5 ppm	CA ON OEL
		C	1.5 ppm	CA QC OEL
		TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
Acetaldehyde	75-07-0	(c)	25 ppm 45 mg/m ³	CA AB OEL
		C	25 ppm	CA BC OEL
		C	25 ppm 45 mg/m ³	CA QC OEL
		C	25 ppm	ACGIH
Acrolein	107-02-8	(c)	0.1 ppm 0.2 mg/m ³	CA AB OEL
		C	0.1 ppm	CA BC OEL
		TWAEV	0.1 ppm 0.23 mg/m ³	CA QC OEL
		STEV	0.3 ppm 0.69 mg/m ³	CA QC OEL
		C	0.1 ppm	ACGIH
Butyraldehyde	123-72-8	TWA	25 ppm 75 mg/m ³	US WEEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Lead	7439-92-1	Lead (Lead)	In blood	Not criti-cal	200 µg/l	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-sure assessment demonstrates exposures outside the re-commended guidelines, use respiratory protection.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

- Filter type : Self-contained breathing apparatus
- Hand protection
Material : Heat resistant gloves
- Material : Nitrile rubber
- Material : Natural Rubber
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Eye protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : solid
- Color : silver, gray
- Odor : odorless
- Odor Threshold : No data available
- pH : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

Melting point/freezing point : > 100 °C

Initial boiling point and boiling range : 1,740 °C

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : Not applicable

Lower explosion limit / Lower flammability limit : Not applicable

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

Density : 8.4 g/cm³ (20 °C)

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : Not applicable

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.1	06/24/2024	10776807-00008	Date of first issue: 06/07/2017

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition products

Thermal decomposition : Lead monoxide
Formaldehyde
Acetaldehyde
Acrolein
Butyraldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Tin:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.75 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Lead:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Rosin:

Acute oral toxicity : LD50 (Rat): 2,800 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Tin:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Lead:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Rosin:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Tin:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Lead:

Species : Rabbit
Result : No eye irritation

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Rosin:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Lead:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Rosin:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Tin:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Rosin:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:

Tin:

Species : Rat
Application Route : Ingestion
Exposure time : 115 weeks
Result : negative
Remarks : Based on data from similar materials

Lead:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : positive
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

May damage fertility. May damage the unborn child.
May cause harm to breast-fed children.

Components:

Lead:

Reproductive toxicity - Assessment : Positive evidence of adverse effects on sexual function and fertility from human epidemiological studies., Positive evidence of adverse effects on development from human epidemiological studies., Studies indicating a hazard to babies during the lactation period

Rosin:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

Components:

Lead:

Target Organs : Kidney, Central nervous system, Blood
Assessment : Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Tin:

Species : Rat
NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 407

Rosin:

Species : Rat, male
NOAEL : 335 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Lead:

General Information : Target Organs: Blood
Symptoms: anemia

Target Organs: Central nervous system
Symptoms: Neurological disorders

Target Organs: Kidney
Symptoms: renal failure

Target Organs: Reproductive organs
Symptoms: Reduced fertility, male reproductive effects

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Tin:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 12.4 µg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 19.2 µg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 100 µg/l
Exposure time: 7 d
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to microorganisms : EC50: > 511 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Lead:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l
Exposure time: 48 h
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l
Exposure time: 72 h
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

EC10 (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l
Exposure time: 72 h
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

Toxicity to fish (Chronic toxicity) : EC10 (Oncorhynchus mykiss (rainbow trout)): > 0.01 - 0.1 mg/l
Exposure time: 570 d
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: > 0.001 - 0.01 mg/l
Exposure time: 30 d

Rosin:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1 - 10 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 911 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Raphidocelis subcapitata (freshwater green alga)): 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 10,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Rosin:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 71 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version 4.1 Revision Date: 06/24/2024 SDS Number: 10776807-00008 Date of last issue: 05/29/2023
Date of first issue: 06/07/2017

Bioaccumulative potential

Components:

Rosin:

Partition coefficient: n-octanol/water : log Pow: > 3 - 6.2
Method: OECD Test Guideline 117

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead)
Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s. (Lead)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

IMDG-Code

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.1	06/24/2024	10776807-00008	Date of first issue: 06/07/2017

UN number	:	UN 3077
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead)
Class	:	9
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number	:	UN 3077
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead)
Class	:	9
Packing group	:	III
Labels	:	9
ERG Code	:	171
Marine pollutant	:	yes(Lead)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products VOC content: 0 %
---	--

The ingredients of this product are reported in the following inventories:

DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	---	--

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.1	06/24/2024	10776807-00008	Date of first issue: 06/07/2017

CA QC OEL	:	the Occupational Health and Safety Act. Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / (c)	:	ceiling occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA BC OEL / C	:	ceiling limit
CA ON OEL / C	:	Ceiling Limit (C)
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA ON OEL / STEL	:	Short-Term Exposure Limit (STEL)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
CA QC OEL / C	:	Ceiling
US WEEL / TWA	:	8-hr TWA

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Solder Slug, 3/0 AWG, Purple

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2023
4.1	06/24/2024	10776807-00008	Date of first issue: 06/07/2017

compile the Material Safety
Data Sheet

eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/24/2024
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8