

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
Date of first issue: 04/06/2020

SECTION 1. IDENTIFICATION

Product name : HIGH-BUILD UNDERBODY SEALANT, 560 g
Product code : 890.90720
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Coloring agents, dyes

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Carcinogenicity (Inhalation) : Category 1A
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
Date of first issue: 04/06/2020

Specific target organ toxicity : Category 2 (Central nervous system)
- repeated exposure

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H350 May cause cancer by inhalation.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
 Date of first issue: 04/06/2020

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Toluene	108-88-3	$\geq 10 - < 30$ *
Limestone	1317-65-3	$\geq 10 - < 30$ *
Propane	74-98-6	$\geq 10 - < 30$ *
Isobutane	75-28-5	$\geq 5 - < 10$ *
Solvent naphtha (petroleum), heavy aliphatic	64742-96-7	$\geq 1 - < 5$ *
Quartz	14808-60-7	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
 If vomiting occurs have person lean forward.
 Call a physician or poison control center immediately.
 Rinse mouth thoroughly with water.
 Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
 Causes skin irritation.
 May cause drowsiness or dizziness.

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

May cause cancer by inhalation.
 Suspected of damaging the unborn child.
 May cause damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
 Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Flash back possible over considerable distance.
 Vapors may form explosive mixtures with air.
 Exposure to combustion products may be a hazard to health.
 If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
 Nitrogen oxides (NO_x)
 Silicon oxides
 Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Use water spray to cool unopened containers.
 Remove undamaged containers from fire area if it is safe to do so.
 Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
 Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
 Use personal protective equipment.
 Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
 Prevent further leakage or spillage if safe to do so.
 Prevent spreading over a wide area (e.g., by containment or oil barriers).

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
 Date of first issue: 04/06/2020

Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable solids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which in contact with water emit flammable gases
 Explosives

Recommended storage temperature : < 40 °C

Storage period : 36 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Toluene	108-88-3	TWA	50 ppm 188 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
Limestone	1317-65-3	TWA	10 mg/m ³	CA AB OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
Propane	74-98-6	STEL	20 mg/m ³	CA BC OEL
		TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
Isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Solvent naphtha (petroleum), heavy aliphatic	64742-96-7	TWA	200 mg/m ³ (total hydrocarbon vapor)	CA AB OEL
Quartz	14808-60-7	TWA (Respirable particulates)	0.025 mg/m ³	CA AB OEL
		TWA (Respirable frac-	0.1 mg/m ³	CA ON OEL

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
 Date of first issue: 04/06/2020

		tion)		
		TWAEV (respirable dust)	0.1 mg/m ³	CA QC OEL
		TWA (Res- pirable)	0.025 mg/m ³ (Silica)	CA BC OEL
		TWA (Respi- rable particu- late matter)	0.025 mg/m ³ (Silica)	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work- week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
 Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

Filter type	:	Self-contained breathing apparatus
Hand protection Material	:	butyl-rubber
Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
Eye protection	:	Wear the following personal protective equipment: Safety glasses
Skin and body protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Hygiene measures	:	If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Propellant	:	Propane, Isobutane
Color	:	black
Odor	:	solvent
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling	:	90 °C

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

range

Flash point	:	-4 °C	Flash point is only valid for liquid portion in the aerosol can.
Evaporation rate	:	Not applicable	
Flammability (solid, gas)	:	Extremely flammable aerosol.	
Upper explosion limit / Upper flammability limit	:	12.9 %(V)	
Lower explosion limit / Lower flammability limit	:	0.5 %(V)	
Vapor pressure	:	50 - 80 mmHg (21 °C)	
Relative vapor density	:	> 1	
Relative density	:	1.01	
Solubility(ies)			
Water solubility	:	No data available	
Partition coefficient: n-octanol/water	:	Not applicable	
Autoignition temperature	:	> 232 °C	
Decomposition temperature	:	No data available	
Viscosity			
Viscosity, dynamic	:	Not applicable	
Viscosity, kinematic	:	Not applicable	
Explosive properties	:	Not explosive	
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.	
Particle size	:	Not applicable	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:**Toluene:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Limestone:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

Solvent naphtha (petroleum), heavy aliphatic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:**Toluene:**

Species : Rabbit
Method : Directive 67/548/EEC, Annex V, B.4.
Result : Skin irritation

Limestone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Solvent naphtha (petroleum), heavy aliphatic:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
Date of first issue: 04/06/2020

Quartz:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Toluene:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Limestone:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Solvent naphtha (petroleum), heavy aliphatic:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Quartz:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Toluene:**

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : Directive 67/548/EEC, Annex V, B.6.
Result : negative

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
Date of first issue: 04/06/2020

Limestone:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

Solvent naphtha (petroleum), heavy aliphatic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:**Toluene:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: inhalation (vapor)
Method: OECD Test Guideline 478
Result: negative

Limestone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

Remarks: Based on data from similar materials

Propane:Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negativeGenotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative**Isobutane:**Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materialsGenotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials**Solvent naphtha (petroleum), heavy aliphatic:**Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materialsGenotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative
Remarks: Based on data from similar materials**Carcinogenicity**

May cause cancer by inhalation.

Components:**Toluene:**Species : Rat
Application Route : inhalation (vapor)
Exposure time : 103 weeks
Result : negativeSpecies : Mouse
Application Route : Skin contact
Exposure time : 24 Months

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
Date of first issue: 04/06/2020

Result : negative

Quartz:

Species : Humans
Application Route : inhalation (dust/mist/fume)
Result : positive

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Reproductive toxicity

Suspected of damaging the unborn child.

Components:**Toluene:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
Date of first issue: 04/06/2020

Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Solvent naphtha (petroleum), heavy aliphatic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Toluene:**

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

Isobutane:

Assessment : May cause drowsiness or dizziness.

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version Revision Date: SDS Number: Date of last issue: 04/06/2020
1.1 11/19/2020 5638269-00002 Date of first issue: 04/06/2020

Solvent naphtha (petroleum), heavy aliphatic:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:**Toluene:**

Routes of exposure : Inhalation
Target Organs : Central nervous system
Assessment : May cause damage to organs through prolonged or repeated exposure.

Quartz:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Toluene:**

Species : Rat
LOAEL : 1.875 mg/l
Application Route : inhalation (vapor)
Exposure time : 6 Months

Species : Rat
NOAEL : 625 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Limestone:

Species : Rat
NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 422
Remarks : Based on data from similar materials

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

Isobutane:

Species	:	Rat
NOAEL	:	9000 ppm
Application Route	:	inhalation (gas)
Exposure time	:	6 Weeks
Method	:	OECD Test Guideline 422

Solvent naphtha (petroleum), heavy aliphatic:

Species	:	Rat
NOAEL	:	750 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

Quartz:

Species	:	Rat
LOAEL	:	0.002 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	13 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Components:**Toluene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Solvent naphtha (petroleum), heavy aliphatic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure**Components:****Toluene:**

Inhalation	:	Target Organs: Central nervous system Symptoms: Neurological disorders
------------	---	---

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version 1.1 Revision Date: 11/19/2020 SDS Number: 5638269-00002 Date of last issue: 04/06/2020
Date of first issue: 04/06/2020

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Toluene:**

- Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : NOEC (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l
Exposure time: 40 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l
Exposure time: 7 d
- Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 84 mg/l
Exposure time: 24 h

Limestone:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials
- EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials
- Toxicity to microorganisms : EC50: > 100 mg/l

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Solvent naphtha (petroleum), heavy aliphatic:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.4 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL10 (Pseudokirchneriella subcapitata (green algae)): 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.48 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction

Quartz:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Persistence and degradability**Components:****Toluene:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 20 d

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

Remarks: Based on data from similar materials

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Solvent naphtha (petroleum), heavy aliphatic:

Biodegradability : Result: Inherently biodegradable.

Bioaccumulative potential**Components:****Toluene:**

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 90

Partition coefficient: n-octanol/water : log Pow: 2.73

Isobutane:

Partition coefficient: n-octanol/water : log Pow: 2.8

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION**International Regulations**

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
ERG Code : 126
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 328.3 g/l
Remarks: VOC content excluding water

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEL	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transporta-

HIGH-BUILD UNDERBODY SEALANT, 560 g

Version	Revision Date:	SDS Number:	Date of last issue: 04/06/2020
1.1	11/19/2020	5638269-00002	Date of first issue: 04/06/2020

tion of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/19/2020
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8