

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

SECTION 1. IDENTIFICATION

Product name : PAG 46-H, HFO-1234YF lubricant, 236 mL
Product code : 892.123470
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Acute toxicity (Oral) : Category 4
Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitization : Sub-category 1A

GHS label elements

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version 2.4 Revision Date: 06/23/2024 SDS Number: 10669818-00009 Date of last issue: 11/20/2022
Date of first issue: 05/10/2017

Hazard pictograms

:



Signal Word

: Warning

Hazard Statements

: H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary Statements

: **Prevention:**
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, eye protection and face protection.
Response:
P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-	Polyoxypropylene Monobutyl ether	9003-13-8	$\geq 80 - \leq 100$ *
[[[2-	2-Ethylhexyl	2461-15-6	$\geq 1 - < 5$ *

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version 2.4	Revision Date: 06/23/2024	SDS Number: 10669818-00009	Date of last issue: 11/20/2022 Date of first issue: 05/10/2017
----------------	------------------------------	-------------------------------	---

Ethylhex-
yl)oxy]methyl]oxirane

glycidyl ether

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Get medical attention.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

Avoid breathing mist or vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

- Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Organic vapor Type

Hand protection

- Material : Nitrile rubber
Break through time : 240 min
Glove thickness : 0.11 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : Colorless to pale yellow

Odor : characteristic

Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 200 °C

Flash point : 174 °C
Method: ASTM D 93, closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

Density	:	No data available
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	41.4 - 50.6 mm ² /s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed.

Product:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

Acute oral toxicity : Acute toxicity estimate: 505.05 mg/kg
Method: Calculation method

Components:

Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-:

Acute oral toxicity : LD50 (Rat, female): > 300 - < 2,000 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

[[2-Ethylhexyl]oxy]methyl]oxirane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.15 mg/l
Exposure time: 7 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:

Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-:

Species : reconstructed human epidermis (RhE)
Method : Regulation (EC) No. 440/2008, Annex, B.40
Result : Skin irritation

[[2-Ethylhexyl]oxy]methyl]oxirane:

Species : Rabbit
Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-:

Result : Irritation to eyes, reversing within 21 days

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version 2.4 Revision Date: 06/23/2024 SDS Number: 10669818-00009 Date of last issue: 11/20/2022
Date of first issue: 05/10/2017

[[[(2-Ethylhexyl)oxy]methyl]oxirane:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

[[[(2-Ethylhexyl)oxy]methyl]oxirane:

Test Type : Maurer optimisation test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : positive

Assessment : Probability or evidence of high skin sensitization rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

[[[(2-Ethylhexyl)oxy]methyl]oxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

Reproductive toxicity

Not classified based on available information.

Components:

Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-:

Species : Rat
NOAEL : 100 mg/kg
LOAEL : 500 mg/kg
Application Route : Ingestion
Exposure time : 28 - 54 Days
Method : OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 333 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction

EL10 (Pseudokirchneriella subcapitata (green algae)): 93.7 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 10 min
Method: OECD Test Guideline 209

[[[(2-Ethylhexyl)oxy]methyl]oxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 5,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 7.2 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Persistence and degradability

Components:

Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

[[[(2-Ethylhexyl)oxy]methyl]oxirane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Bioaccumulative potential

Components:

Poly[oxy(methyl-1,2-ethanediyl)], α -butyl- ω -hydroxy-:

Partition coefficient: n- : log Pow: > 1.18 - 4.37

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version 2.4	Revision Date: 06/23/2024	SDS Number: 10669818-00009	Date of last issue: 11/20/2022 Date of first issue: 05/10/2017
----------------	------------------------------	-------------------------------	---

octanol/water

Method: OECD Test Guideline 117

[[[(2-Ethylhexyl)oxy]methyl]oxirane:

Partition coefficient: n- : log Pow: 3.83
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content

CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 -
Guidelines for VOC in Consumer Products
VOC content: 0 %

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/23/2024
Date format : mm/dd/yyyy

SAFETY DATA SHEET

according to the Hazardous Products Regulations



PAG 46-H, HFO-1234YF lubricant, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/20/2022
2.4	06/23/2024	10669818-00009	Date of first issue: 05/10/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8