

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

SECTION 1. IDENTIFICATION

Product name : PURLOGIC EASY, Insulating mounting foam, 553 g
Product code : 892.143
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Foams
Sealant

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Acute toxicity (Inhalation) : Category 4
Skin irritation : Category 2
Eye irritation : Category 2B
Respiratory sensitization : Category 1

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

Skin sensitization : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3
- single exposure

Specific target organ toxicity : Category 2 (Respiratory Tract)
- repeated exposure (Inhalation)

Simple Asphyxiant : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 + H320 Causes skin and eye irritation.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.
May displace oxygen and cause rapid suffocation.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.
P284 Wear respiratory protection.

**PURLOGIC EASY, Insulating mounting foam,
553 g**
Version
6.2Revision Date:
11/03/2022SDS Number:
10622308-00008Date of last issue: 06/08/2022
Date of first issue: 06/05/2015**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical attention.
 P333 + P313 If skin irritation or rash occurs: Get medical attention.
 P337 + P313 If eye irritation persists: Get medical attention.
 P342 + P311 If experiencing respiratory symptoms: Call a doctor.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Diphenylmethane diisocyanate, isomers and homologues	Polymethylene polyphenyl polyisocyanate	9016-87-9	>= 30 - < 60 *
Isobutane	Propane, 2-methyl-	75-28-5	>= 5 - < 10 *
Dimethyl ether	Methane, 1,1'-oxybis-	115-10-6	>= 5 - < 10 *
Phosphorous oxychloride, reaction products with propylene oxide	2-Propanol, 1-chloro-, 2,2',2''-phosphate	1244733-77-4	>= 1 - < 5 *
Propane	Dimethylmethane	74-98-6	>= 1 - < 5 *
4,4'-Diphenylmethane diisocyanate	Benzene, 1,1'-methylenebis[4-	101-68-8	>= 0.1 - < 1 *

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

	isocyanato-		
--	-------------	--	--

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- | | | |
|---|---|---|
| General advice | : | In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| If inhaled | : | If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately. |
| In case of skin contact | : | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : | Causes skin and eye irritation.
May cause an allergic skin reaction.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure if inhaled.
Gas reduces oxygen available for breathing.
Respiratory symptoms, including pulmonary edema, may be delayed.
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome). |
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| Notes to physician | : | Treat symptomatically and supportively. |

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray in large fire situations
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Chlorine compounds
Oxides of phosphorus
Nitrogen oxides (NO_x)
Isocyanates
Hydrogen cyanide (hydrocyanic acid)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for : Non-sparking tools should be used.
-

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

containment and cleaning up	<p>Soak up with inert absorbent material.</p> <p>Suppress (knock down) gases/vapors/mists with a water spray jet.</p> <p>For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.</p> <p>After approximately one hour, transfer to waste container and do not seal, due to evolution of carbon dioxide.</p> <p>Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.</p> <p>Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.</p>
-----------------------------	---

SECTION 7. HANDLING AND STORAGE

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	: If sufficient ventilation is unavailable, use with local exhaust ventilation. If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
Advice on safe handling	: Do not get on skin or clothing. Do not breathe spray. Do not swallow. Do not get in eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Keep container tightly closed. Keep away from water. Protect from moisture. Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Do not spray on an open flame or other ignition source. Do not breathe decomposition products.
Conditions for safe storage	: Store locked up.

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

Protect from moisture.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

Storage period : 12 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diphenylmethane diisocyanate, isomers and homologues	9016-87-9	TWA	0.005 ppm 0.07 mg/m ³	CA AB OEL
		TWAEV	0.005 ppm 0.051 mg/m ³	CA QC OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
Isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Dimethyl ether	115-10-6	TWA	1,000 ppm	CA BC OEL
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
4,4'-Diphenylmethane diisocyanate	101-68-8	TWA	0.005 ppm	CA BC OEL
		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWAEV	0.005 ppm 0.051 mg/m ³	CA QC OEL
		TWA	0.005 ppm	ACGIH

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Formaldehyde	50-00-0	TWA	0.75 ppm 0.9 mg/m ³	CA AB OEL
		(c)	1 ppm 1.3 mg/m ³	CA AB OEL
		TWA	0.1 ppm	CA BC OEL
		STEL	0.3 ppm	CA BC OEL
		STEL	1 ppm	CA ON OEL
		C	1.5 ppm	CA ON OEL
		C	2 ppm 3 mg/m ³	CA QC OEL
		TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
		Methanol	67-56-1	TWA
STEL	250 ppm 328 mg/m ³			CA AB OEL
TWA	200 ppm			CA BC OEL
STEL	250 ppm			CA BC OEL
STEV	250 ppm 328 mg/m ³			CA QC OEL
TWAEV	200 ppm 262 mg/m ³			CA QC OEL
TWA	200 ppm			ACGIH
STEL	250 ppm			ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Polyethylene
Break through time : > 30 min
Glove thickness : 0.025 mm

Remarks : Choose gloves to protect hands against chemicals depending

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Propellant : Isobutane, Propane, Butane, Dimethyl ether
- Color : colored
- Odor : characteristic
- Odor Threshold : No data available
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable
- Flash point : -21 °C

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	199 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
		Heating may cause an explosion.
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions. Polymerizes at high temperatures with evolution of carbon dioxide.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. Isocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; the-

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

se reactions can become violent. Contact is increased by stirring or if the other material mixes with the isocyanate.
 Exothermic reaction with acids, amines and alcohols
 Reacts with water to form carbon dioxide and heat
 Isocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea.
 If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
 Hazardous decomposition products will be formed upon contact with water or humid air.
 Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Exposure to moisture.
Heat, flames and sparks.

Incompatible materials : Oxidizing agents
 Acids
 Bases
 Water
 Alcohols
 Amines
 Ammonia
 Aluminum
 Zinc
 Brass
 Tin
 Copper
 Galvanized metals
 Humid air

Hazardous decomposition products

Thermal decomposition : Formaldehyde
Methanol

SECTION 11. TOXICOLOGICAL INFORMATION
Information on likely routes of exposure

Inhalation
 Skin contact
 Ingestion
 Eye contact

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 3.25 mg/l

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.24 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm
Exposure time: 4 h
Test atmosphere: gas

Phosphorous oxychloride, reaction products with propylene oxide:

Acute oral toxicity : LD50 (Rat): 500 - 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

4,4'-Diphenylmethane diisocyanate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral tox-

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

icity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2.24 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Species : Rabbit
Result : Skin irritation

Phosphorous oxychloride, reaction products with propylene oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

4,4'-Diphenylmethane diisocyanate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes eye irritation.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Result : Irritation to eyes, reversing within 7 days

Phosphorous oxychloride, reaction products with propylene oxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

4,4'-Diphenylmethane diisocyanate:

Result : Irritation to eyes, reversing within 7 days
Remarks : Based on national or regional regulation.

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

Routes of exposure : inhalation (dust/mist/fume)
Species : Rat
Result : positive

Assessment : Probability of respiratory sensitization in humans based on animal testing

Phosphorous oxychloride, reaction products with propylene oxide:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

4,4'-Diphenylmethane diisocyanate:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitization in humans

Routes of exposure : Inhalation
Species : Rat
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitization in humans based on animal testing

Germ cell mutagenicity

Not classified based on available information.

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative

Isobutane:

- Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Dimethyl ether:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
- Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
- Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
- Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila mel-*
anogaster (in vivo)
Application Route: inhalation (gas)
Result: negative

Phosphorous oxychloride, reaction products with propylene oxide:

- Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA syn-
thesis in mammalian cells (in vitro)
Method: OECD Test Guideline 482
Result: negative

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Dimethyl ether:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

Result : negative

4,4'-Diphenylmethane diisocyanate:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Result : positive
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: negative

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Phosphorous oxychloride, reaction products with propylene oxide:

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the
reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the
reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

4,4'-Diphenylmethane diisocyanate:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Assessment : May cause respiratory irritation.

Isobutane:

Assessment : May cause drowsiness or dizziness.

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version 6.2 Revision Date: 11/03/2022 SDS Number: 10622308-00008 Date of last issue: 06/08/2022
Date of first issue: 06/05/2015

Propane:

Assessment : May cause drowsiness or dizziness.

4,4'-Diphenylmethane diisocyanate:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Respiratory Tract) through prolonged or repeated exposure if inhaled.

Components:**Diphenylmethane diisocyanate, isomers and homologues:**

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Phosphorous oxychloride, reaction products with propylene oxide:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

4,4'-Diphenylmethane diisocyanate:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Repeated dose toxicity**Components:****Diphenylmethane diisocyanate, isomers and homologues:**

Species : Rat
NOAEL : 1.4 mg/m³
LOAEL : 4.1 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 13 Weeks

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Dimethyl ether:

Species : Rat
NOAEL : 47.11 mg/l

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

Application Route : inhalation (vapor)
Exposure time : 2 y

Phosphorous oxychloride, reaction products with propylene oxide:

Species : Rat
LOAEL : 52 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

4,4'-Diphenylmethane diisocyanate:

Species : Rat
NOAEL : 0,2 mg/m³
LOAEL : 1 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 y
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Diphenylmethane diisocyanate, isomers and homologues:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 10 mg/l
Exposure time: 21 d

Dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4,100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 4,400 mg/l

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

aquatic invertebrates Exposure time: 48 h

Toxicity to microorganisms : EC10 (*Pseudomonas putida*): > 1,600 mg/l

Phosphorous oxychloride, reaction products with propylene oxide:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 51 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): 131 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): 82
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (*Pseudokirchneriella subcapitata* (green algae)): 42 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other : NOEC (*Daphnia magna* (Water flea)): 32 mg/l
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d

Toxicity to microorganisms : EC50: 784 mg/l
Exposure time: 3 h
Method: ISO 8192

4,4'-Diphenylmethane diisocyanate:

Toxicity to fish : LC50 (*Oryzias latipes* (Orange-red killifish)): > 3,000 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): 129.7 mg/l
aquatic invertebrates Exposure time: 24 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (*Desmodesmus subspicatus* (green algae)): > 1,640
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (*Desmodesmus subspicatus* (green algae)): 1,640 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC (*Daphnia magna* (Water flea)): 10 mg/l
aquatic invertebrates (Chronic toxicity) Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Persistence and degradability**Components:****Diphenylmethane diisocyanate, isomers and homologues:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Phosphorous oxychloride, reaction products with propylene oxide:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 14 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.D.

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

4,4'-Diphenylmethane diisocyanate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 302
Remarks: Based on data from similar materials

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

Bioaccumulative potential**Components:****Isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2.8

Dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0.2

Phosphorous oxychloride, reaction products with propylene oxide:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 0.8 - 14

Partition coefficient: n-octanol/water : log Pow: 2.68

4,4'-Diphenylmethane diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 200

Partition coefficient: n-octanol/water : log Pow: 4.51

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1

IATA-DGR

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
ERG Code	: 126
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 20.6 % / 200 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION
Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA AB OEL / (c)	:	ceiling occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA BC OEL / C	:	ceiling limit
CA ON OEL / C	:	Ceiling Limit (C)
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA ON OEL / STEL	:	Short-Term Exposure Limit (STEL)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
CA QC OEL / C	:	Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Con-

**PURLOGIC EASY, Insulating mounting foam,
553 g**

Version	Revision Date:	SDS Number:	Date of last issue: 06/08/2022
6.2	11/03/2022	10622308-00008	Date of first issue: 06/05/2015

centration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/03/2022
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8