

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

SECTION 1. IDENTIFICATION

Product name : RTV SILICONE SEALANT, School bus yellow, 300 mL
Product code : 892.5717
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : 1-800-263-5002
Telefax : 1-905-564-3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Sealant
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin corrosion : Category 1
Serious eye damage : Category 1
Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.
H361f Suspected of damaging fertility.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version
6.1

Revision Date:
11/12/2025

SDS Number:
10702798-00010

Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

P264 Wash skin thoroughly after handling.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P330 + P331 + P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER.
P303 + P361 + P353 + P310 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.
P308 + P313 IF exposed or concerned: Get medical attention.
P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Corrosive to the respiratory tract.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated middle	No data available	64742-46-7	$\geq 5 - < 10$ *
Triacetoxymethylsilane	Silanetriol, 1-ethyl-, 1,1,1-triacetate	17689-77-9	$\geq 1 - < 5$ *
Methylsilanetriyl triacetate	Silanetriol, 1-methyl-, 1,1,1-triacetate	4253-34-3	$\geq 1 - < 5$ *
Carbon black	Lampblack	1333-86-4	$\geq 1 - < 5$ *
Titanium dioxide	Titanium(IV) oxide	13463-67-7	$\geq 1 - < 5$ *
Octamethylcyclotetra-siloxane	Cyclotetrasiloxane, 2,2,4,4,6,6,8,8-octamethyl-	556-67-2	$\geq 0.1 - < 1$ *

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention immediately.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Causes digestive tract burns.
Causes serious eye damage.
Suspected of damaging fertility.
Causes severe burns.
Corrosive to respiratory system.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Silicon oxides

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe dusts or mists.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure
-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

- assessment
Keep container tightly closed.
Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
Carbon black	1333-86-4	TWA	3.5 mg/m ³	CA AB OEL
		TWA (Inhalable)	3 mg/m ³	CA BC OEL
		TWAEV (inhalable dust)	3 mg/m ³	CA QC OEL
		TWA (Inhalable particulate matter)	3 mg/m ³	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Titanium dioxide

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m ³	CA AB OEL
		STEL	15 ppm 37 mg/m ³	CA AB OEL
		TWA	10 ppm	CA BC OEL
		STEL	15 ppm	CA BC OEL
		TWAEV	10 ppm 25 mg/m ³	CA QC OEL
		STEV	15 ppm 37 mg/m ³	CA QC OEL
		TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often!
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Color	:	yellow
Odor	:	vinegar-like
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	> 100 °C
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	Not applicable
Lower explosion limit / Lower flammability limit	:	Not applicable
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	1.007
Density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	Not applicable
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.
Hazardous decomposition products will be formed upon contact with water or humid air.

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents
Water

Hazardous decomposition products

Contact with water or humid air : Acetic acid

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

Distillates (petroleum), hydrotreated middle:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,000 mg/m³

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Triacetoxymethylsilane:

Acute oral toxicity : LD50 (Rat): 1,460 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Methylsilanetriyl triacetate:

Acute oral toxicity : LD50 (Rat): 1,600 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Carbon black:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 425
Remarks: The test was conducted according to guideline

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: The test was conducted according to guideline

Octamethylcyclotetrasiloxane:

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): 36 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,375 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

Skin corrosion/irritation

Causes severe burns.

Components:

Distillates (petroleum), hydrotreated middle:

Assessment : Repeated exposure may cause skin dryness or cracking.

Triacetoxymethylsilane:

Species : Rabbit
Result : Corrosive after 3 minutes to 1 hour of exposure

Methylsilanetriyl triacetate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

Carbon black:

Species : Rabbit
Result : No skin irritation

Titanium dioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : The test was conducted equivalent or similar to guideline

Octamethylcyclotetrasiloxane:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Distillates (petroleum), hydrotreated middle:

Result : No eye irritation

Triacetoxymethylsilane:

Result : Irreversible effects on the eye

Methylsilanetriyl triacetate:

Species : Rabbit
Result : Irreversible effects on the eye

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

Carbon black:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Titanium dioxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : The test was conducted according to guideline

Octamethylcyclotetrasiloxane:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated middle:

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Result : negative

Triacetoxymethylsilane:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Assessment : Does not cause skin sensitization.

Methylsilanetriyl triacetate:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

Carbon black:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Titanium dioxide:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : The test was conducted according to guideline

Octamethylcyclotetrasiloxane:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated middle:

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Triacetoxymethylsilane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Methylsilanetriyl triacetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Method: OECD Test Guideline 479
Result: negative

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila mel-
anogaster* (in vivo)
Species: *Drosophila melanogaster* (vinegar fly)
Application Route: Ingestion
Method: OECD Test Guideline 477
Result: negative

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: The test was conducted according to guideline

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: The test was conducted according to guideline

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: The test was conducted according to guideline

Genotoxicity in vivo : Test Type: Transgenic rodent somatic cell gene mutation as-
say
Species: Mouse (male)
Application Route: Intravenous injection
Method: OECD Test Guideline 488
Result: negative
Remarks: The test was conducted equivalent or similar to
guideline

Octamethylcyclotetrasiloxane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Inhalation
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Carbon black:

Species : Rat
Application Route : Inhalation
Exposure time : 24 Months
Result : positive

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Reproductive toxicity

Suspected of damaging fertility.

Components:

Carbon black:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Test Type: Embryo-fetal development
Species: Mouse
Application Route: inhalation (dust/mist/fume)
Result: negative

Titanium dioxide:

Effects on fertility : Test Type: Extended one-generation reproduction toxicity

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: negative
Remarks: The test was conducted according to guideline

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: The test was conducted according to guideline

Octamethylcyclotetrasiloxane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Inhalation
Method: OPPTS 870.3800
Result: positive

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Inhalation
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Titanium dioxide:

Species : Rat
NOAEL : $\geq 1,000$ mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : The test was conducted according to guideline

Octamethylcyclotetrasiloxane:

Species : Rat
NOAEL : 1.82 mg/l

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

Application Route : inhalation (vapor)
Exposure time : 2 y

Species : Rabbit
NOAEL : ≥ 960 mg/kg
Application Route : Skin contact
Exposure time : 3 Weeks

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated middle:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated middle:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): $> 87,556$ mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): $> 1,000$ mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): $> 1,000$ mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOELR: $> 1,000$ mg/l
Exposure time: 28 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 5 mg/l
Exposure time: 21 d

Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h

Triacetoxymethylsilane:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 251 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 168.7 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

Remarks: Data from similar compositions

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 24.41 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 18 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): \geq 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Methylsilanetriyl triacetate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 500 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): \geq 500 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.
Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 500 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

Carbon black:

- Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 5,600 mg/l
Exposure time: 24 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL10 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Titanium dioxide:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: The test was conducted according to guideline
Based on transformation/dissolution testing and data from soluble metal compounds
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: The test was conducted according to guideline
- Toxicity to algae/aquatic plants : EL50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline
- NOELR (Raphidocelis subcapitata (freshwater green alga)): >= 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline
- Toxicity to microorganisms : NOEC (activated sludge): >= 1,000 mg/l
Exposure time: 3 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

Method: OECD Test Guideline 209

Remarks: The test was conducted according to guideline

Octamethylcyclotetrasiloxane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.022 mg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 0.015 mg/l
aquatic invertebrates Exposure time: 48 h
Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): >
plants 0.022 mg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility.

EC10 (Pseudokirchneriella subcapitata (green algae)): >=
0.022 mg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.0044 mg/l
icity) Exposure time: 14 d

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 0.0079 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity)

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated middle:

Biodegradability : Result: Inherently biodegradable.

Triacetoxymethylsilane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 74 %
Exposure time: 21 d

Methylsilanetriyl triacetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 74 %
Exposure time: 21 d
Method: Directive 67/548/EEC Annex V, C.4.A.
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Biodegradability : Result: Not readily biodegradable.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

Biodegradation: 3.7 %
Exposure time: 29 d
Method: OECD Test Guideline 310

Bioaccumulative potential

Components:

Octamethylcyclotetrasiloxane:

Bioaccumulation : Species: Pimephales promelas (fathead minnow)
Bioconcentration factor (BCF): 12,400
Method: OPPTS 850.1730

Partition coefficient: n-octanol/water : log Pow: 6.488
Method: OECD Test Guideline 123

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1759
Proper shipping name : CORROSIVE SOLID, N.O.S.
(Methylsilanetriyl triacetate, Triacetoxylethylsilane)
Class : 8
Packing group : III
Labels : 8
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 1759
Proper shipping name : Corrosive solid, n.o.s.
(Methylsilanetriyl triacetate, Triacetoxylethylsilane)
Class : 8
Packing group : III
Labels : Corrosive

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

Packing instruction (cargo aircraft) : 864
Packing instruction (passenger aircraft) : 860

IMDG-Code

UN number : UN 1759
Proper shipping name : CORROSIVE SOLID, N.O.S.
(Methylsilanetriyl triacetate, Triacetoxethylsilane, Octamethylcyclotetrasiloxane)
Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1759
Proper shipping name : CORROSIVE SOLID, N.O.S.
(Methylsilanetriyl triacetate, Triacetoxethylsilane)
Class : 8
Packing group : III
Labels : 8
ERG Code : 154
Marine pollutant : yes(Octamethylcyclotetrasiloxane)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 3 % / 30.21 g/l

The ingredients of this product are reported in the following inventories:

CA. DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

Canadian lists

No substances are subject to CEPA Section 84 Ministerial Conditions.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version 6.1 Revision Date: 11/12/2025 SDS Number: 10702798-00010 Date of last issue: 06/24/2025
Date of first issue: 10/31/2016

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

SAFETY DATA SHEET

according to the Hazardous Products Regulations



RTV SILICONE SEALANT, School bus yellow, 300 mL

Version	Revision Date:	SDS Number:	Date of last issue: 06/24/2025
6.1	11/12/2025	10702798-00010	Date of first issue: 10/31/2016

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/12/2025
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8