

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

**SECTION 1. IDENTIFICATION**

Product name : HHS GREASE, High-performance grease +PTFE, 246 g  
Product code : 893.1067  
Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Anti-friction agent and lubricant

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Skin irritation : Category 2  
Reproductive toxicity : Category 2  
Specific target organ toxicity : Category 3  
- single exposure  
Simple Asphyxiant : Category 1

**HHS GREASE, High-performance grease  
+PTFE, 246 g**Version  
6.10Revision Date:  
01/25/2023SDS Number:  
10709783-00011Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009**GHS label elements**

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility.  
May displace oxygen and cause rapid suffocation.

Precautionary Statements

: **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
**Storage:**  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).  
**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.**Other hazards**

None known.

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Isobutane	Propane, 2-methyl-	75-28-5	$\geq 30 - < 60$ *
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Naphtha (petroleum), hydrotreated light	92128-66-0	$\geq 10 - < 30$ *
Propane	Dimethylmethane	74-98-6	$\geq 5 - < 10$ *
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Heptane, branched, cyclic and linear	64742-49-0	$\geq 1 - < 5$ *
Butane	Butyl hydride	106-97-8	$\geq 1 - < 5$ *
Distillates (petroleum), hydrotreated heavy paraffinic	Mineral oil, petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	$\geq 1 - < 5$ *
Titanium dioxide	Titanic anhydride	13463-67-7	$\geq 1 - < 5$ *
n-Hexane	Hexyl hydride	110-54-3	$\geq 0.1 - < 1$ *

\* Actual concentration or concentration range is withheld as a trade secret

**Alternative CAS Numbers for some regions**

Chemical name	Alternative CAS Number(s)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility.  
Gas reduces oxygen available for breathing.
- Protection of first-aiders : First Aid responders should pay attention to self-protection,  
and use the recommended personal protective equipment  
when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting  
due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency measures : Evacuate personnel to safe areas.  
Remove all sources of ignition.
-

## HHS GREASE, High-performance grease +PTFE, 246 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

- gency procedures : Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.
- Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing spray.  
Do not swallow.  
Avoid contact with eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

environment.  
Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA	400 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	400 ppm 1,640 mg/m <sup>3</sup>	CA AB OEL
		STEL	500 ppm 2,050 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Mist)	1 mg/m <sup>3</sup>	CA BC OEL
Titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWA (Total dust)	10 mg/m <sup>3</sup>	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	CA BC OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Respirable particulate matter)	2.5 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	0.2 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
n-Hexane	110-54-3	TWA	50 ppm 176 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 176 mg/m <sup>3</sup>	CA QC OEL
		TWA	50 ppm	ACGIH

**This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.**

Titanium dioxide

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
n-Hexane	110-54-3	2,5-Hexanedione	Urine	End of shift	0.5 mg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust venti-

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10	Revision Date: 01/25/2023	SDS Number: 10709783-00011	Date of last issue: 11/15/2022 Date of first issue: 12/23/2009
-----------------	------------------------------	-------------------------------	---

---

lation.

**Personal protective equipment**

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Self-contained breathing apparatus
- Hand protection
- Material : Nitrile rubber
  - Break through time : 480 min
  - Glove thickness : 0.45 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : aerosol
- Propellant : Isobutane, Propane, Butane
- Color : white



**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Odor	:	solvent
Odor Threshold	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	60 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	11 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Density	:	0.773 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	200 °C
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

**Components:****Isobutane:**

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm  
Exposure time: 4 h  
Test atmosphere: gas

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Propane:**

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,800 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

**Titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

**n-Hexane:**

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 31.86 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

**Titanium dioxide:**

Species : Rabbit  
Result : No skin irritation

**n-Hexane:**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Result : No eye irritation

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

---

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

**Titanium dioxide:**

Species : Rabbit  
Result : No eye irritation

**n-Hexane:**

Species : Rabbit  
Result : No eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : Based on data from similar materials

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

**Titanium dioxide:**

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

**n-Hexane:**

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Isobutane:**

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (vapor) Method: OPPTS 870.5395 Result: negative

**Propane:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

---

Result: negative

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

**Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

**n-Hexane:**

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapor)  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 78 weeks  
Method : OECD Test Guideline 451  
Result : negative  
Remarks : Based on data from similar materials

**Titanium dioxide:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.  
This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.



**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

---

**n-Hexane:**

Species : Mouse  
Application Route : inhalation (vapor)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : negative  
Remarks : Based on data from similar materials

**Reproductive toxicity**

Suspected of damaging fertility.

**Components:****Isobutane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

---

Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

**Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the  
reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the  
reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening  
test  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Skin contact  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

**n-Hexane:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Application Route: inhalation (vapor)  
Result: positive

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: inhalation (vapor)  
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

**STOT-single exposure**

May cause drowsiness or dizziness.

**Components:****Isobutane:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

**Propane:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Assessment : May cause drowsiness or dizziness.

**Butane:**

Assessment : May cause drowsiness or dizziness.

**n-Hexane:**

Assessment : May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Components:****n-Hexane:**

Routes of exposure : inhalation (vapor)  
Target Organs : Central nervous system  
Assessment : May cause damage to organs through prolonged or repeated exposure.

**Repeated dose toxicity****Components:****Isobutane:**

Species : Rat  
NOAEL : 9000 ppm

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

---

Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rat  
NOAEL : > 20 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks

**Propane:**

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species : Rat  
NOAEL : 12.47 mg/l  
Application Route : Inhalation  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

**Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
NOAEL : 1,000 mg/kg  
Application Route : Skin contact  
Exposure time : 4 Weeks  
Method : OECD Test Guideline 410  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : > 980 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 4 Weeks

**Titanium dioxide:**

Species : Rat  
NOAEL : 24,000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Species : Rat  
NOAEL : 10 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 y

**n-Hexane:**

Species : Mouse  
LOAEL : 1.76 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks

Species : Rat, male  
NOAEL : 568 mg/kg  
LOAEL : 3,973 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

**Aspiration toxicity**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**n-Hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Experience with human exposure****Components:****n-Hexane:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Central nervous system depression

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

---

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility.
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

---

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.17 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l  
Exposure time: 10 min  
Method: DIN 38 412 Part 8  
Remarks: Based on data from similar materials

**Titanium dioxide:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

**n-Hexane:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.5 mg/l

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version 6.10      Revision Date: 01/25/2023      SDS Number: 10709783-00011      Date of last issue: 11/15/2022  
Date of first issue: 12/23/2009

---

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.88 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 55 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEL (Pseudokirchneriella subcapitata (green algae)): 30 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

**Persistence and degradability****Components:****Isobutane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77.05 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h



**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Remarks: Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**n-Hexane:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Isobutane:**

Partition coefficient: n-  
octanol/water : log Pow: 2.8

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Partition coefficient: n-  
octanol/water : log Pow: 4  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Partition coefficient: n-  
octanol/water : log Pow: > 4  
Remarks: Based on data from similar materials

**Butane:**

Partition coefficient: n-  
octanol/water : log Pow: 2.31

**n-Hexane:**

Partition coefficient: n-  
octanol/water : log Pow: 4

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

**IATA-DGR**

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

ERG Code : 126  
Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION**
**The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

**SECTION 16. OTHER INFORMATION**
**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
 CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
 CA BC OEL : Canada. British Columbia OEL  
 CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
 ACGIH / TWA : 8-hour, time-weighted average  
 ACGIH / STEL : Short-term exposure limit  
 CA AB OEL / TWA : 8-hour Occupational exposure limit  
 CA AB OEL / STEL : 15-minute occupational exposure limit  
 CA BC OEL / TWA : 8-hour time weighted average  
 CA BC OEL / STEL : short-term exposure limit  
 CA QC OEL / TWA EV : Time-weighted average exposure value  
 CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median

**HHS GREASE, High-performance grease  
+PTFE, 246 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
6.10	01/25/2023	10709783-00011	Date of first issue: 12/23/2009

---

Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 01/25/2023  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8