

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

---

**SECTION 1. IDENTIFICATION**

Product name : ZINC-RICH WELD-THRU PRIMER, 460 g  
Product code : 893.109  
Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Solvent-borne coatings

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Specific target organ toxicity : Category 3  
- single exposure  
Specific target organ toxicity : Category 2 (Auditory system)  
- repeated exposure

**GHS label elements**

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
 Date of first issue: 08/06/2012

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe spray.  
 P271 Use only outdoors or in a well-ventilated area.

**Response:**  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
 P314 Get medical attention if you feel unwell.

**Storage:**  
 P405 Store locked up.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

**Disposal:**  
 P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Propane	Dimethylmethane	74-98-6	>= 10 - < 30 *
Butane	Butyl hydride	106-97-8	>= 10 - < 30 *
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	>= 10 - < 30 *
Isobutane	Propane, 2-methyl-	75-28-5	>= 5 - < 10 *

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
 Date of first issue: 08/06/2012

Xylene	Benzene, dimethyl-	1330-20-7	$\geq 5 - < 10$ *
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	No data available	90622-57-4	$\geq 1 - < 5$ *

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
 Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
 Remove contaminated clothing and shoes.  
 Get medical attention.  
 Wash clothing before reuse.  
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
 Get medical attention if symptoms occur.  
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
 Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.  
 Vapors may form explosive mixtures with air.  
 Exposure to combustion products may be a hazard to health.

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

---

If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.
- Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
 Date of first issue: 08/06/2012

- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
 Do not breathe spray.  
 Do not swallow.  
 Avoid contact with eyes.  
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Take precautionary measures against static discharges.  
 Take care to prevent spills, waste and minimize release to the environment.  
 Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Do not pierce or burn, even after use.  
 Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:  
 Self-reactive substances and mixtures  
 Organic peroxides  
 Oxidizing agents  
 Flammable solids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Substances and mixtures which in contact with water emit flammable gases  
 Explosives  
 Gases
- Recommended storage temperature : < 40 °C

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm	CA QC OEL

**ZINC-RICH WELD-THRU PRIMER, 460 g**
Version  
8.4Revision Date:  
01/20/2023SDS Number:  
10773948-00012Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

			1,900 mg/m <sup>3</sup>	
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
n-Butyl acetate	123-86-4	STEL	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL
		TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Xylene	1330-20-7	TWA	100 ppm 434 mg/m <sup>3</sup>	CA AB OEL
		STEL	150 ppm 651 mg/m <sup>3</sup>	CA AB OEL
		TWAEV	100 ppm 434 mg/m <sup>3</sup>	CA QC OEL
		STEV	150 ppm 651 mg/m <sup>3</sup>	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	20 ppm	ACGIH
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	90622-57-4	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g cre-atinine	ACGIH BEI

**Engineering measures**

- : Minimize workplace exposure concentrations.
- If sufficient ventilation is unavailable, use with local exhaust ventilation.
- If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Dust formation may be relevant in the processing of this pro-

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

---

duct. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

**Personal protective equipment**

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Self-contained breathing apparatus
- Hand protection
- Material : butyl-rubber
  - Break through time : ≤ 15 min
  - Glove thickness : 0.7 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety glasses
- Skin and body protection : Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : Aerosol containing a liquefied gas
- Propellant : Propane, Butane, Isobutane
- Color : gray

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

---

Odor : characteristic

Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data available

Initial boiling point and boiling range : -44.5 °C

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 10.9 %(V)

Lower explosion limit / Lower flammability limit : 1.2 %(V)

Vapor pressure : 3,600 hPa (20 °C)

Relative vapor density : Not applicable

Density : 1.561 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 365 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**



## ZINC-RICH WELD-THRU PRIMER, 460 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

---

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

## SECTION 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

**Components:****Propane:**

Acute inhalation toxicity	:	LC50 (Rat): > 800000 ppm Exposure time: 15 min Test atmosphere: gas
---------------------------	---	---

**Butane:**

Acute inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	---	--

**n-Butyl acetate:**

## ZINC-RICH WELD-THRU PRIMER, 460 g

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

---

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Isobutane:**

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm  
Exposure time: 4 h  
Test atmosphere: gas

**Xylene:**

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Remarks: Based on data from similar materials

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****n-Butyl acetate:**

Species : Rabbit  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

**Xylene:**

Species : Rabbit  
Result : Skin irritation

## ZINC-RICH WELD-THRU PRIMER, 460 g

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

---

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Species : Rabbit  
Result : Mild skin irritation  
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.  
Remarks : Based on data from similar materials

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****n-Butyl acetate:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**Xylene:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****n-Butyl acetate:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**Xylene:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Result : negative

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Test Type : Maximization Test  
Routes of exposure : Skin contact

## ZINC-RICH WELD-THRU PRIMER, 460 g

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

---

Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Propane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

**Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Isobutane:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Xylene:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

## ZINC-RICH WELD-THRU PRIMER, 460 g

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

---

Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-  
malian cells  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Skin contact  
Result: negative

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro sister chromatid exchange assay in mam-  
malian cells  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Components:****Xylene:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative

**Reproductive toxicity**

Not classified based on available information.

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

---

**Components:****Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**n-Butyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OECD Test Guideline 416  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Isobutane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test

## ZINC-RICH WELD-THRU PRIMER, 460 g

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

---

Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Xylene:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

**STOT-single exposure**

May cause drowsiness or dizziness.

**Components:****Propane:**

Assessment : May cause drowsiness or dizziness.

**Butane:**

Assessment : May cause drowsiness or dizziness.

**n-Butyl acetate:**

Assessment : May cause drowsiness or dizziness.

**Isobutane:**

Assessment : May cause drowsiness or dizziness.

**Xylene:**

Assessment : May cause respiratory irritation.

**STOT-repeated exposure**

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

**Components:****Xylene:**

Routes of exposure : inhalation (vapor)

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

---

Target Organs : Auditory system  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

**Repeated dose toxicity****Components:****Propane:**

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**n-Butyl acetate:**

Species : Rat  
NOAEL : 2.4 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 90 Days

**Isobutane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Xylene:**

Species : Rat  
LOAEL : > 0.2 - 1 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

Species : Rat  
LOAEL : 150 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Species : Rat  
NOAEL : > 1 mg/l  
Application Route : inhalation (vapor)



**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

---

Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials
Species	:	Rat
NOAEL	:	> 300 mg/kg
Application Route	:	Ingestion
Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials

**Aspiration toxicity**

Not classified based on available information.

**Components:****Xylene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****n-Butyl acetate:**

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 18 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia sp. (Water flea)): 44 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials  NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 23.2 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	IC50 (Tetrahymena pyriformis): 356 mg/l

## ZINC-RICH WELD-THRU PRIMER, 460 g

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

---

Exposure time: 40 h

**Xylene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l  
Exposure time: 35 d  
Method: OECD Test Guideline 210  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version 8.4      Revision Date: 01/20/2023      SDS Number: 10773948-00012      Date of last issue: 08/12/2022  
Date of first issue: 08/06/2012

---

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 1 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211

**Persistence and degradability****Components:****Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**n-Butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

**Isobutane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Xylene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics:**

Biodegradability : Result: Not readily biodegradable.  
Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Butane:**

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

---

Partition coefficient: n-octanol/water : log Pow: 2.31

**n-Butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3

**Isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2.8

**Xylene:**

Partition coefficient: n-octanol/water : log Pow: 3.16  
Remarks: Calculation

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

**IATA-DGR**

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1

---

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

---

Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS (Zinc)  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : yes(Zinc)

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION**

**Volatile organic compounds (VOC) content** : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 50.17 %

**The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

---

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>
--	---	---

Revision Date	:	01/20/2023
Date format	:	mm/dd/yyyy

**ZINC-RICH WELD-THRU PRIMER, 460 g**

Version	Revision Date:	SDS Number:	Date of last issue: 08/12/2022
8.4	01/20/2023	10773948-00012	Date of first issue: 08/06/2012

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8