

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4 Revision Date: 06/08/2023 SDS Number: 10778160-00010 Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

SECTION 1. IDENTIFICATION

Product name : LACQUER SPRAY, Gloss White-Aluminum, 462 g
Product code : 893.339006
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Paints

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Eye irritation : Category 2A
Reproductive toxicity : Category 2

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4 Revision Date: 06/08/2023 SDS Number: 10778160-00010 Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

Specific target organ toxicity : Category 3
- single exposure

Specific target organ toxicity : Category 2 (Auditory system)
- repeated exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4 Revision Date: 06/08/2023 SDS Number: 10778160-00010 Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

disposal plant.

Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Acetone	2-Propanone	67-64-1	$\geq 30 - < 60$ *
Butane	Butyl hydride	106-97-8	$\geq 10 - < 30$ *
Propane	Dimethylmethane	74-98-6	$\geq 10 - < 30$ *
Isobutane	Propane, 2-methyl-	75-28-5	$\geq 10 - < 30$ *
n-Butyl acetate	Acetic acid, butyl ester	123-86-4	$\geq 1 - < 5$ *
2-Methoxy-1-methylethyl acetate	Methoxyisopropyl acetate	108-65-6	$\geq 1 - < 5$ *
Ethanol	Ethyl alcohol	64-17-5	$\geq 1 - < 5$ *
Xylene	Benzene, dimethyl-	1330-20-7	$\geq 1 - < 5$ *
Butyl glycollate	Acetic acid, 2-hydroxy-, butyl ester	7397-62-8	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4	Revision Date: 06/08/2023	SDS Number: 10778160-00010	Date of last issue: 11/15/2022 Date of first issue: 12/23/2009
-----------------	------------------------------	-------------------------------	---

- | | | |
|---|---|--|
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : | Prolonged or repeated contact may dry skin and cause irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure. |
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| Notes to physician | : | Treat symptomatically and supportively. |
-

SECTION 5. FIRE-FIGHTING MEASURES

- | | | |
|--|---|---|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | None known. |
| Specific hazards during fire fighting | : | Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
| Hazardous combustion products | : | Carbon oxides
Nitrogen oxides (NO _x) |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. |
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|--|
| Personal precautions, protective equipment and emergency procedures | : | Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal pro- |
|---|---|--|

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

ective equipment recommendations (see section 8).

- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**
Version
11.4Revision Date:
06/08/2023SDS Number:
10778160-00010Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases

Recommended storage temperature : < 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m ³	CA AB OEL
		STEL	750 ppm 1,800 mg/m ³	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWAEV	500 ppm 1,190 mg/m ³	CA QC OEL
		STEV	1,000 ppm 2,380 mg/m ³	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
Isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
n-Butyl acetate	123-86-4	STEL	200 ppm	CA AB OEL

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**
Version
11.4Revision Date:
06/08/2023SDS Number:
10778160-00010Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

			950 mg/m ³	
		TWA	150 ppm 713 mg/m ³	CA AB OEL
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWA	50 ppm 270 mg/m ³	CA ON OEL
Ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m ³	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		STEV	1,000 ppm	CA QC OEL
		STEL	1,000 ppm	ACGIH
Xylene	1330-20-7	TWA	100 ppm 434 mg/m ³	CA AB OEL
		STEL	150 ppm 651 mg/m ³	CA AB OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	150 ppm 651 mg/m ³	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Xylene	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4	Revision Date: 06/08/2023	SDS Number: 10778160-00010	Date of last issue: 11/15/2022 Date of first issue: 12/23/2009
-----------------	------------------------------	-------------------------------	---

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Self-contained breathing apparatus
- Hand protection
- Material : butyl-rubber
 - Break through time : <= 15 min
 - Glove thickness : 0.7 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Propellant : Propane, Butane, Isobutane

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

Color	:	colored
Odor	:	characteristic
Odor Threshold	:	No data available
pH	:	Solvent mixture; pH value determination not possible, no aqueous solution
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-44.5 °C
Flash point	:	< 0 °C Flash point is only valid for liquid portion in the aerosol can.
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	13 %(V)
Lower explosion limit / Lower flammability limit	:	1.7 %(V)
Vapor pressure	:	3,600 hPa (20 °C)
Relative vapor density	:	Not applicable
Density	:	No data available
Solubility(ies) Water solubility	:	partly miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	365 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4	Revision Date: 06/08/2023	SDS Number: 10778160-00010	Date of last issue: 11/15/2022 Date of first issue: 12/23/2009
-----------------	------------------------------	-------------------------------	---

Oxidizing properties : The substance or mixture is not classified as oxidizing.
Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Extremely flammable aerosol.
Vapors may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.
Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method
Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method
Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Acetone:**

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg
Acute inhalation toxicity : LC50 (Rat): 76 mg/l

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4 Revision Date: 06/08/2023 SDS Number: 10778160-00010 Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

Isobutane:

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

2-Methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC0 (Rat): 9.48 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Ethanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Xylene:

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Butyl glycollate:

Acute oral toxicity : LD50 (Rat): 4,595 mg/kg

Acute inhalation toxicity : LC0 (Rat): \geq 6.2 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

Not classified based on available information.

Components:**Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

2-Methoxy-1-methylethyl acetate:

Species : Rabbit
Result : No skin irritation

Ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Xylene:

Species : Rabbit
Result : Skin irritation

Butyl glycollate:

Species : Rabbit
Result : No skin irritation

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Acetone:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

n-Butyl acetate:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

2-Methoxy-1-methylethyl acetate:

Species	:	Rabbit
Result	:	No eye irritation

Ethanol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

Xylene:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Butyl glycollate:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Acetone:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

n-Butyl acetate:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

2-Methoxy-1-methylethyl acetate:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Ethanol:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

Xylene:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

Butyl glycollate:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Acetone:**

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
-----------------------	---

Test Type: Bacterial reverse mutation assay (AMES) Result: negative
--

Test Type: Chromosome aberration test in vitro Result: negative
--

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse
----------------------	--

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4 Revision Date: 06/08/2023 SDS Number: 10778160-00010 Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

Application Route: Ingestion
Result: negative

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4	Revision Date: 06/08/2023	SDS Number: 10778160-00010	Date of last issue: 11/15/2022 Date of first issue: 12/23/2009
-----------------	------------------------------	-------------------------------	---

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Ingestion
Result: equivocal

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Butyl glycollate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Mouse Lymphoma

Method: OECD Test Guideline 476

Result: negative

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4 Revision Date: 06/08/2023 SDS Number: 10778160-00010 Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

Carcinogenicity

Not classified based on available information.

Components:**Acetone:**

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

2-Methoxy-1-methylethyl acetate:

Species : Rat
Application Route : inhalation (vapor)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:**Acetone:**

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Application Route: inhalation (gas)

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4 Revision Date: 06/08/2023 SDS Number: 10778160-00010 Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

Method: OECD Test Guideline 422
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

2-Methoxy-1-methylethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4	Revision Date: 06/08/2023	SDS Number: 10778160-00010	Date of last issue: 11/15/2022 Date of first issue: 12/23/2009
-----------------	------------------------------	-------------------------------	---

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Butyl glycollate:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Acetone:**

Assessment : May cause drowsiness or dizziness.

Butane:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

Isobutane:

Assessment : May cause drowsiness or dizziness.

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

2-Methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:**Xylene:**

Routes of exposure	:	inhalation (vapor)
Target Organs	:	Auditory system
Assessment	:	Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity**Components:****Acetone:**

Species	:	Rat
NOAEL	:	900 mg/kg
LOAEL	:	1,700 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

Species	:	Rat
NOAEL	:	45 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	8 Weeks

Butane:

Species	:	Rat
NOAEL	:	9000 ppm
Application Route	:	inhalation (gas)
Exposure time	:	6 Weeks
Method	:	OECD Test Guideline 422

Propane:

Species	:	Rat
NOAEL	:	7.214 mg/l

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4 Revision Date: 06/08/2023 SDS Number: 10778160-00010 Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

n-Butyl acetate:

Species : Rat
NOAEL : 2.4 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days

2-Methoxy-1-methylethyl acetate:

Species : Rat
NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 41 - 45 Days
Method : OECD Test Guideline 422

Species : Mouse
NOAEL : 1.62 mg/l
Application Route : inhalation (vapor)
Exposure time : 2 y
Remarks : Based on data from similar materials

Species : Rabbit
NOAEL : > 1,838 mg/kg
Application Route : Skin contact
Exposure time : 90 Days
Remarks : Based on data from similar materials

Ethanol:

Species : Rat
NOAEL : 1,280 mg/kg
LOAEL : 3,156 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Xylene:

Species : Rat
LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Butyl glycollate:

Species : Rat
NOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 29 Days
Method : OECD Test Guideline 407

Aspiration toxicity

Not classified based on available information.

Components:**Acetone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Acetone:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): \geq 79 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 61,150 mg/l
Exposure time: 30 min
Method: ISO 8192

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

n-Butyl acetate:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (Water flea)): 44 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23.2 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials
- Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

2-Methoxy-1-methylethyl acetate:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (algae)): > 1,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 100 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC10: > 1,000 mg/l
Exposure time: 0.5 h

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

Ethanol:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia (water flea)): > 1,000 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l
Exposure time: 72 h
- EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l
Exposure time: 72 h
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 9.6 mg/l
Exposure time: 9 d
- Toxicity to microorganisms : EC50 (Pseudomonas putida): 6,500 mg/l
Exposure time: 16 h

Xylene:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials
- Toxicity to microorganisms : NOEC: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Butyl glycolate:

- Toxicity to fish : LC0 (Leuciscus idus (Golden orfe)): >= 50 mg/l
Exposure time: 48 h
Method: DIN 38412

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 280 mg/l
Exposure time: 24 h
Method: DIN 38412

Toxicity to algae/aquatic plants : EC10 (Lemna gibba (gibbous duckweed)): > 87.4 mg/l
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): 2,320 mg/l
Exposure time: 18 h

Persistence and degradability**Components:****Acetone:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Butane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4 Revision Date: 06/08/2023 SDS Number: 10778160-00010 Date of last issue: 11/15/2022
Date of first issue: 12/23/2009

Ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 84 %
Exposure time: 20 d

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Butyl glycollate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential**Components:****Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

Butane:

Partition coefficient: n-octanol/water : log Pow: 2.31

Isobutane:

Partition coefficient: n-octanol/water : log Pow: 2.8

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

2-Methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.2

Ethanol:

Partition coefficient: n-octanol/water : log Pow: -0.35

Xylene:

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version 11.4	Revision Date: 06/08/2023	SDS Number: 10778160-00010	Date of last issue: 11/15/2022 Date of first issue: 12/23/2009
-----------------	------------------------------	-------------------------------	---

Partition coefficient: n-
octanol/water : log Pow: 3.16
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation
TDG

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS

Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
ERG Code	:	126
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION
The ingredients of this product are reported in the following inventories:

DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	---	--

SECTION 16. OTHER INFORMATION
Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

Revision Date	:	06/08/2023
Date format	:	mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their

**LACQUER SPRAY, Gloss White-Aluminum,
462 g**

Version	Revision Date:	SDS Number:	Date of last issue: 11/15/2022
11.4	06/08/2023	10778160-00010	Date of first issue: 12/23/2009

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8