

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

SECTION 1. IDENTIFICATION

Product name : MOLY 50S, Anti-seize grease, 284 g
Product code : 893.923290
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : +1 (905) 564 6225
Telefax : +1 (905) 564 3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Anti-friction agent and lubricant
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

|| No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	No data available	64742-52-5	$\geq 30 - < 60$ *
Graphite	Graphitic carbon	7782-42-5	$\geq 10 - < 30$ *
Molybdenum sulfide	Molybdenum bisulfide	1317-33-5	$\geq 10 - < 30$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/19/2022
5.0	06/23/2024	10652560-00007	Date of first issue: 07/02/2012

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

Recommended storage temperature : 4 - 29 °C

Storage period : 120 Months

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Graphite	7782-42-5	TWA (Respirable)	2 mg/m ³	CA BC OEL
		TWAEV (respirable dust)	2 mg/m ³	CA QC OEL
		TWA (Respirable)	2 mg/m ³	CA AB OEL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		Molybdenum sulfide	1317-33-5	TWA (Total)
TWA (Respirable)	3 mg/m ³ (Molybdenum)			CA AB OEL
TWAEV (inhalable dust)	10 mg/m ³ (Molybdenum)			CA QC OEL
TWAEV (respirable dust)	3 mg/m ³ (Molybdenum)			CA QC OEL
TWA (Inhalable)	10 mg/m ³ (Molybdenum)			CA BC OEL
TWA (Respirable)	3 mg/m ³ (Molybdenum)			CA BC OEL
TWA (Inhalable particulate matter)	10 mg/m ³ (Molybdenum)			ACGIH

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

		late matter)		
		TWA (Respirable particulate matter)	3 mg/m ³ (Molybdenum)	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection
Material : butyl-rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : black

Odor : mild

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : 316 °C

Flash point : 177 °C
Method: closed cup

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : Not applicable

Lower explosion limit / Lower flammability limit : Not applicable

Vapor pressure : < 0.1 Pa (21 °C)

Relative vapor density : Not applicable

Density : 1.4 g/cm³

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : Not applicable

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

SECTION 10. STABILITY AND REACTIVITY

- Reactivity : Not classified as a reactivity hazard.
- Chemical stability : Stable under normal conditions.
- Possibility of hazardous reactions : Can react with strong oxidizing agents.
- Conditions to avoid : None known.
- Incompatible materials : Oxidizing agents
- Hazardous decomposition products : No hazardous decomposition products are known.
-

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Graphite:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Molybdenum sulfide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Graphite:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Molybdenum sulfide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Graphite:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

Molybdenum sulfide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Graphite:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Molybdenum sulfide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

Result: negative
Remarks: Based on data from similar materials

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Molybdenum sulfide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

Reproductive toxicity

Not classified based on available information.

Components:

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Molybdenum sulfide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rat
NOAEL : > 0.98 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

Graphite:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version 5.0 Revision Date: 06/23/2024 SDS Number: 10652560-00007 Date of last issue: 11/19/2022
Date of first issue: 07/02/2012

Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Molybdenum sulfide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : EC10 (Oncorhynchus mykiss (rainbow trout)): > 1 mg/l
Exposure time: 78 d
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 1 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC (activated sludge): > 100 mg/l
Exposure time: 17 d
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/19/2022
5.0	06/23/2024	10652560-00007	Date of first issue: 07/02/2012

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- | | | |
|------------------------|---|---|
| Waste from residues | : | Do not dispose of waste into sewer. |
| | | Dispose of in accordance with local regulations. |
| Contaminated packaging | : | Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product. |
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content	CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products VOC content: < 0.1 %
---	---

The ingredients of this product are reported in the following inventories:

DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/19/2022
5.0	06/23/2024	10652560-00007	Date of first issue: 07/02/2012

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



MOLY 50S, Anti-seize grease, 284 g

Version	Revision Date:	SDS Number:	Date of last issue: 11/19/2022
5.0	06/23/2024	10652560-00007	Date of first issue: 07/02/2012

Data Sheet [cy, http://echa.europa.eu/](http://echa.europa.eu/)

Revision Date : 06/23/2024
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8